



New cultured ledgerstone sections



New cultured ledgerstone sections



New cultured ledgerstone sections

New cultured ledgerstone sections



New cultured ledgerstone sections



New cultured ledgerstone sections



New cultured ledgerstone sections

New cultured ledgerstone sections



## STONE VENEER SPECIFICATION DATA

### 1. MANUFACTURER:

Prestige Stone Products LLC.  
9290 Winesburg Road  
Dundee, OH 44624  
Phone: 330.439.5318 Fax: 330.439.5319  
e-mail: [sales.prestigestone@gmail.com](mailto:sales.prestigestone@gmail.com)  
Web: [www.prestigestoneproducts.com](http://www.prestigestoneproducts.com)

### 2. PRODUCT DESCRIPTION:

#### \*BASIC USE\*

Prestige Stone Products veneer stone is a lightweight concrete facade designed for use on exterior or interior walls. The product is not intended for structural use, and because it is a lightweight product, does not require any additional footings. Veneer or manufactured stone may be applied to almost any load bearing wall, wood frame, steel, or masonry.

#### \*COMPOSITION AND MATERIALS\*

Prestige Stone Products are produced from a combination of Portland cement, lightweight aggregates, and permanent mineral oxide colors. The products are manufactured in molds which are produced from natural stone.

#### \*PRODUCTS\*

Stone Veneer – Corners and Flats in nine styles  
Hearthstone – One style  
Window Trim, Sills and Rowlocks – six styles  
Keystones – Two styles  
Wall caps and Pier caps – Two styles in various sizes  
Utility Pieces – Light Blocks, Receptacle Blocks, Water Hydrant Blocks, Brick Accessories, Brick Window Sills, and Brick Window Trim.

#### \*SIZES AND SHAPES\*

Prestige Stone will vary in size and shape. See the company's current literature for detailed information on the size of each stone product. Stone thickness will vary from 1" - 2" ( 25.4 - 51 mm )

### 3. TECHNICAL DATA

Compression Strength – In accordance ASTM C39 - 5695 PSI  
Absorption – ASTM C1195 - 14.7%  
Split Tensile Test ASTM C496 - 499 PSI  
Freeze / Thaw - ( C67 ) No disintegration and less than 1% weight loss  
Thickness – 1"- 2"  
Fire Rating - Zero flame spread, Zero smoke developed, Zero fuel contributed  
Color retention – Permanent mineral oxide color  
Veneer Unit Weight – 12 to 15 lbs. Installed