



**Christ Community Chapel**  
**Site Information**  
**City of Hudson Planning Commission Application**

Total Area of Site	28.596 acres (1,245,642 square feet)
Total Impervious Cover	78,307 square feet buildings 364,749 square feet pavement and walkways 44,500 square feet turf field 487,556 square feet total impervious cover
Percentage of Site Covered by Impervious Cover	39%
Total Building Coverage	78,307 square feet
Floor Area to Lot Area Ratio	0.0628
Gross Floor Area	78,307 square feet
% Total of Undisturbed Land with a Breakdown by Use	657,107 square feet of open space and woods
Proposed Use and Square Footage for Each Use within Each Structure on Site	Restroom Building - 398 square feet
Number of Stories	One
Actual Height	Restroom Building - 12'-8"
Finished Floor Elevation	1016.22
Foundation Type	CMU Foundations
Total Square Footage for Building and for Each Floor	See Above - Single Story Building Proposed

C:\DC\ACD\at\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\03-CIVIL\PLAN\LOT\Major Site Plans\765295 COVER SHEET.dwg - 5/21/2025 - Jake McDaniel

OWNER/DEVELOPER:  
CHRIST COMMUNITY CHAPEL  
750 W. STREETSBORO STREET  
HUDSON, OH 44236  
PHONE: (330) 650-9533  
CONTACT: JIMMY KOZY

ARCHITECT:  
SOL HARRIS DAY  
6677 FRANK AVE NW NORTH  
CANTON, OH 44720  
PHONE: (330) 493-3722  
CONTACT: JULIE ZIGA  
EMAIL: JZIGA@SOLHARRISDAY.COM

ENGINEER:  
CESO, INC.  
175 MONTROSE WEST AVE, SUITE 400  
AKRON, OH 44321  
PHONE: (234) 349-2514  
CONTACT: HANNAH OKES, PE  
EMAIL: HANNAH.OKES@CESOINC.COM

GOVERNING AGENCIES AND UTILITY COMPANIES

SEWER:  
SUMMIT COUNTY DEPARTMENT OF  
SANITARY SEWER SERVICES  
RUSSELL M. PRY BUILDING  
1180 SOUTH MAIN STREET, SUITE 201  
AKRON, OH 44301  
PHONE: (330) 926-2405

GAS SERVICE:  
ENBRIDGE GAS  
PHONE: 1-800-362-7557

WATER:  
CITY OF HUDSON PUBLIC WORKS  
1769 GEORGETOWN ROAD  
HUDSON, OH 44236  
PHONE: (330) 342-1750

ELECTRIC:  
CITY OF HUDSON PUBLIC WORKS  
HUDSON PUBLIC POWER  
1769 GEORGETOWN ROAD  
HUDSON, OH 44236  
PHONE: (330) 342-1750

STORMWATER:  
HUDSON PUBLIC WORKS DEPARTMENT  
1769 GEORGETOWN ROAD  
HUDSON, OH 44236  
PHONE: (330) 342-1750

ZONING:  
CITY OF HUDSON  
1140 TEREX ROAD  
HUDSON, OH 44236  
PHONE: (330) 342-1790

PROPERTY DATA:

PARCEL OWNER: HUDSON COMMUNITY CHAPEL

PARCEL INFO - LOTS 31 &41 PER SUMMIT COUNTY		AREA OUTSIDE OF ROW
3009095	10.86 AC	9.9690 AC
3009094	4.76 AC	4.9441AC
3007723	14.45 AC	13.6829 AC

ADDRESS: 750 W. STREETSBORO STREET  
HUDSON, OH 44236

LOT COVERAGE:  
TOTAL AREA OF SITE: 28.596 ACRES

	EXISTING-BUILDING	PROPOSED-BUILDING
TOTAL BUILDING COVERAGE:	66,464 SF (CHURCH) 960 SF (GARAGE)	398 SF (RESTROOM)

FLOOR AREA TO LOT AREA RATIO:  
GROSS FLOOR AREA: 67,822 / (28.596\*43,560)=0.0544=5.44%  
66,464+960+398=67,822 SF

IMPERVIOUS COVERAGE: TOTAL BUILDING (67,822 SF) + TURF SOCCER FIELD (44,500 SF) +  
SIDEWALKS/PAVEMENT (364,749 SF) = 477,071 SF

IMPERVIOUS TO LOT AREA RATIO: 477,071 / (28.596\*43,560)=0.3829=38.29%

UNDISTURBED LAND BY USE:  
EX. BUILDINGS 66,464 SF (CHURCH) +960 SF (GARAGE) = 67,424 SF  
EX. PAVEMENT & WALKS 349,920 SF  
OPEN SPACE & WOODS 657,107 SF

ZONING: DISTRICT 1: SUBURBAN RESIDENTIAL NEIGHBORHOOD  
ADJACENT ZONING NORTH & WEST: 6. WESTERN HUDSON GATEWAY  
ADJACENT ZONING EAST: 1. SUBURBAN RESIDENTIAL DISTRICT

EXISTING USE: CHURCH CAMPUS / PLACE OF WORSHIP

PROPOSED USE: PROPOSED TURF FIELD & RESTROOM BUILDING

BUILDING SETBACKS	REQUIRED	EXISTING	PROPOSED
FRONTAGE ALONG STREET:	100'	N/A	349' OFF STREETSBORO RD
SIDE:	50'	N/A	362'
REAR:	50'	N/A	776'

PARKING:  
TOTAL EXISTING PARKING SPACES: 898 TOTAL PROPOSED PARKING SPACES: 897  
ADA PARKING SPACES: 43

FLOODPLAIN DESIGNATION: PARCEL IS LOCATED WITHIN "ZONE X" (AREA OF MINIMAL FLOOD HAZARD) AS INDICATED BY THE FLOOD  
INSURANCE RATE MAP (FIRM) COMMUNITY PANEL NUMBER 39153C0126E, EFFECTIVE DATE: 7/20/2009;  
PUBLISHED BY THE FEDERAL EMERGENCY MANAGEMENT AGENCY.

CITY OF HUDSON, SUMMIT COUNTY, OHIO  
SITE IMPROVEMENT PLANS  
FOR  
CHRIST COMMUNITY CHAPEL  
750 W. STREETSBORO STREET  
HUDSON, OHIO 44236



VICINITY MAP  
NOT TO SCALE

Sheet List Table	
Sheet Number	Sheet Title
C1.0	COVER SHEET
C2.0	GENERAL NOTES
C3.0	DEMOLITION PLAN
C4.0	OVERALL SITE
C4.1	FIELD SITE AND PAVEMENT PLAN
C5.0	OVERALL GRADING PLAN
C5.1	FIELD GRADING PLAN
C5.2	DETENTION DETAIL
C6.0	SWPPP NOTES & DETAILS
C6.1	SWPPP DETAILS
C6.2	SWPPP PHASE 1
C6.3	SWPPP PHASE 2
C6.4	SWPPP PHASE 3
C7.0	OVERALL UTILITY PLAN
C7.1	FIELD UTILITY PLAN
C7.2	FORCEMAIN PROFILE
C8.0	CONSTRUCTION DETAILS
C8.1	WATER DETAILS
C8.2	WATER DETAILS
C8.3	WATER DETAILS
C8.4	STORM DETAILS
C8.5	STORM DETAILS
C8.6	STORM DETAILS
C8.7	SANITARY - DSSS-STANDARDS
C8.8	SANITARY DETAILS
C8.9	SANITARY DETAILS
C8.10	GRINDER PUMP DETAILS
C8.11	FIELD DETAILS
L1.0	LANDSCAPE PLAN - NORTH
L1.1	LANDSCAPE PLAN - SOUTH
L1.2	LANDSCAPE DETAILS & NOTES

SURVEY BY DIEBEL SURVEYING INC.		DATE
1 OF 2	ALTAINSPS LAND TITLE SURVEY	7/19/2024
2 OF 2	ALTAINSPS LAND TITLE SURVEY	7/19/2024
1 OF 1	EXISTING TREE SITE PLAN	1/23/2025

PROJECT NO. 240628

ODOT STANDARD CONSTRUCTION DRAWINGS

ODOT HW-2.1 - HALF HEIGHT HEADWALL  
ODOT MH-1 - MANHOLE NO. 1



FORTY- EIGHT (48) HOURS  
BEFORE DIGGING IS TO  
COMMENCE, THE CONTRACTORS  
SHALL NOTIFY THE FOLLOWING  
AGENCIES: OHIO UTILITIES  
PROTECTION SERVICE AT 811 OR  
800-362-2764 AND ALL OTHER  
AGENCIES WHICH MIGHT HAVE  
UNDERGROUND UTILITIES  
INVOLVING THIS PROJECT AND  
ARE NONMEMBERS OF STATE  
UTILITIES PROTECTION SERVICE



CESO  
WWW.CESOINC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: N/A

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET

Drawing Title:

COVER SHEET

C1.0



GENERAL NOTES

DEMOLITION NOTES

1.

THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS REQUIRED FOR DEMOLITION AND DISPOSAL. THE DEMOLITION, REMOVAL, AND DISPOSAL IS TO BE APPROVED BY ALL GOVERNING AUTHORITIES, OF ALL FACILITIES SUCH AS: STRUCTURES, PADS, WALLS, FLUMES, FOUNDATIONS, PARKING, DRIVES, DRAINAGE, STRUCTURES, UTILITIES, WELLS, ETC., SUCH THAT THE IMPROVEMENTS SHOWN ON THE REMAINING PLANS CAN BE CONSTRUCTED. ALL FACILITIES TO BE REMOVED SHALL BE UNDERCUT TO SUITABLE MATERIAL AND BROUGHT TO GRADE WITH SUITABLE COMPACTED FILL MATERIAL AS SPECIFIED BY A QUALIFIED PROFESSIONAL GEOTECHNICAL ENGINEER. IF UNDOCUMENTED FACILITIES ARE FOUND ON SITE, CONTRACTOR SHALL CONTACT THE OWNER AND UTILITY COMPANY PRIOR TO REMOVAL. ALL FACILITIES SHALL BE PLUGGED, ABANDONED, OR REMOVED PER STATE AND LOCAL REQUIREMENTS.
2.

FEDERAL, STATE AND LOCAL CODE REQUIREMENTS SHALL GOVERN THE DISPOSAL OF DEBRIS INCLUDING ANY POTENTIALLY HAZARDOUS AND TOXIC MATERIALS. ALL MATERIALS AND STRUCTURES DESIGNATED AS "TO BE REMOVED" SHALL BE DISPOSED OF OFF SITE AND AT THE COST OF THE CONTRACTOR.
3.

THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING JOB SITE SAFETY PER OSHA REQUIREMENTS AT ALL TIMES.
4.

PRIOR TO DEMOLITION, IT IS THE CONTRACTOR'S RESPONSIBILITY TO CALL THE STATE 811 AND NOTIFY ALL UTILITY COMPANIES TO SCHEDULE UTILITY SERVICE REMOVAL AND/OR ABANDONMENT. ALL UTILITIES SHALL BE REMOVED/RELOCATED PER THE SPECIFICATIONS OF THE UTILITY COMPANIES. THE CONTRACTOR IS RESPONSIBLE TO PAY ALL FEES AND CHARGES ASSOCIATED WITH THIS WORK
5.

CONTRACTOR SHALL MAINTAIN ALL UTILITY SERVICES TO INHABITED BUILDINGS ON SITE AND ADJACENT PROPERTIES AT ALL TIMES. INTERRUPTIONS SHALL BE APPROVED BY THE OWNERS OF THE BUILDINGS/PROPERTIES.
6.

THE LOCATIONS OF ALL EXISTING UTILITIES SHOWN ON THIS PLAN HAVE BEEN DETERMINED FROM THE BEST INFORMATION AVAILABLE AND ARE GIVEN FOR THE CONVENIENCE OF THE CONTRACTOR. THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THEIR ACCURACY. PRIOR TO THE START OF ANY DEMOLITION ACTIVITY, THE CONTRACTOR SHALL NOTIFY THE UTILITY COMPANIES FOR ONSITE LOCATIONS OF EXISTING UTILITIES. IF THE LOCATION OR ELEVATION OF THE EXISTING UTILITIES ARE FOUND TO BE DIFFERENT FROM THE PLANS, CONTRACTOR SHALL CONTACT THE ENGINEER IMMEDIATELY.
7.

CONTRACTOR SHALL PROTECT EXISTING SITE FEATURES TO REMAIN INSIDE AND OUTSIDE CONSTRUCTION LIMITS. CONTRACTOR IS RESPONSIBLE TO DOCUMENT ALL EXISTING DAMAGES AND NOTIFY THE CITY/COUNTY PRIOR TO CONSTRUCTION START. ANY EXISTING SITE FEATURE TO REMAIN THAT IS DAMAGED DURING CONSTRUCTION, SUCH AS, BUT NOT LIMITED TO, DRAINAGE, UTILITIES, PAVEMENT, CURB, ETC. SHALL BE REPAIRED TO A CONDITION THAT IS EQUAL TO, OR BETTER THAN, THE EXISTING CONDITIONS. PRIOR TO BEING DAMAGED, THE CONTRACTOR IS RESPONSIBLE FOR REPAIRING ANY DAMAGE TO THE SATISFACTION OF THE OWNER AT NO ADDITIONAL COST.
8.

CONTINUOUS ACCESS SHALL BE MAINTAINED TO THE SURROUNDING PROPERTIES AT ALL TIMES DURING DEMOLITION OF THE EXISTING FACILITIES.
9.

THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING TRAFFIC CONTROL. ALL TRAFFIC CONTROL MEASURES SHALL BE IN ACCORDANCE WITH STATE DEPARTMENT OF TRANSPORTATION REGULATIONS AND LOCAL REGULATIONS.
10.

THE CONTRACTOR IS RESPONSIBLE FOR PLACING AND MAINTAINING CONSTRUCTION FENCE, SIGNS, ETC. TO WARN AND KEEP UNAUTHORIZED PEOPLE OFF SITE FOR THE DURATION OF THE PROJECT.
11.

PRIOR TO DEMOLITION, ALL EROSION CONTROL DEVICES ARE TO BE INSTALLED PER THE GOVERNING AGENCIES GUIDELINES AND STANDARDS. DUST CONTROL SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
12.

SAWCUT LINE PROVIDED IS FOR REFERENCE ONLY. CONTRACTOR WILL BE RESPONSIBLE FOR DETERMINING THE EXTENT OF THE SAWCUT THAT WILL BE REQUIRED AS WELL AS PAVEMENT REPAIRS TO INSTALL UTILITY TRENCHING. IF ANY DAMAGE OCCURS ON ANY OF THE SURROUNDING PAVEMENT, ETC. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ITS REMOVAL AND REPAIR. THE CONTRACTOR IS RESPONSIBLE FOR REMOVING THAT WHICH IS NECESSARY TO COMPLETE THE INTENT OF THE PROPOSED IMPROVEMENTS. SAWCUT EXISTING PAVEMENT TO FULL DEPTH, USING CARE TO CUT NEAT, STRAIGHT LINES. CUT AT EXISTING JOINTS WHERE POSSIBLE.
13.

THE CONTRACTOR SHALL MAINTAIN A WELL-DRAINED SITE, FREE OF STANDING WATER DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR TEMPORARY DRAINAGE MEASURES DURING CONSTRUCTION.
14.

IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO STUDY THE PLANS AND VISIT THE SITE TO DETERMINE THE ITEMS THAT MUST BE REMOVED TO COMPLY WITH THE SITE DEVELOPMENT PLANS. NO EXTRA FEE WILL BE PAID FOR THE REMOVAL OF ANY ITEM NOT LISTED THAT IS VISIBLE UPON A SITE VISIT. THE DEMOLITION PLAN IS INTENDED TO PRESENT THE SCOPE OF THE DEMOLITION, AND DOES NOT GUARANTEE THAT ALL ITEMS ARE ADDRESSED.
15.

THE CONTRACTOR SHALL OBTAIN ALL PERMITS FOR ALL SITE DEVELOPMENT WORK, PAY ALL FEES FOR PERMITS AND CHECK ALL GOVERNING AUTHORITIES' SPECIFICATIONS FOR BUT NOT LIMITED TO, GUTTERS, SIDEWALKS, POLES, AND OTHER STRUCTURES, INCLUDING THE REMOVAL OR RELOCATION OF EXISTING UTILITIES OR OTHER PHYSICAL OBJECTS SHOWN ON PLANS OR NOTED OTHERWISE.
16.

THE CONTRACTOR SHALL CREATE AND IMPLEMENT AN EROSION AND SEDIMENTATION CONTROL PLAN FOR ALL SITE CONSTRUCTION ACTIVITIES ASSOCIATED WITH THE PROJECT. THE PLAN MUST CONFORM TO THE EROSION AND SEDIMENTATION REQUIREMENTS OF THE CONSTRUCTION GENERAL PERMIT OR LOCAL STANDARDS AND CODES, WHICHEVER IS MORE STRINGENT.
17.

ALL COSTS FOR INSPECTIONS AND/OR TESTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR UNLESS NOTED OTHERWISE.

SITE NOTES

1.

ALL WORK AND MATERIALS SHALL COMPLY WITH ALL CITY/COUNTY REGULATIONS AND CODES AND O.S.H.A. STANDARDS.
2.

ALL MATERIAL NOTED ON DRAWINGS WILL BE SUPPLIED BY THE CONTRACTOR UNLESS OTHERWISE NOTED.
3.

CONTRACTOR SHALL REFER TO THE ARCHITECTURAL PLANS TO COORDINATE ACCESS POINTS AND ELEVATIONS. REFER TO ARCHITECTURAL PLANS. FOR EXACT LOCATIONS AND DIMENSIONS OF DOORS, ENTRY RAMP, AND CANOPY.
4.

THE CONTRACTOR SHALL OBTAIN ALL PERMITS FOR ALL SITE DEVELOPMENT WORK, PAY ALL FEES FOR PERMITS AND CHECK ALL GOVERNING AUTHORITIES' SPECIFICATIONS FOR BUT NOT LIMITED TO, GUTTERS, SIDEWALKS, POLES, AND OTHER STRUCTURES, INCLUDING THE REMOVAL OR RELOCATION OF EXISTING UTILITIES OR OTHER PHYSICAL OBJECTS SHOWN ON PLANS OR NOTED OTHERWISE.
5.

THE CONTRACTOR SHALL CREATE AND IMPLEMENT AN EROSION AND SEDIMENTATION CONTROL PLAN FOR ALL SITE CONSTRUCTION ACTIVITIES ASSOCIATED WITH THE PROJECT. THE PLAN MUST CONFORM TO THE EROSION AND SEDIMENTATION REQUIREMENTS OF THE CONSTRUCTION GENERAL PERMIT OR LOCAL STANDARDS AND CODES, WHICHEVER IS MORE STRINGENT.
6.

ALL COSTS FOR INSPECTIONS AND/OR TESTS SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR UNLESS NOTED OTHERWISE.
7.

ACCESSIBILITY STANDARDS SHALL BE IN ACCORDANCE WITH FEDERAL AND LOCAL REQUIREMENTS FOR HANDICAP ACCESSIBILITY, INCLUDING BUT NOT LIMITED TO THE AMERICANS WITH DISABILITIES ACT ACCESSIBILITY GUIDELINES. ADA PARKING STALLS SHALL MEET ADA GRADE GUIDELINES. CONTRACTOR SHALL FIELD VERIFY EXISTING GRADES AT ACCESS POINTS, ACCESSIBLE ROUTES, AND EXISTING PARKING TO REMAIN TO DETERMINE COMPLIANCE WITH STANDARDS.
8.

ALL DISTURBED AREAS ARE TO RECEIVE 6" OF TOPSOIL, SEED, MULCH AND WATER UNTIL A HEALTHY STAND OF GRASS IS ESTABLISHED.
9.

ALL DIMENSIONS AND RADII ARE TO THE FACE OF THE CURB OR EDGE OF PAVEMENT, AS APPLICABLE, UNLESS OTHERWISE NOTED.
10.

ALL CURB RADII ARE 5 FEET UNLESS OTHERWISE NOTED.
11.

PROVIDE SIGNAGE AND STRIPING AS SHOWN. ALL SIGNAGE AND PAVEMENT MARKINGS SHALL COMPLY WITH THE GOVERNING MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (M.U.T.C.D.). PAVEMENT MARKINGS ON ASPHALT SHALL BE WHITE. PAVEMENT MARKINGS ON CONCRETE SHALL BE YELLOW.
12.

REFER TO ARCHITECTURAL PLANS FOR PROPOSED BUILDING SIGNAGE.
13.

REFER TO MECHANICAL PLANS FOR EQUIPMENT LAYOUT.
14.

REFER TO ELECTRICAL PLANS FOR ELECTRICAL WORK.
15.

PAVEMENT SECTION THICKNESS TO MATCH EXISTING SECTIONS FROM THE 2007-2008 PLANS BY BRAUN & STEIDL ARCHITECTS. REFER TO DETAILS.
16.

REFER TO ORIGINAL SURVEY PROVIDED BY DEIBEL SURVEYING INC, DATED 07/02/2024.
17.

ALL LIGHT POLES TO BE LOCATED 3' FROM THE BACK OF CURB, AS MEASURED FROM THE FACE OF POLE FOUNDATION, UNLESS OTHERWISE DENOTED ON PLANS.

GRADING NOTES

1.

THE CONTRACTOR IS SPECIFICALLY CAUTIONED THAT THE LOCATION AND/OR ELEVATION OF EXISTING UTILITIES AS SHOWN ON THESE PLANS IS BASED ON RECORDS OF THE VARIOUS UTILITY COMPANIES, AND WHERE POSSIBLE, MEASUREMENTS TAKEN IN THE FIELD. THE INFORMATION IS NOT TO BE RELIED ON AS BEING EXACT OR COMPLETE. THE CONTRACTOR MUST CALL THE APPROPRIATE UTILITY COMPANIES AT LEAST 72 HOURS BEFORE ANY EXCAVATION TO REQUEST EXACT FIELD LOCATION OF UTILITIES. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO RELOCATE ALL EXISTING UTILITIES WHICH CONFLICT WITH THE PROPOSED IMPROVEMENTS SHOWN ON THE PLANS.
2.

THE TOPOGRAPHIC SURVEY WAS PERFORMED BY A REGISTERED LAND SURVEYOR. IF CONTRACTOR DOES NOT ACCEPT EXISTING TOPOGRAPHY AS SHOWN ON THE PLANS, WITHOUT EXCEPTION, HE SHALL HAVE MADE, AT HIS EXPENSE, A TOPOGRAPHIC SURVEY BY A REGISTERED LAND SURVEYOR AND SUBMIT IT TO THE OWNER FOR REVIEW.
3.

CONSTRUCTION SHALL COMPLY WITH ALL APPLICABLE GOVERNING CODES AND BE CONSTRUCTED TO SAME.
4.

THE CONTRACTOR SHALL ADHERE TO ALL TERMS & CONDITIONS AS OUTLINED IN THE EPA OR APPLICABLE STATE GENERAL N.P.D.E.S. PERMIT FOR STORM WATER DISCHARGE ASSOCIATED WITH CONSTRUCTION ACTIVITIES.
5.

EXISTING AND PROPOSED GRADE CONTOUR INTERVALS ARE SHOWN AT 1 FOOT INTERVALS.
6.

ALL SPOT ELEVATIONS REFER TO FINISHED PAVEMENT ELEVATIONS UNLESS OTHERWISE NOTED.
7.

ALL ADA ACCESSIBLE PARKING SPACES AND LOADING AREAS SHALL BE GRADED WITH A 2.0% MAXIMUM SLOPE IN ALL DIRECTIONS. ALL ADA ACCESSIBLE ROUTES SHALL BE GRADED WITH A 2.0% MAXIMUM CROSS SLOPE AND 5.0% MAXIMUM RUNNING SLOPE.
8.

MAINTAIN EXISTING DRAINAGE PATTERN THROUGHOUT THE SITE, EXCEPT WITHIN THE LIMITS OF DISTURBANCE (LOD).
9.

COORDINATE GRADES AT BUILDING ENTRIES WITH ARCHITECTURAL PLANS.
10.

EXISTING DRAINAGE STRUCTURES SHALL BE INSPECTED AND REPAIRED AS NEEDED, AND EXISTING PIPES ARE TO BE CLEANED TO REMOVE ALL SILT AND DEBRIS AFTER CONSTRUCTION IS COMPLETE.
11.

IF ANY EXISTING STRUCTURES TO REMAIN ARE DAMAGED DURING CONSTRUCTION IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO REPAIR AND/OR REPLACE THE EXISTING STRUCTURE AS NECESSARY TO RETURN IT TO A CONDITION EQUAL TO OR BETTER THAN IT'S CONDITION PRIOR TO DAMAGE.
12.

CONTRACTOR SHALL ASSURE POSITIVE DRAINAGE AWAY FROM BUILDING AND WITHIN PAVED AREAS.
13.

ALL TOPSOIL MUST BE REMOVED BEFORE FILL MATERIAL IS PLACED.
14.

ALL WET, OR OTHERWISE UNSUITABLE SOILS MUST BE STABILIZED, THIS MAY BE ACCOMPLISHED BY DRYING, REMOVAL & REPLACEMENT, REMOVAL & DRYING & RECOMPACTION, OR SOIL TREATMENT (LIME/CEMENT) UNDER THE SUPERVISION OF A QUALIFIED PROFESSIONAL GEOTECHNICAL ENGINEER.
15.

ALL UNSURFACED AREAS, DISTURBED BY GRADING, OPERATION SHALL RECEIVE 6" OF TOPSOIL. CONTRACTOR SHALL APPLY STABILIZATION FABRIC TO ALL SLOPES 3H:1V OR STEEPER AND SEED WITH LOW MAINTENANCE GRASS SEED MIX. CONTRACTOR SHALL SEED DISTURBED AREAS IN ACCORDANCE WITH SPECIFICATIONS UNTIL A HEALTHY STAND OF GRASS IS OBTAINED. ALL EXPOSED SURFACE AREAS SHALL BE STABILIZED PER THE SWPPP AND LANDSCAPE REQUIREMENTS AS PART OF THIS PLAN SET.
16.

ALL STORM PIPE ENTERING STRUCTURES SHALL BE GROUTED TO ASSURE CONNECTION AT STRUCTURE IS SOIL TIGHT.
17.

ALL STORM STRUCTURES SHALL HAVE A SMOOTH UNIFORM POURED MORTAR INVERT FROM INVERT IN TO INVERT OUT.
18.

REFER TO STORM DETAILS FOR CITY OF HUDSON ALLOWED MATERIALS, INSTALLATION, AND TESTING. NOTE THAT PIPES LARGER THAN 15" WILL BE REQUIRED TO BE RCP PER CITY CODE.
19.

ALL STORM SEWER STRUCTURE GRATES AND FRAMES WITHIN PAVEMENT SHALL BE HEAVY DUTY.
20.

ALL STORM DRAINAGE SHALL BE PERFORMED IN ACCORDANCE WITH ALL CITY OF HUDSON AND ODOT STANDARDS.
21.

ALL DOWNSPOUT DRAIN LINES OR ROOF LEADERS SHALL HAVE A 1.0% MINIMUM SLOPE, UNLESS OTHERWISE NOTED. CONNECT ALL DOWNSPOUTS AND ROOF LEADERS TO THE STORM SEWER SYSTEM. REFER TO ARCHITECTURAL PLANS FOR DOWNSPOUT AND ROOF LEADER LOCATIONS. PROVIDE POSITIVE DRAINAGE AND PAVEMENT REPAIR AS NEEDED.
22.

ROOF DRAINS, FOUNDATION DRAINS, AND OTHER CLEAN WATER CONNECTIONS TO THE SANITARY SEWER SYSTEM ARE PROHIBITED.
23.

THE STORM SEWER GRADE WILL BE SUCH THAT A MINIMUM COVER IS MAINTAINED TO WITHSTAND AASHTO HS-25 LOADING ON THE PIPE. PROVIDE MINIMUM 2.0 FEET OF COVER FOR ALL STORM SEWERS UNLESS OTHERWISE NOTED.
24.

WHEN A SANITARY SEWER MAIN LIES ABOVE A STORM SEWER, OR WITHIN 18 INCHES BELOW, THE SANITARY SEWER WILL HAVE AN IMPERVIOUS ENCASEMENT OR BE CONSTRUCTED OF STRUCTURAL SEWER PIPE FOR A MINIMUM OF 10 FEET ON EACH SIDE OF WHERE THE STORM SEWER CROSSES.
25.

IF EXISTING FIELD TILES ARE ENCOUNTERED DURING CONSTRUCTION THEY SHALL BE REPAIRED AND/OR TIED INTO A STORM SEWER SYSTEM AS NEEDED TO MAINTAIN POSITIVE DRAINAGE.

UTILITY NOTES

1.

THE CONTRACTOR IS SPECIFICALLY CAUTIONED THAT THE LOCATION AND/OR ELEVATION OF EXISTING UTILITIES AS SHOWN ON THESE PLANS IS BASED ON RECORDS OF THE VARIOUS UTILITY COMPANIES, AND WHERE POSSIBLE, MEASUREMENTS TAKEN IN THE FIELD. THE INFORMATION IS NOT TO BE RELIED ON AS BEING EXACT OR COMPLETE.
2.

THE CONTRACTOR MUST CALL THE APPROPRIATE UTILITY COMPANIES AT LEAST 72 HOURS BEFORE ANY EXCAVATION TO REQUEST EXACT FIELD LOCATION OF UTILITIES. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO RELOCATE ALL EXISTING UTILITIES WHICH CONFLICT WITH THE PROPOSED IMPROVEMENTS SHOWN ON THE PLANS.
3.

CONTRACTOR SHALL COMPLY TO THE FULLEST EXTENT WITH THE LATEST STANDARDS OF O.S.H.A. DIRECTIVES OR ANY OTHER AGENCY HAVING JURISDICTION FOR EXCAVATION AND TRENCHING PROCEDURES. THE CONTRACTOR SHALL USE SUPPORT SYSTEMS, SLOPING, BENCHING, AND OTHER MEANS OF PROTECTION. THIS TO INCLUDE BUT NOT LIMITED FOR ACCESS AND EGRESS FROM ALL EXCAVATION AND TRENCHING. CONTRACTOR IS RESPONSIBLE TO COMPLY WITH PERFORMANCE CRITERIA FOR O.S.H.A.
4.

CONTRACTOR IS RESPONSIBLE FOR REPAIRS OF DAMAGE TO ANY EXISTING UTILITY DURING CONSTRUCTION AT NO COST TO THE OWNER.
5.

ALL FILL MATERIAL IS TO BE IN PLACE AND COMPACTED BEFORE INSTALLATION OF PROPOSED UTILITIES.
6.

CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES FOR INSTALLATION REQUIREMENTS AND SPECIFICATIONS. THE CONTRACTOR SHALL CONDUCT ALL REQUIRED TESTS TO THE SATISFACTION OF THE RESPECTIVE UTILITY REGULATIONS AND THE OWNER'S INSPECTION AUTHORITIES.
7.

CONTRACTOR SHALL NOTIFY THE UTILITY AUTHORITY'S INSPECTORS 72 HOURS BEFORE CONNECTING TO ANY EXISTING LINE.
8.

WATER AND SANITARY UTILITIES SHALL HAVE TEN (10) FEET OF HORIZONTAL CLEARANCE WHEN PARALLEL OR 18" VERTICAL CLEARANCE WHEN CROSSING. ALL CLEARANCE DISTANCES SHALL BE MEASURE FROM OUTSIDE EDGE OF PIPE TO OUTSIDE EDGE OF PIPE. THE CROSSING SHALL BE ARRANGED SO THAT THE SANITARY SEWER JOINTS WILL BE EQUIDISTANT AND AS FAR AS POSSIBLE FROM THE WATER LINE JOINTS.
9.

IF A WATER LINE PASSES UNDER THE SANITARY SEWER LINE, THE SEWER LINE SHOULD BE CONSTRUCTED OF A WATERTIGHT MATERIAL APPROVED BY THE REGULATORY AGENCY FOR USE IN WATER MAIN CONSTRUCTION AND SHALL EXTEND TEN (10) FEET ON BOTH SIDES OF THE CROSSING, AS MEASURED PERPENDICULAR TO THE WATER LINES. ADEQUATE STRUCTURAL SUPPORT SHALL BE PROVIDED FOR THE SEWER TO MAINTAIN LINE AND GRADE.
10.

UNDERGROUND LINES SHALL BE INSTALLED, INSPECTED AND APPROVED BEFORE BACKFILLING.
11.

CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES FOR INSTALLATION REQUIREMENTS AND SPECIFICATIONS. THE CONTRACTOR SHALL CONDUCT ALL REQUIRED TESTS TO THE SATISFACTION OF THE RESPECTIVE UTILITY REGULATIONS AND THE OWNER'S INSPECTION AUTHORITIES.
12.

UTILITY TRENCHES WITHIN PAVED AREAS TO BE BACKFILLED PER UTILITY TRENCH DETAIL PROVIDED WITHIN THE CONSTRUCTION DETAILS SHEET.
13.

ALL WATER LINE WORK SHALL BE PERFORMED IN ACCORDANCE WITH CITY OF HUDSON WATERLINE STANDARDS, AND RECOMMENDED STANDARDS FOR WATER WORKS (10 STATES STANDARDS), LATEST EDITION AND STATE REGULATIONS.
14.

INSTALL ALL WATER LINES WITH A MINIMUM COVER OF 4'.
15.

ON-SITE WATER LINE MATERIAL SHALL BE PER CITY OF HUDSON STANDARDS, REFER TO WATER DETAILS. PRIOR TO CONSTRUCTION VERIFY ALL CITY OF HUDSON TESTING REQUIREMENTS THAT APPLY TO LATERAL INSTALLATION.
16.

ON-SITE SANITARY SEWER LINE MATERIALS AND INSTALLATION SHALL FOLLOW SUMMIT COUNTY DSSS STANDARD CONSTRUCTION DRAWINGS AND PROCEDURES FOR SANITARY SEWERS. REFER TO THE PROCEDURES AND STANDARD DRAWINGS IN THE CONSTRUCTION DETAILS SHEETS.
17.

REFER TO ARCHITECTURAL DRAWINGS FOR EXACT BUILDING UTILITY CONNECTION LOCATIONS, SERVICE SIZES TO BE DETERMINED BY ARCHITECT.
18.

CLEAN OUTS AND CURB BOXES WITHIN THE PAVED AREAS MUST HAVE TRAFFIC LOADING FRAMES AND COVERS.

EXHIBIT A  
GENERAL CONSTRUCTION NOTES

1.

CONSTRUCTION OF THE SITE WORK AND UTILITIES SHALL BE GOVERNED BY THE CITY OF HUDSON'S "ENGINEERING STANDARDS FOR INFRASTRUCTURE CONSTRUCTION", LATEST EDITION.
2.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING AND PAYING FOR ALL PERMITS REQUIRED FOR THE PROJECT.
3.

THE CONTRACTOR MUST ALERT THE OHIO UTILITY PROTECTION SERVICES AT LEAST 48 HOURS BEFORE ANY EXCAVATION IS TO BEIGIN.
4.

ALL EXISTING APPURTENANCES (UTILITY POLES, VALVES, HYDRANTS, MANHOLES, ETC) ARE TO BE MAINTAINED BY THE CONTRACTOR UNLESS OTHERWISE SHOWN ON THE PLANS.
5.

THE DESIGN ENGINEER CERTIFIES THAT ALL UTILITIES ARE SHOWN AS THEY APPEAR ON EXISTING RECORDS OR FIELD LOCATED.
6.

ALL KNOWN ABOVE AND UNDERGROUND SERVICES HAVE BEEN NOTED ON THE DRAWINGS. THE CONTRACTOR ACCEPTS FULL RESPONSIBILITY FOR ANY SERVICES DAMAGED DURING THE CONSTRUCTION OF THE PROJECT WHETHER SHOWN OR NOT ON THE DRAWINGS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING THE SERVICE AS SOON AS POSSIBLE AT THE CONTRACTOR'S OWN EXPENSE.
7.

VIDEO RECORDING OF PROJECT SHALL BE DELIVERED AND ACCEPTED BY THE CITY OF HUDSON ENGINEERING DEPARTMENT A MINIMUM OF 7 CALENDAR DAYS PRIOR TO START OF CONSTRUCTION ACTIVITIES.
8.

NOTIFY THE CITY OF HUDSON ENGINEERING DEPARTMENT A MINIMUM OF FORTY-EIGHT HOURS (2 WORKING DAYS) PRIOR TO THE START OF CONSTRUCTION.
9.

A PRECONSTRUCTION MEETING SHALL BE SCHEDULED A MINIMUM OF 48 HOURS (2 WORKING DAYS) AFTER SUBMISSION OF A MINIMUM OF 6 APPROVED SETS OF PLANS AND ALL SHOP DRAWINGS APPLICABLE TO THE PROPOSED IMPROVEMENTS. A PRECONSTRUCTION MEETING MUST BE HELD PRIOR TO START OF ANY CONSTRUCTION.
10.

THE LIMITS OF CLEARING AND GRADING SHALL BE FIELD STAKED AND LINED WITH ORANGE CONSTRUCTION FENCING 48 HOURS (2 WORKING DAYS) PRIOR TO THE PRECONSTRUCTION MEETING. AREAS BEYOND THE LIMITS OF CLEARING AND GRADING SHALL NOT BE DISTURBED INCLUDING THE STOCKPILE OF ANY MATERIALS OR CONSTRUCTION TRAFFIC.
11.

ALL ROAD SURFACES, EASEMENTS, OR RIGHT-OF-WAY DISTURBED BY THE CONSTRUCTION OF ANY PART OF THESE IMPROVEMENTS ARE TO BE RESTORED ACCORDING TO THE CITY OF HUDSON "ENGINEERING STANDARDS FOR INFRASTRUCTURE CONSTRUCTION" AS DIRECTED BY THE CITY OF HUDSON AND/OR ITS ENGINEER.
12.

THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE CITY OF HUDSON OR ITS REPRESENTATIVE IF SUSPECTED HAZARDOUS MATERIAL OR ANY OTHER MATERIAL THAT MAY CREATE A HEALTH RISK IS DISCOVERED ON SITE.
13.

ALL DISTURBED STORM SEWERS AND/OR APPURTENANCES, SIGNS, GUARD RAILING, MAIL AND/OR PAPER BOXES, DRIVE CULVERTS, FENCES, TREES, LANDSCAPING, OR OTHER ITEMS DISTURBED BY THE CONSTRUCTION SHALL BE RESTORED OR REPAIRED TO AT LEAST THE BEFORE-CONSTRUCTION CONDITION.
14.

ANY DEFECTS DISCOVERED IN NEW CONSTRUCTION, WORKMANSHIP, EQUIPMENT OR MATERIALS SHALL BE REPAIRED, OR CORRECTED BY APPROVED METHODS AS DIRECTED BY THE CITY OF HUDSON.
15.

NUCLEAR COMPACTION TESTING SHALL BE REQUIRED FOR ALL FILL AREAS OVER TWO FEET (2') IN DEPTH, AT 6" LIFTS PER ASTM A-1557, 95% MODIFIED.
16.

APPROVAL BY THE CITY OF HUDSON ENGINEER CONSTITUTES NEITHER EXPRESSED NOR IMPLIED WARRANTIES AS TO THE FITNESS, ACCURACY, OR SUFFICIENCY OF PLANS, DESIGNS OR SPECIFICATIONS.
17.

DURING TAPPING OF EXISTING UTILITIES, ANY TRAFFIC CONTROL REQUESTED OR REQUIRED BY THE CITY OF HUDSON WILL BE PROVIDED BY THE CONTRACTOR AT NO COST TO THE CITY.
18.

COMPLIANCE WITH THE OCCUPATIONAL AND SAFETY ACT OF 1970 IS REQUIRED BY ALL CONTRACTORS ON THIS PROJECT.
19.

ROOF DRAINS, FOUNDATION DRAINS, AND OTHER CLEAN WATER CONNECTIONS TO THE SANITARY SEWER ARE PROHIBITED.
20.

ALL DISTURBED AREAS SHALL RECEIVE 4" OF TOPSOIL AND BE SEEDED AND MULCHED AS PER SECTION 9 - LANDSCAPING AND STREET TREES OF THE CITY'S "ENGINEERING STANDARDS FOR INFRASTRUCTURE CONSTRUCTION", LATEST EDITION.
21.

IF MUD, SOIL, OR OTHER DEBRIS IS DEPOSITED ON ADJACENT STREETS, ROADS, OR OTHER PROPERTY, THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REMOVAL OF SUCH AS DIRECTED BY THE CITY OF HUDSON OR ITS ENGINEER AT THE END OF EACH WORK DAY, OR AS REQUIRED DURING THE WORK DAY.
22.

ALL PROPOSED SLOPES 3:1 OR STEEPER AND ALL EARTHEN DRAINAGE WAYS SHALL RECEIVE JUTE OR EXCELSIOR MATTING AS PER ODOT 671.
23.

ALL STORM SEWERS WITHIN PUBLIC RIGHTS-OF-WAY AND CITY OF HUDSON EASEMENTS SHALL BE PER SECTION 4 - STORM COLLECTION OF THE CITY'S "ENGINEERING STANDARDS FOR INFRASTRUCTURE CONSTRUCTION", LATEST EDITION.
24.

ALL PIPES SHALL BE PLACED OVER 4" OF BEDDING. BEDDING MATERIAL SHALL BE AS SPECIFIED IN CITY'S "ENGINEERING STANDARDS FOR INFRASTRUCTURE CONSTRUCTION", LATEST EDITION, FOR THE TYPE OF PIPE.
25.

CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING AND PROTECTING THE FLOW OF VEHICULAR AND PEDESTRIAN TRAFFIC AROUND THE JOB SITE. TRAFFIC CONTROL SHALL BE COORDINATED WITH THE CITY OF HUDSON POLICE DEPARTMENT.
26.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING PLANT TICKETS FOR ALL MATERIALS DELIVERED TO THE SITE. PLANT TICKETS MUST SHOW NET QUANTITY OF DELIVERED MATERIAL. MATERIAL DELIVERED OR PLACED WITHOUT PLANT TICKETS SHALL BE REMOVED AND PROPERLY DISPOSED AT THE EXPENSE OF THE CONTRACTOR.
27.

ALL DELIVERED MATERIALS SHALL MEET THE STANDARDS AND SPECIFICATIONS OF THE CITY OF HUDSON OR OTHER APPLICABLE AGENCIES. THE CITY OF HUDSON, OR ITS REPRESENTATIVE, RESERVES THE RIGHT TO REJECT ANY DELIVERED MATERIAL WHICH DOES NOT CONFORM TO THE APPLICABLE STANDARDS AND SPECIFICATIONS.
28.

THE CITY OF HUDSON OR ITS REPRESENTATIVE, RESERVES, THE RIGHT TO HALT ALL CONSTRUCTION ACTIVITY FOR NONCONFORMANCE OF PLANS, SPECIFICATIONS AND OTHER APPLICABLE STANDARDS OR REGULATIONS.
29.

ALL CHANGES TO APPROVED DRAWINGS AND/OR SPECIFICATIONS MUST BE REAPPROVED BY THE CITY OF HUDSON PRIOR TO CONSTRUCTION.
30.

ALL PAVING MATERIAL MUST BE PROVIDED BY ODOT CERTIFIED SUPPLIER. WRITTEN PROOF SHALL BE REQUIRED UPON DELIVERY OF MATERIALS. THE CERTIFIED MIX DESIGN MUST BE SUBMITTED TO, AND APPROVED BY, THE CITY OF HUDSON PRIOR TO SCHEDULING A PRECONSTRUCTION MEETING.
31.

CONTRACTOR/DEVELOPER SHALL PROVIDE ALL REQUIRED ROADWAY SIGNAGE AS PER ODOT MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES INCLUDING STREET IDENTIFICATION SIGNAGE PER CITY STANDARDS FOR ALL ASPECTS OF THE IMPROVEMENT.
32.

ALL BONDS AND OR LETTERS OF CREDIT SHALL NOT BE RELEASED OR REDUCED AND NO WATER OR SANITARY SEWER CUSTOMERS CAN BE CONNECTED UNTIL ALL RECORD DRAWINGS HAVE BEEN SUBMITTED, REVIEWED AND APPROVED BY THE CITY OF HUDSON.
33.

ALL WORK, EXCEPT SIDEWALKS, STREET TREES AND STREET LIGHTS, AS PART OF THESE PLANS SHALL BE COMPLETED, INCLUDING PUNCH LIST ITEMS AND DEFICIENCY WORK WITHIN 1 YEAR OF THE DATE OF APPROVAL BY THE CITY ENGINEER. SIDEWALKS, STREET TREES AND STREET LIGHTS SHALL BE COMPLETED WITHIN TWO YEARS OF THE DATE OF APPROVAL BY THE CITY ENGINEER.
34.

FAILURE TO COMPLETE THE PROJECT IN ITS ENTIRETY AS APPROVED BY THE PLANNING COMMISSION, INCLUDING PUNCH LIST ITEMS, WILL RESULT IN THE CITY OF HUDSON HOLDING ALL FUTURE ZONING CERTIFICATES UNTIL ALL WORK HAS BEEN COMPLETED AND APPROVED.
35.

MANUFACTURERS OR SUPPLIERS AFFIDAVIT FOR ALL CONSTRUCTION MATERIALS SHALL BE PROVIDED AS PER THE CITY'S "ENGINEERING STANDARDS FOR INFRASTRUCTURE CONSTRUCTION", LATEST EDITION PRIOR TO THE START OF CONSTRUCTION.
36.

THE CONSTRUCTION OF SANITARY SEWERS, WATER MAINS, LIFT STATIONS AND APPURTENANCES IS PROHIBITED UNTIL ALL PLANS HAVE BEEN APPROVED BY THE OHIO ENVIRONMENTAL PROTECTION AGENCY.
37.

ALL SANITARY SEWERS SHALL COMPLY WITH THE SUMMIT COUNTY DEPARTMENT OF SANITARY SEWER SERVICES.
38.

SHOP DRAWINGS FOR THE PROPOSED LIGHT FIXTURES SHALL BE ATTACHED TO THE APPROVED LIGHTING PLAN AND SUBMITTED WITH THE SIX SETS OF PLANS AS REQUIRED IN NOTE 8. THE LIGHT FIXTURES SHALL HAVE A RECESSED LAMP, FLAT LENSES AND OPTIONAL HOUSE SHIELDING AVAILABLE. THE CITY MAY REQUIRE HOUSE SHIELDS TO BE ADDED AND OTHER MODIFICATIONS AFTER CONSTRUCTION AT THE EXPENSE OF THE CONTRACTOR.
39.

THE OWNER SHALL SUBMIT A NOTICE OF INTENT (N.O.I) APPLICATION TO THE OHIO ENVIRONMENTAL PROTECTION AGENCY (E.P.A) AND OBTAIN AUTHORIZATION FOR STORM WATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITY UNDER THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (N.P.D.E.S) OR THE LATEST FEDERAL, STATE AND/OR LOCAL REGULATIONS. THE OWNER SHALL SUBMIT A COPY OF THE N.P.D.E.S. PERMIT TO THE CITY OF HUDSON 48 HOURS (2 WORKING DAYS) PRIOR TO SCHEDULING A PRECONSTRUCTION MEETING.
40.

ALL EXCESS EXCAVATED MATERIAL WHICH HAS BEEN STOCKPILED AT THE WORK SITE, AND WHICH WILL NOT BE USED FOR BACKFILL OR OTHER FILL PURPOSES, SHALL BE REMOVED FROM THE PROJECT AREA WITHIN 48 HOURS OF THE EXCAVATION IN ACCORDANCE WITH SECTION 1.20 OF THE ENGINEERING STANDARDS.
41.

ACTIVITIES AND LAND ADJACENT TO THIS PROJECT MAY BE AFFECTED BY CONSTRUCTION NOISE. IN ORDER TO MINIMIZE ANY ADVERSE CONSTRUCTION NOISE IMPACTS, ANY POWER-OPERATED CONSTRUCTION-TYPE DEVICE SHALL NOT BE OPERATED BETWEEN THE HOURS OF 7:00 PM AND 7:00 AM WITHOUT PRIOR APPROVAL OF THE ENGINEER. IN ADDITION, ANY SUCH DEVICE SHALL NOT BE OPERATED AT ANY TIME IN SUCH A MANNER THAT THE NOISE CAUSED SUBSTANTIALLY EXCEEDS THE REASONABLE AND EFFICIENT PERFORMANCE OF SUCH EQUIPMENT.
42.

THERE SHALL BE NO WORK ON PRIVATE PROPERTY WITHOUT WRITTEN CONSENT FROM THE CITY AND THE PRIVATE PROPERTY OWNER.



www.cesoinc.com

175 Monroeville West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0960 Fax: 988.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY

CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: N/A

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET

Drawing Title:


GENERAL NOTES

C2.0







C:\D:\ACD\Drawings\CCCC - Hudson - Civil Master Plan Study\Project Files\CESO\03-CIVIL\PLAN\LOT\Major Site Plans\765295 - OVERALL SITE PLAN.dwg - 5/21/2025 - Jake McDaniel



- SITE LEGEND**
- EXISTING**
- REFER TO ALTA SURVEY BY DIEBEL FOR EXISTING FEATURES LEGEND
- PROPOSED**
- PROPOSED BUILDING
  - PROPOSED ASPHALT PAVEMENT
  - PROPOSED MILL & OVERLAY
  - PROPOSED HEAVY DUTY CONCRETE PAVEMENT
  - PROPOSED CONCRETE SIDEWALK
  - PROPOSED TURF SOCCER FIELD
  - RIGHT-OF-WAY
  - PROPERTY LINE
  - SETBACK
  - EASEMENT
  - CENTERLINE
  - CONCRETE CURB
  - PAVEMENT/WALK
  - PARKING SPACE COUNT
  - SIGN
  - CATCH BASIN
  - STORM MANHOLE
  - SANITARY MANHOLE
  - CURB INLET
  - CLEANOUT
  - YARD DRAIN
  - DOWN SPOUT
  - LIGHT POLE



INDEX OF ECOLOGICAL INTEGRITY



FORTY- EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**  
750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: 1"=60'

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET


Drawing Title:

**OVERALL SITE**

**C4.0**



C:\D:\ACD\Draws\CESO\CCCC - Hudson - Civil Master Plan Study\Project Files\CESO\CCCC-CIVIL\PLAN\LOT Major Site Plans\765295 SITE PLAN.dwg - 5/21/2025 - Jake McDaniel



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY  
CHAPEL**

750 W. STREETSBO RO STREET  
HUDSON, OH 44236

Revisions / Submissions		
ID	Description	Date

© 2025 CESO, INC.


Project Number: 765295  
Scale: AS SHOWN  
Drawn By: KAN  
Checked By: JMS  
Date: 5/22/2025  
Issue: PERMIT SET

Drawing Title:  
**FIELD SITE AND  
PAVEMENT PLAN**

**C4.1**



C:\Users\kocinski\Documents\CES\0303-Civil\Plan\LOT\Major Site Plans\765295 - OVERALL GRADING PLAN.dwg - 5/22/2025 - Jonathan Kocinski




**GRADING LEGEND**

EXISTING  
REFER TO ALTA SURVEY BY DIEBEL FOR EXISTING FEATURES LEGEND

PROPOSED

- BUILDING
- MAJOR CONTOUR
- MINOR CONTOUR
- STRUCTURE NUMBER
- CATCH BASIN
- CLEANOUT
- YARD DRAIN



FORTY-EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**

750 W. STREETSBORO STREET  
HUDSON, OH 44236


Revisions / Submissions		
ID	Description	Date

© 2025 CESO, INC.	
Project Number:	765295
Scale:	1"=50'
Drawn By:	KAN
Checked By:	JMS
Date:	5/22/2025
Issue:	PERMIT SET

Drawing Title:  
**OVERALL GRADING PLAN**

**C5.0**





C:\Users\kocinski\Documents\CES03\03-CIVIL\PLAN\LOT Major Site Plans\765295 GRADING PLAN.dwg - 5/22/2025 - Jonathan Kocinski



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**  
750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID Description Date

© 2025 CESO, INC.

Project Number: 765295

Scale: 1"=20'

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET

Drawing Title:

**FIELD GRADING PLAN**

**C5.1**







STORMWATER POLLUTION PREVENTION PLAN (SWPPP) PROJECT NARRATIVE:

PLAN ENGINEERS: CESO, INC. 175 MONTROSE WEST AVE., SUITE 400 AKRON, OH 44321 PHONE: (330) 349-2514 CONTACT: HANNAH OKES

OWNER: CHRIST COMMUNITY CHAPEL 750 W. STREETSBORO STREET HUDSON, OH 44236 PHONE: (330) 493-3722

THE PROPOSED PROJECT IS THE CONSTRUCTION OF TURF SOCCER FIELD AND RESTROOM AREA. THE SUBJECT PARCEL IS 28.596 ACRES. THE TOTAL DISTURBED AREA IS 3.93 ACRES.

THE SITE DRAINS TO THE EXISTING SITE EXITS THE SITE VIA THE EXISTING STORMWATER MANAGEMENT AREA, LEAVES THE SITE TO THE NORTH, AND EVENTUALLY OUTFALLS INTO MUD BROOK.

ON-SITE SOILS: Ca CANADICE SILTY CLAY LOAM 0% - 2% SLOPES SOIL GROUP D 0.5% OF SITE AREA CcB CANADEA SILT LOAM 2% - 6% SLOPES SOIL GROUP D 46.9% OF SITE AREA CcC2 CHILI GRAVELLY LOAM 6% - 12% SLOPES SOIL GROUP A 6.9% OF SITE AREA EuC ELLSWORTH-URBAN LAND COMPLEX 6% - 18% SLOPES SOIL GROUP D 7.2% OF SITE AREA GbC2 GEEBURG SILT LOAM 6% - 12% SLOPES SOIL GROUP D 19.3% OF SITE AREA GbD2 GEEBURG SILT LOAM 12% - 18% SLOPES SOIL GROUP D 1.6% OF SITE AREA Mn MAHONING-URBAN LAND COMPLEX 0% - 2% SLOPES SOIL GROUP D 9.0% OF SITE AREA Sb SEBRING SILT LOAM 0% - 2% SLOPES SOIL GROUP D 1.9% OF SITE AREA Wb WHEELING SILT LOAM 2% - 6% SLOPES SOIL GROUP B 6.7% OF SITE AREA

THE PRE-EXISTING CONDITIONS ON-SITE IS EXISTING CHURCH BUILDING, PARKING LOT, AND SOCCER FIELD. NOI #TBD

SWPPP GENERAL NOTES


- ALL EROSION AND SEDIMENTATION CONTROL SHALL BE PERFORMED ACCORDING TO: SWPPP AND DETAIL PLANS; ACCORDING TO THE LATEST EPA AUTHORIZATION FOR CONSTRUCTION ACTIVITY UNDER THE "NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM" (NPDES); ANY AND ALL REQUIRED PERMITS, REPORTS, AND RELATED DOCUMENTS. ALL CONTRACTORS AND SUBCONTRACTORS MUST BECOME FAMILIAR WITH ALL OF THE ABOVE.
- CONTRACTOR SHALL IMPLEMENT BEST MANAGEMENT PRACTICES (BMPs) AS REQUIRED BY THE SWPPP. ADDITIONAL BEST MANAGEMENT PRACTICES SHALL BE IMPLEMENTED AS DICTATED BY CONDITIONS AND GRADE CHANGES TO THE SITE AT NO ADDITIONAL COST TO OWNER THROUGHOUT ALL PHASES OF CONSTRUCTION.
- CONTRACTOR SHALL MINIMIZE CLEARING AND DISTURBANCE TO THE ENVIRONMENT TO THE MAXIMUM EXTENT POSSIBLE OR AS REQUIRED BY THE GENERAL PERMIT.
- SEDIMENT STRUCTURES AND PERIMETER SEDIMENT BARRIERS SHALL BE IMPLEMENTED AS THE FIRST STEP OF GRADING WITHIN SEVEN (7) DAYS FROM THE START OF CLEARING AND GRUBBING, AND SHALL CONTINUE TO FUNCTION UNTIL THE DEVELOPMENT AREA IS STABILIZED.
- PERMANENT SOIL STABILIZATION OF DISTURBED AREAS BY MEANS OF VEGETATION, LANDSCAPE TYPE MULCHING, MATTING, SOD, RIP RAP, AND OTHER APPROVED LANDSCAPING TECHNIQUES TO BE APPLIED AS FOLLOWS:
  - WITHIN SEVEN (7) DAYS OF ANY AREA THAT WILL BE DORMANT FOR ONE (1) YEAR OR MORE.
  - WITHIN TWO (2) DAYS OF ANY AREA WITHIN 50 FEET OF A STREAM AT FINAL GRADE.
  - WITHIN SEVEN (7) DAYS FOR ANY OTHER AREA AT FINAL GRADE.
- TEMPORARY SOIL STABILIZATION OF DISTURBED AREAS BY MEANS OF TEMPORARY VEGETATION, MULCHING, GEOTEXTILES, SOD, PRESERVATION OF EXISTING VEGETATION, AND OTHER APPROVED TECHNIQUES TO BE APPLIED AS FOLLOWS:
  - WITHIN TWO (2) DAYS OF ANY AREA WITHIN 50 FEET OF A STREAM NOT AT FINAL GRADE.
  - WITHIN SEVEN (7) DAYS OF ANY AREA THAT WILL BE DORMANT FOR MORE THAN TWENTY ONE (21) DAYS, BUT LESS THAN ONE (1) YEAR.
  - PRIOR TO THE ONSET OF WINTER WEATHER FOR AREAS THAT WILL BE IDLE OVER WINTER.
- TEMPORARY SEEDING, MULCHING, AND FERTILIZER SPECIFICATIONS:

SEEDING: ANNUAL RYEGRASS AT 2.02 POUNDS PER 1,000 S.F.

MULCHING: STRAW MATERIAL SHALL BE UNROTTED SMALL GRAIN STRAW APPLIED AT A RATE OF TWO (2) TON/ACRE, OR 80-100 POUNDS PER 1,000 S.F. MULCH MATERIALS SHALL BE RELATIVELY FREE OF ALL KINDS OF WEEDS AND SHALL BE FREE OF PROHIBITIVE NOXIOUS WEEDS. MULCH SHALL BE SPREAD UNIFORMLY BY HAND OR MECHANICAL MEANS. FROM NOVEMBER 01 THRU MARCH 15 INCREASE THE RATE OF STRAW MULCH TO THREE (3) TON/ACRE.

FERTILIZER: APPLY FERTILIZER AT HALF THE RATE OF PERMANENT APPLICATION AND AS PER SPECIFICATIONS. IF PROJECT CONDITIONS PREVENT FERTILIZING THE SOIL, THEN THIS ITEM MAY BE WAIVED.
- SLOPES SHALL BE LEFT IN A ROUGHENED CONDITION DURING THE GRADING PHASE TO REDUCE RUNOFF VELOCITIES AND EROSION. ALL SLOPES 3:1 OR GREATER THAN 3:1 SHALL BE FERTILIZED, SEEDED, AND CURLEX BLANKETS BY AMERICAN EXCELSIOR COMPANY, NORTH AMERICAN GREEN, INC. OR AN APPROVED EQUAL AS SPECIFIED IN THE PLANS SHALL BE INSTALLED ON THE SLOPES.
- NO SOLID (OTHER THAN SEDIMENT) OR LIQUID WASTE, INCLUDING BUILDING MATERIALS, SHALL BE DISCHARGED IN STORM WATER RUNOFF. ALL NON-SEDIMENT POLLUTANTS MUST BE DISPOSED OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL GUIDELINES. WASH OUT OF CEMENT TRUCKS SHOULD OCCUR IN DESIGNATED PIT OR DIKED AREAS, WHERE WASHINGS CAN BE REMOVED AND PROPERLY DISPOSED OFF-SITE WHEN THEY HARDEN. STORAGE TANKS SHOULD ALSO BE LOCATED IN PIT OR DIKED AREAS. IN ADDITION, SUFFICIENT OIL AND GREASE ABSORBING MATERIALS AND FLOTATION BOOMS TO CLEAN AND CONTAIN FUEL AND CHEMICAL SPILLS MUST BE KEPT ON SITE.
- IF THE ACTION OF VEHICLES TRAVELING OVER THE STABILIZED CONSTRUCTION EXIT DOES NOT SUFFICIENTLY REMOVE MOST OF THE DIRT AND MUD, THEN THE TIRES MUST BE WASHED BEFORE VEHICLES ENTER A PUBLIC ROAD. PROVISIONS MUST BE MADE TO INTERCEPT THE WATER AND TRAP THE SEDIMENT BEFORE IT IS CARRIED OFF THE SITE.
- RUBBISH, TRASH, GARBAGE, LITTER, OR OTHER SUCH MATERIALS SHALL BE DISPOSED INTO SEALED CONTAINERS. MATERIALS SHALL BE PREVENTED FROM LEAVING THE SITE THROUGH THE ACTION OF WIND OR STORM WATER DISCHARGE INTO DRAINAGE DITCHES OR WATERS OF THE STATE.
- DUST CONTROL USING APPROVED MATERIALS MUST BE PERFORMED AT ALL TIMES. THE USE OF MOTOR OILS AND OTHER PETROLEUM BASED OR TOXIC LIQUIDS FOR DUST SUPPRESSION IS PROHIBITED.
- ON-SITE AND OFF-SITE STOCKPILE AND BORROW AREAS SHALL BE PROTECTED FROM EROSION AND SEDIMENTATION BY THE USE OF BEST MANAGEMENT PRACTICES. THESE AREAS MUST BE SHOWN IN THE SITE MAP AND PERMITTED IN ACCORDANCE WITH GENERAL PERMIT REQUIREMENTS. AT A MINIMUM SILT FENCE TO BE PLACED AT PERIMETER OF STOCKPILE AREA TO PREVENT SOIL FROM LEAVING THE STOCKPILE AREA.
- ALL MATERIALS SPILLED, DROPPED, WASHED, OR TRACKED ONTO THE ROADWAYS OR INTO THE STORM SEWERS MUST BE REMOVED IMMEDIATELY.
- ALL CONSTRUCTION SHALL BE STABILIZED AT THE END OF EACH DAY; THIS INCLUDES BACKFILLING OF TRENCHES FOR UTILITY CONSTRUCTION AND PLACEMENT OF GRAVEL OR ASPHALT FOR ROAD CONSTRUCTION.

- THE LAST LAYER OF SOIL, INCLUDING TOP SOIL SHOULD BE COMPACTED TO 80% - 85% OF THE MAXIMUM STANDARD PROCTOR DENSITY, IN AREAS OUTSIDE THE PARKING LOT THAT WILL RECEIVE VEGETATION. THIS IS PARTICULARLY IMPORTANT IN CUT SLOPE AND EMBANKMENT AREAS. IN PAVEMENT AND ISLAND AREAS, IT IS RECOMMENDED THAT THE SOIL BE COMPACTED TO 98% AND 95% OF THE MAXIMUM STANDARD PROCTOR DENSITY RESPECTIVELY; THE LAST COMPACTED LAYER MAY BE SCARIFIED TO IMPROVE THE SOIL GROWTH CHARACTERISTICS.
  - ALL DEWATERING ACTIVITIES SUCH AS PUMPING DOWN OF FLOODED FOUNDATION AND UTILITY TRENCHES MUST PASS THROUGH THE RETROFITTED DETENTION BASIN OR A SEDIMENT CONTROL PRACTICE PRIOR TO WATER LEAVING THE SITE.
  - SILT FENCE AND OTHER PERIMETER EROSION CONTROL MEASURES SHOWN OFF LIMITS OF DISTURBANCE FOR CLARITY PURPOSES ONLY. CONTRACTOR TO ENSURE PERIMETER EROSION CONTROL MEASURES ARE PLACED AT THE LIMITS OF DISTURBANCE. ANY DISCREPANCIES SHOULD BE BROUGHT TO THE ENGINEER PRIOR TO PLACEMENT OF ANY EROSION CONTROL MEASURES.
- SWPPP MAINTENANCE NOTES
- ALL CONTROL MEASURES STATED IN THE SWPPP SHALL BE MAINTAINED IN FULLY FUNCTIONAL CONDITION UNTIL TEMPORARY OR PERMANENT STABILIZATION OF THE SITE IS ACHIEVED. ALL EROSION AND SEDIMENTATION CONTROL MEASURES SHALL BE INSPECTED BY A QUALIFIED PERSON IN ACCORDANCE TO THE CONTRACT DOCUMENTS OR THE APPLICABLE PERMIT, WHICHEVER IS MORE STRINGENT, AND REPAIRED ACCORDING TO THE FOLLOWING.
  - INLET PROTECTION DEVICES AND CONTROLS SHALL BE REPAIRED OR REPLACED WHEN THEY SHOW SIGNS OF UNDERMINING AND OR DETERIORATION. INLET PROTECTION DEVICES SHOULD BE ROUTINELY CLEANED AND MAINTAINED.
  - ALL SEEDED AREAS SHALL BE CHECKED REGULARLY TO ENSURE THAT A GOOD STANDING OF GRASS IS MAINTAINED. AREAS SHOULD BE FERTILIZED, WATERED, AND RESEEDING AS NEEDED.
  - MINIMIZE OFF-SITE SEDIMENT TRACKING OF VEHICLES BY THE USE OF STONE MATERIAL IN ALL CONSTRUCTION ENTRANCES, ALONG WITH REGULARLY SCHEDULED SWEEPING/GOOD HOUSEKEEPING. STABILIZED CONSTRUCTION ENTRANCES TO BE PROPERLY MAINTAINED BY GENERAL CONTRACTOR AND IN GOOD WORKING ORDER AT ALL TIMES; THIS MAY REQUIRE PERIODIC TOP DRESSING OF THE STONE AS CONDITIONS DEMAND.
  - THE TEMPORARY PARKING AND STORAGE AREA SHALL BE KEPT IN GOOD CONDITION (SUITABLE FOR PARKING AND STORAGE) BY GENERAL CONTRACTOR. THIS MAY REQUIRE PERIODIC TOP DRESSING OF THE TEMPORARY PARKING AS CONDITIONS DEMAND.
  - CONTRACTORS AND SUBCONTRACTORS WILL BE RESPONSIBLE FOR REMOVING ALL SEDIMENT FROM THE SITE, AND STORM SEWER SYSTEMS. SEDIMENT DEPOSITION DURING SITE STABILIZATION MUST ALSO BE REMOVED.
  - STONE CONSTRUCTION EXIT TO BE MAINTAINED BY GENERAL CONTRACTOR UNTIL SITE HAS BEEN PAVED OR IS NO LONGER REQUIRED.
  - ALL CATCH BASIN GRATES ARE TO BE PROTECTED WITH INLET BAGS AFTER THEY ARE INSTALLED. THEY SHOULD BE ROUTINELY CLEANED AND MAINTAINED.
  - CONTAINERS SHALL BE AVAILABLE FOR DISPOSAL OF DEBRIS, TRASH, HAZARDOUS OR PETROLEUM WASTES. ALL CONTAINERS MUST BE COVERED AND LEAK-PROOF. ALL WASTE MATERIAL SHALL BE DISPOSED OF AT FACILITIES APPROVED FOR THE PERTINENT MATERIAL.
  - BRICKS, HARDENING CONCRETE AND SOIL WASTE SHALL BE FREE FROM CONTAMINATION WHICH MAY LEACH CONSTITUENTS TO WATERS OF THE STATE.
  - CLEAN CONSTRUCTION WASTES THAT WILL BE DISPOSED INTO THE PROPERTY SHALL BE SUBJECT TO ANY LOCAL PROHIBITIONS ON THIS TYPE OF DISPOSAL.
  - ALL CONSTRUCTION AND DEMOLITION DEBRIS (C&D) WASTE SHALL BE DISPOSED OF IN A STATE APPROVED C&D LANDFILL. CONSTRUCTION DEBRIS MAY BE DISPOSED OF ON-SITE, BUT DEMOLITION DEBRIS MUST BE DISPOSED IN A STATE APPROVED LANDFILL. ALSO, MATERIALS WHICH CONTAIN ASBESTOS MUST COMPLY WITH ALL LOCAL AND STATE REGULATIONS.
  - AREA SHALL BE DESIGNATED BY CONTRACTOR AND SHOWN ON SWPPP MAP FOR MIXING OR STORAGE OF COMPOUNDS SUCH AS FERTILIZERS, LIME ASPHALT, OR CONCRETE, THESE DESIGNATED AREAS SHALL BE LOCATED AWAY FROM WATERCOURSES, DRAINAGE DITCHES, FIELD DRAINS, OR OTHER STORMWATER DRAINAGE AREA.
  - EQUIPMENT FUELING & MAINTENANCE SHALL BE IN DESIGNATED AREAS ONLY.
  - A SPILL PREVENTION CONTROL AND COUNTERMEASURE (SPCC) PLAN MUST BE DEVELOPED FOR SITES WITH ONE ABOVE-GROUND STORAGE TANK OF 660 GALLONS OR MORE, TOTAL ABOVE-GROUND STORAGE OF 1,330 GALLONS OR BELOW-GROUND STORAGE OF 4,200 GALLONS OF FUEL.
  - ALL DESIGNATED CONCRETE WASHOUT AREAS SHALL BE LOCATED AWAY FROM WATERCOURSES, DRAINAGE DITCHES, FIELD DRAINS OR OTHER STORMWATER DRAINAGE AREAS.
  - ALL CONTAMINATED SOIL MUST BE TREATED AND/OR DISPOSED IN AN EPA APPROVED SOLID WASTE MANAGEMENT FACILITY OR HAZARDOUS WASTE TREATMENT, STORAGE OR DISPOSAL FACILITIES.
  - THE CONTRACTOR SHALL CONTACT THE STATE EPA, THE LOCAL FIRE DEPARTMENT AND THE LOCAL EMERGENCY PLANNING COMMITTEE IN THE EVENT OF A PETROLEUM SPILL (>25 GALLONS) OR THE PRESENCE OF SHEEN.
  - OPEN BURNING IS NOT PERMITTED ON THE SITE.
  - CONTRACTOR TO ENSURE STREETS SHALL BE CLEARED OF DEBRIS FROM SITE AND SWEEP CLEAN ON AN AS NEEDED BASIS.



SPECIFICATIONS FOR SILT FENCE

FABRIC PROPERTIES	VALUES	TEST METHODS
GRAB TENSILE STRENGTH	90 LB. MINIMUM	ASTM D-1682
MULEN BURST STRENGTH	190 PSI MINIMUM	ASTM D-3786
SLURRY FLOW RATE	0.3 GAL/MIN/FT. MAX.	
EQUIVALENT OPENING SIZE	40-80	US STD. SIEVE CW 02215
ULTRAVIOLET RADIATION STABILITY	90% MINIMUM	ASTM - G 26

CRITERIA FOR SILT FENCE MATERIALS


- FENCE POSTS - THE LENGTH SHALL BE A MINIMUM OF 32 INCHES LONG. WOOD POSTS WILL BE 2 IN. X 2 IN. HARDWOOD OF SOUND QUALITY. THE MAXIMUM SPACING BETWEEN POSTS SHALL BE 10 FT.
- SILT FENCE FABRIC (SEE CHART BELOW)

NOTES:

- SILT FENCE SHALL BE CONSTRUCTED BEFORE UPSLOPE LAND DISTURBANCE BEGINS.
- ALL SILT FENCE SHALL BE PLACED AS CLOSE TO THE CONTOUR AS POSSIBLE SO THAT WATER WILL NOT CONCENTRATE AT LOW POINTS IN THE FENCE AND SO THAT SMALL SWALES OR DEPRESSIONS WHICH MAY CARRY SMALL CONCENTRATED FLOWS TO THE SILT FENCE ARE DISSIPATED ALONG ITS LENGTH.
- TO PREVENT WATER PONDED BY THE SILT FENCE FROM FLOWING AROUND THE ENDS, EACH END SHALL BE CONSTRUCTED UPSLOPE SO THAT THE ENDS ARE AT A HIGHER ELEVATION.
- WHERE POSSIBLE, SILT FENCE SHALL BE PLACED ON THE FLATTEST AREA AVAILABLE.
- WHERE POSSIBLE, VEGETATION SHALL BE PRESERVED FOR 5 FT. (OR AS MUCH AS POSSIBLE) UPSLOPE FROM THE SILT FENCE. IF VEGETATION IS REMOVED, IT SHALL BE ESTABLISHED WITHIN 7 DAYS FROM THE INSTALLATION OF THE SILT FENCE.
- THE HEIGHT OF THE SILT FENCE SHALL BE A MINIMUM OF 16 IN. ABOVE THE ORIGINAL GROUND SURFACE.
- THE SILT FENCE SHALL BE PLACED IN A TRENCH CUT A MINIMUM F 6 IN. DEEP. THE TRENCH SHALL BE CUT WITH A TRENCHER, CABLE LAYING MACHINE, OR OTHER SUITABLE DEVICES WHICH WILL ENSURE ADEQUATE UNIFORM TRENCH DEPTH.
- THE SILT FENCE SHALL BE PLACED WITH THE STAKES ON THE DOWNSLOPE SIDE OF THE GEOTEXTILE AND SO THAT THE 8 INCHES OF CLOTH ARE BELOW THE GROUND SURFACE. EXCESS MATERIAL SHALL LAY ON THE BOTTOM OF THE 6 IN. DEEP TRENCH. THE TRENCH SHALL BE BACKFILLED AND COMPACTED.
- SEAMS BETWEEN SECTIONS OF SILT FENCE SHALL BE OVERLAPPED WITH THE END STAKES OF EACH SECTION WRAPPED TOGETHER BEFORE DRIVING INTO THE GROUND.
- MAINTENANCE - SILT FENCE SHALL ALLOW RUNOFF TO PASS ONLY AS DIFFUSE FLOW THROUGH THE GEOTEXTILE. IF RUNOFF OVERTOPS SILT FENCE, FLOWS UNDER OR AROUND THE ENDS, OR IN ANY OTHER WAY BECOMES A CONCENTRATED FLOW, ONLY OF THE FOLLOWING SHALL BE PERFORMED, AS APPROPRIATE:
  - THE LAYOUT OF THE SILT FENCE SHALL BE CHANGED,
  - ACCUMULATED SEDIMENT SHALL BE REMOVED, OR
  - OTHER PRACTICES SHALL BE INSTALLED.

SILT FENCE

NTS




SECTION

NOTES:

- INLET PROTECTION SHALL BE CONSTRUCTED EITHER BEFORE UPSLOPE LAND DISTURBANCE BEGINS OR BEFORE THE INLET BECOMES FUNCTIONAL.
- THE EARTH AROUND THE INLET SHALL BE EXCAVATED COMPLETELY TO A DEPTH AT LEAST 18 INCHES.
- THE WOODEN FRAME SHALL BE CONSTRUCTED OF 2-INCH BY 4-INCH CONSTRUCTION GRADE LUMBER. THE 2-INCH BY 4-INCH POSTS SHALL BE DRIVEN 18" INTO THE GROUND AT FOUR CORNERS OF THE INLET AND THE TOP PORTION OF 2-INCH BY 4-INCH FRAME ASSEMBLED USING THE OVERLAP JOINT SHOWN. THE TOP OF THE FRAME SHALL BE AT LEAST 6 INCHES BELOW ADJACENT ROADS IF PONDED WATER WILL POSE A SAFETY HAZARD TO TRAFFIC.
- WIRE MESH SHALL BE OF SUFFICIENT STRENGTH TO SUPPORT FABRIC WITH WATER FULLY IMPOUNDED AGAINST IT. IT SHALL BE STRETCHED TIGHTLY AROUND THE FRAME AND FASTENED SECURELY TO THE FRAME.
- GEOTEXTILE MATERIAL SHALL HAVE AN EQUIVALENT OPENING SIZE OF 20-40 Sieve and BE RESISTANT TO SUNLIGHT. IT SHALL BE STRETCHED TIGHTLY AROUND THE FRAME AND FASTENED SECURELY. IT SHALL EXTEND FROM THE TOP OF THE FRAME TO 18 INCHES BELOW THE INLET NOTCH ELEVATION. THE GEOTEXTILE SHALL OVERLAP ACROSS ONE SIDE OF THE INLET SO THE ENDS OF THE CLOTH ARE NOT FASTENED TO THE SAME POST.
- BACKFILL SHALL BE PLACED AROUND THE INLET IN COMPACTED 6 INCH LAYERS UNTIL THE EARTH IS EVEN WITH NOTCH ELEVATION ON ENDS AND TOP ELEVATION ON SIDES.
- A COMPACTED EARTH DIKE OR CHECK DAM SHALL BE CONSTRUCTED IN THE DITCH LINE BELOW THE INLET IF THE INLET IS NOT IN A DEPRESSION. THE TOP OF THE DIKE SHALL BE AT LEAST 6 INCHES HIGHER THAN THE TOP OF THE FRAME.

AREA INLET PROTECTION

NTS




NOTE:


INLET PROTECTION SHALL BE DANDY BAG OR APPROVED OTHER.

INLET PROTECTION

NTS



SECTION  
NTS



NOTES:

- ALL MATERIAL TO MEET SPECIFICATIONS.
- COMPOST SOCKS FILL TO MEET APPLICATION REQUIREMENTS.
- FILTER MEDIA TO BE DISPERSED ON SITE, AS DETERMINED BY ENGINEER.

PLAN  
NTS

COMPOST SOCK ON LAND

NTS



CESO  
WWW.CESOINC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID Description Date

© 2025 CESO, INC.

Project Number: 765295

Scale: N/A

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025


Issue: PERMIT SET

Drawing Title:

SWPPP NOTES &  
DETAILS

C6.0


C:\D:\ACD\Draws\CESO\CCCC - Hudson - Civil Master Plan Study\Project Files\CESO\CCCC-CIVIL\PLAN\LOT\Major Site Plans\765295 - SWPPP NOTES.dwg - 5/21/2025 - Jake McDaniel



- NOTES:
1. ACTUAL LAYOUT DETERMINED IN THE FIELD.
  2. THE CONCRETE WASHOUT SIGN SHALL BE INSTALLED WITHIN 30' OF THE TEMPORARY CONCRETE WASHOUT FACILITY.
  3. THE WASHOUT MUST HAVE SUFFICIENT VOLUME TO CONTAIN ALL LIQUID AND CONCRETE WASTE GENERATED BY WASHOUT OPERATIONS INCLUDING BUT NOT LIMITED TO OPERATIONS ASSOCIATED WITH GROUT AND MORTAR.

### CONCRETE WASHOUT

NTS



- NOTES:
1. PREPARE SOIL BEFORE INSTALLING BLANKETS, INCLUDING ANY NECESSARY APPLICATION OF LIME, FERTILIZER, AND SEED.
  2. BEGIN AT THE TOP OF THE SLOPE BY ANCHORING THE BLANKET IN A 6" DEEP BY 6" WIDE TRENCH WITH APPROXIMATELY 12" OF BLANKET EXTENDED BEYOND THE UP-SLOPE PORTION OF THE TRENCH AS SHOWN IN DETAIL.
  3. ROLL THE BLANKETS (A.) DOWN OR (B.) HORIZONTALLY ACROSS THE SLOPE. BLANKETS WILL UNROLL WITH APPROPRIATE SIDE AGAINST THE SOIL SURFACE. ALL BLANKETS MUST BE SECURELY FASTENED TO SOIL SURFACE BY PLACING STAPLES/STAKES IN APPROPRIATE LOCATIONS AS PER MANUFACTURES RECOMMENDATION.
  4. THE EDGES OF PARALLEL BLANKETS MUST BE STAPLED WITH MINIMUM 6" OVERLAP. TO ENSURE PROPER SEAM ALIGNMENT, PLACE THE EDGE OF THE OVERLAPPING BLANKET (BLANKET BEING INSTALLED ON TOP) EVEN WITH THE SEAM STITCH ON THE PREVIOUSLY INSTALLED BLANKET.
  5. CONSECUTIVE BLANKETS SPICED DOWN THE SLOPE MUST BE PLACED END OVER END (SHINGLE STYLE) WITH AN APPROXIMATE 3" OVERLAP. STAPLE THROUGH OVERLAPPED AREA, APPROXIMATELY 12" APART ACROSS ENTIRE BLANKET WIDTH.
  6. PLACE STAPLES/STAKES PER MANUFACTURER'S RECOMMENDATION FOR THE APPROPRIATE SLOPE BEING APPLIED.

### EROSION CONTROL BLANKET

NTS

- NOTES:
1. STONE SIZE - (1.5-2.5 INCH) STONE SHALL BE USED, OR RECYCLED CONCRETE EQUIVALENT.
  2. LENGTH - THE CONSTRUCTION ENTRANCE SHALL BE AS LONG AS REQUIRED TO STABILIZE HIGH TRAFFIC AREAS BUT NOT LESS THAN 70 FT. (EXCEPTION: APPLY 30 FT. MINIMUM TO SINGLE RESIDENCE LOTS.
  3. THICKNESS - THE STONE LAYER SHALL BE AT LEAST 6 INCHES THICK FOR LIGHT DUTY ENTRANCES OR AT LEAST 10 INCHES FOR HEAVY DUTY USE.
  4. WIDTH - THE ENTRANCE SHALL BE AT LEAST 14 FEET WIDE, BUT NOT LESS THAN THE FULL WIDTH AT POINTS WHERE INGRESS OR EGRESS OCCURS.
  5. GEOTEXTILE - A GEOTEXTILE SHALL BE LAID OVER THE ENTIRE AREA PRIOR TO PLACING STONE. IT SHALL BE COMPOSED OF STRONG ROT-PROOF POLYMERIC FIBERS AND MEET THE FOLLOWING SPECIFICATIONS:
  6. TIMING - THE CONSTRUCTION ENTRANCE SHALL BE INSTALLED AS SOON AS IS PRACTICAL BEFORE MAJOR GRADING ACTIVITIES.
  7. CULVERT - A PIPE OR CULVERT SHALL BE CONSTRUCTED UNDER THE ENTRANCE IF NEEDED TO PREVENT SURFACE WATER FROM FLOWING ACROSS THE ENTRANCE OR TO PREVENT RUNOFF FROM BEING DIRECTED OUT ONTO PAVED SURFACES.
  8. WATER BAR - A WATER BAR SHALL BE CONSTRUCTED AS PART OF THE CONSTRUCTION ENTRANCE IF NEEDED TO PREVENT SURFACE RUNOFF FROM FLOWING THE LENGTH OF THE CONSTRUCTION ENTRANCE AND OUT ONTO PAVED SURFACES.
  9. MAINTENANCE - TOP DRESSING OF ADDITIONAL STONE SHALL BE APPLIED AS CONDITIONS DEMAND. MUD SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC ROADS, OR ANY SURFACE WHERE RUNOFF IS NOT CHECKED BY SEDIMENT CONTROLS, SHALL BE REMOVED IMMEDIATELY. REMOVAL SHALL BE ACCOMPLISHED BY SCRAPING OR SWEEPING.
  10. CONSTRUCTION ENTRANCES SHALL NOT BE RELIED UPON TO REMOVE MUD FROM VEHICLES AND PREVENT OFF-SITE TRACKING. VEHICLES THAT ENTER AND LEAVE THE CONSTRUCTION-SITE SHALL BE RESTRICTED FROM MUDDY AREAS.
  11. REMOVAL - THE ENTRANCE SHALL REMAIN IN PLACE UNTIL THE DISTURBED AREA IS STABILIZED OR REPLACED WITH A PERMANENT ROADWAY OR ENTRANCE.

### STABILIZED CONSTRUCTION ENTRANCE

NTS

GEOTEXTILE SPECIFICATION FOR CONSTRUCTION ENTRANCE	
MINIMUM TENSILE STRENGTH	200 lbs.
MINIMUM PUNCTURE STRENGTH	80 psi.
MINIMUM TEAR STRENGTH	50 lbs.
MINIMUM BURST STRENGTH	320 psi.
MINIMUM ELONGATION	20%
EQUIVALENT OPENING SIZE	EOS < 0.6 mm.
PERMITIVITY	1x10-3 cm/sec.



**CESO**  
WWW.CESONINC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY  
CHAPEL**

750 W. STREETSBOBO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.


Project Number: 765295  
Scale: AS SHOWN  
Drawn By: KAN  
Checked By: JMS  
Date: 5/22/2025  
Issue: PERMIT SET

Drawing Title:  
**SWPPP DETAILS**

**C6.1**



C:\DC\ACD\at\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\03-CIVIL\PLAN\LOT\Major Site Plans\765295\_SWPPP.dwg - 5/21/2025 - Jake McDaniel



SWPPP LEGEND

EXISTING	
REFER TO ##### FOR EXISTING FEATURES LEGEND	
PROPOSED	
	MAJOR CONTOUR
	MINOR CONTOUR
	PAVEMENT/WALK
	STORM SEWER
	SILT FENCE
	COMPOST SOCK
	GRADING/SEEDING LIMITS
	LIMIT OF DISTURBANCE
	STABILIZED CONSTRUCTION ENTRANCE
	STORAGE AREA
	INLET PROTECTION
	STORM MANHOLE
	CATCH BASIN
	CURB INLET
	STABILIZED CONSTRUCTION ENTRANCE
	TEMPORARY SEEDING
	PERMANENT SOD
	CONCRETE WASHOUT AREA
	SKIMMER
	TREE PROTECTION FENCE

GENERAL NOTES


- ADDITIONAL EROSION AND SEDIMENT CONTROLS MAY BE REQUIRED AS IDENTIFIED WITH OEPA AND LOCAL JURISDICTION INSPECTOR.
- CONTRACTOR SHALL REVIEW THE COMPLETE DRAWING SET AND NOTIFY THE DESIGN PROFESSIONAL IN WRITING PRIOR TO CONSTRUCTION, IF ANY DISCREPANCIES ARE FOUND WITHIN THE DRAWINGS OR WITH ACTUAL FIELD CONDITIONS.
- ALL STORMWATER POLLUTION PREVENTION PLANS, NOTES AND DETAILS SHALL COMPLY WITH THE OEPA RAINWATER AND LAND DEVELOPMENT MANUAL.
- CONTRACTOR IS RESPONSIBLE TO MAINTAIN POST-CONSTRUCTION PERMANENT EROSION CONTROL MEASURES UNTIL ADEQUATE RE-VEGETATION AND STABILIZATION ARE ACHIEVED.
- REMOVE ALL ON SITE FEATURES AS SHOWN ON THE PLAN AND LEGALLY DISPOSE OFF SITE.
- PROTECT EXISTING SITE FEATURES TO REMAIN OUTSIDE CONSTRUCTION LIMITS. REPAIR ANY DAMAGE TO THE SATISFACTION OF THE OWNER AT NO ADDITIONAL COST.
- USE ANY MEANS NECESSARY AND ACCEPTABLE TO THE JURISDICTION TO CONTROL DUST AT THE SITE. PROVIDE STREET CLEANING WHEN NECESSARY OR AS DIRECTED.
- SILT FENCE SHOWN OFF OF LIMITS OF DISTURBANCE FOR CLARITY PURPOSES ONLY. CONTRACTOR TO ENSURE SILT FENCE IS PLACED AT LIMITS OF DISTURBANCE. ANY DISCREPANCIES SHOULD BE BROUGHT TO THE ENGINEER PRIOR TO PLACEMENT OF ANY EROSION CONTROL MEASURES.

SEQUENCE OF CONSTRUCTION - (PHASE ONE)

UNLESS NOTED OTHERWISE, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL EROSION AND SEDIMENT CONTROL MEASURES IN STRICT ACCORDANCE WITH THE SWPPP THROUGHOUT THE DURATION OF THE PROJECT.

- ENSURE NOTICE OF INTENT (N.O.I.) IS FILED. KEEP A COPY OF THE PERMIT AND SWPPP ON SITE.
- INSTALL ALL TEMPORARY EROSION CONTROL MEASURES AS SHOWN ON THE SWPPP.
- INSTALL SEDIMENT BASIN PER PLAN.
- INSPECTION OF EROSION CONTROL MEASURES AS OUTLINED IN NOTES. REPAIRS AND/OR REPLACEMENTS SHALL BE MADE AS NECESSARY.
- SITE DEMOLITION AND CLEARING.

NOTE: IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE THAT ALL SOIL EROSION CONTROL MEASURES ARE INSTALLED AND MAINTAINED DURING CONSTRUCTION.



FORTY- EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



CESO  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: 1"=50'

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET


Drawing Title:

SWPPP PHASE 1

C6.2



C:\D:\ACD\Draws\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\03-CIVIL\PLAN\LOT Major Site Plans\765295\_SWPPP.dwg - 5/21/2025 - Jake McDaniel



#### SWPPP LEGEND

##### EXISTING

REFER TO ALTA SURVEY BY DIEBEL FOR EXISTING FEATURES LEGEND

##### PROPOSED

- |  |                                  |
|--|----------------------------------|
|  | MAJOR CONTOUR                    |
|  | MINOR CONTOUR                    |
|  | PAVEMENT/WALK                    |
|  | STORM SEWER                      |
|  | SILT FENCE                       |
|  | COMPOST SOCK                     |
|  | GRADING/SEEDING LIMITS           |
|  | LIMIT OF DISTURBANCE             |
|  | STABILIZED CONSTRUCTION ENTRANCE |
|  | CONCRETE WASHOUT                 |
|  | INLET PROTECTION                 |
|  | STORM MANHOLE                    |
|  | CATCH BASIN                      |
|  | CURB INLET                       |
|  | STABILIZED CONSTRUCTION ENTRANCE |
|  | TEMPORARY SEEDING                |
|  | PERMANENT SOD                    |
|  | CONCRETE WASHOUT AREA            |
|  | INLET PROTECTION                 |

#### GENERAL NOTES

- ADDITIONAL EROSION AND SEDIMENT CONTROLS MAY BE REQUIRED AS IDENTIFIED WITH OEPA AND LOCAL JURISDICTION INSPECTOR.
- CONTRACTOR SHALL REVIEW THE COMPLETE DRAWING SET AND NOTIFY THE DESIGN PROFESSIONAL IN WRITING PRIOR TO CONSTRUCTION, IF ANY DISCREPANCIES ARE FOUND WITHIN THE DRAWINGS OR WITH ACTUAL FIELD CONDITIONS.
- ALL STORMWATER POLLUTION PREVENTION PLANS, NOTES AND DETAILS SHALL COMPLY WITH THE OEPA RAINWATER AND LAND DEVELOPMENT MANUAL.
- CONTRACTOR IS RESPONSIBLE TO MAINTAIN POST-CONSTRUCTION PERMANENT EROSION CONTROL MEASURES UNTIL ADEQUATE RE-VEGETATION AND STABILIZATION ARE ACHIEVED.
- REMOVE ALL ON SITE FEATURES AS SHOWN ON THE PLAN AND LEGALLY DISPOSE OFF SITE.
- PROTECT EXISTING SITE FEATURES TO REMAIN OUTSIDE CONSTRUCTION LIMITS. REPAIR ANY DAMAGE TO THE SATISFACTION OF THE OWNER AT NO ADDITIONAL COST.
- USE ANY MEANS NECESSARY AND ACCEPTABLE TO THE JURISDICTION TO CONTROL DUST AT THE SITE. PROVIDE STREET CLEANING WHEN NECESSARY OR AS DIRECTED.
- SILT FENCE SHOWN OFF OF LIMITS OF DISTURBANCE FOR CLARITY PURPOSES ONLY. CONTRACTOR TO ENSURE SILT FENCE IS PLACED AT LIMITS OF DISTURBANCE. ANY DISCREPANCIES SHOULD BE BROUGHT TO THE ENGINEER PRIOR TO PLACEMENT OF ANY EROSION CONTROL MEASURES.

#### SEQUENCE OF CONSTRUCTION - (PHASE TWO)


UNLESS NOTED OTHERWISE, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL EROSION AND SEDIMENT CONTROL MEASURES IN STRICT ACCORDANCE WITH THE SWPPP THROUGHOUT THE DURATION OF THE PROJECT.

- INSPECTION OF EROSION CONTROL MEASURES INSTALLED UNDER PHASE ONE AS OUTLINED IN NOTES. REPAIRS AND/OR REPLACEMENTS SHALL BE MADE AS NECESSARY.
- INSTALL ALL TEMPORARY EROSION CONTROL MEASURES AS SHOWN ON THE SOIL EROSION PLAN FOR PHASE TWO.
- ROUGH GRADING. PROVIDE SOIL STABILIZATION OF DISTURBED AREAS WHICH ARE INACTIVE. REFER TO NPDES PERMIT REQUIREMENTS AND SWPPP DETAILS FOR ADDITIONAL INFORMATION.

- STORM SEWER SYSTEM AND UNDERGROUND UTILITY CONSTRUCTION, INCLUDING SANITARY SEWER FORCEMAIN WORK. INSTALL INLET PROTECTION CONCURRENT WITH CONSTRUCTION OF PROPOSED STORM SEWER STRUCTURES.

- RESTROOM BUILDING PAD CONSTRUCTION.
- FINE GRADING AND PAVEMENT SUBGRADE PREPARATION.
- CONCRETE PAVING AND REMAINING CONCRETE FLATWORK.
- PREPARATION OF LANDSCAPED AREAS TO FINISHED GRADE.

NOTE: IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE THAT ALL SOIL EROSION CONTROL MEASURES ARE INSTALLED AND MAINTAINED DURING CONSTRUCTION.



FORTY- EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



**CESO**  
WWW.CESOINC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: 1"=50'

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET


Drawing Title:

**SWPPP PHASE 2**

**C6.3**



C:\DC\ACD\Draws\CESOC\CC - Hudson - Civil Master Plan Study\Project Files\CESOC\CC-CIVIL\PLAN\LOT\Major Site Plans\765295 SWPPP.dwg - 5/21/2025 - Jake McDaniel



#### SEQUENCE OF CONSTRUCTION - (PHASE THREE)

UNLESS NOTED OTHERWISE, THE GENERAL CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL EROSION AND SEDIMENT CONTROL MEASURES IN STRICT ACCORDANCE WITH THE SWPPP THROUGHOUT THE DURATION OF THE PROJECT.

- INSPECTION OF EROSION CONTROL MEASURES INSTALLED UNDER PHASE ONE AND TWO AS OUTLINED IN NOTES. REPAIRS AND/OR REPLACEMENTS SHALL BE MADE AS NECESSARY.
- INSTALL ALL TEMPORARY EROSION CONTROL MEASURES AS SHOWN ON THE SOIL EROSION PLAN FOR PHASE TWO.
- COMPLETE FINE GRADING AND PREPARATION OF LANDSCAPED AREAS TO FINISHED GRADE.
- PERMANENT BMP's.
- FINAL STABILIZATION AND PERMANENT SEEDING. REFER TO THE NPDES REQUIREMENTS FOR ADDITIONAL INFORMATION. REFER TO LANDSCAPE PLAN FOR SOD LIMITS AND PLANTING AREAS.

- REMOVE SOIL EROSION CONTROL MEASURES AFTER PERMANENT VEGETATION HAS BEEN ESTABLISHED. ENSURE NOTICE OF COMPLETION (N.O.C.) IS FILED.

NOTE: IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE THAT ALL SOIL EROSION CONTROL MEASURES ARE INSTALLED AND MAINTAINED DURING CONSTRUCTION. CONTRACTOR IS ALSO RESPONSIBLE FOR REMOVAL OF ALL TEMPORARY EROSION CONTROL MEASURES AFTER PERMANENT VEGETATION HAS BEEN ESTABLISHED.

#### SWPPP LEGEND

##### EXISTING

REFER TO ALTA SURVEY BY DIEBEL FOR EXISTING FEATURES LEGEND


##### PROPOSED

- MAJOR CONTOUR
- MINOR CONTOUR
- PAVEMENT/WALK
- STORM SEWER
- SILT FENCE
- COMPOST SOCK
- GRADING/SEEDING LIMITS
- LIMIT OF DISTURBANCE

- EROSION CONTROL BLANKET ON ALL 3:1 SLOPES OR STEEPER
- STABILIZED CONSTRUCTION ENTRANCE
- CONCRETE WASHOUT
- INLET PROTECTION
- STORM MANHOLE
- CATCH BASIN
- CURB INLET
- STABILIZED CONSTRUCTION ENTRANCE
- TEMPORARY SEEDING
- SOIL STABILIZATION
- CONCRETE WASHOUT AREA
- INLET PROTECTION

#### GENERAL NOTES

- ADDITIONAL EROSION AND SEDIMENT CONTROLS MAY BE REQUIRED AS IDENTIFIED WITH OEPA AND LOCAL JURISDICTION INSPECTOR.
- CONTRACTOR SHALL REVIEW THE COMPLETE DRAWING SET AND NOTIFY THE DESIGN PROFESSIONAL IN WRITING PRIOR TO CONSTRUCTION, IF ANY DISCREPANCIES ARE FOUND WITHIN THE DRAWINGS OR WITH ACTUAL FIELD CONDITIONS.
- ALL STORMWATER POLLUTION PREVENTION PLANS, NOTES AND DETAILS SHALL COMPLY WITH THE OEPA RAINWATER AND LAND DEVELOPMENT MANUAL.
- CONTRACTOR IS RESPONSIBLE TO MAINTAIN POST-CONSTRUCTION PERMANENT EROSION CONTROL MEASURES UNTIL ADEQUATE RE-VEGETATION AND STABILIZATION ARE ACHIEVED.
- REMOVE ALL ON SITE FEATURES AS SHOWN ON THE PLAN AND LEGALLY DISPOSE OFF SITE.
- PROTECT EXISTING SITE FEATURES TO REMAIN OUTSIDE CONSTRUCTION LIMITS. REPAIR ANY DAMAGE TO THE SATISFACTION OF THE OWNER AT NO ADDITIONAL COST.
- USE ANY MEANS NECESSARY AND ACCEPTABLE TO THE JURISDICTION TO CONTROL DUST AT THE SITE. PROVIDE STREET CLEANING WHEN NECESSARY OR AS DIRECTED.
- SILT FENCE SHOWN OFF OF LIMITS OF DISTURBANCE FOR CLARITY PURPOSES ONLY. CONTRACTOR TO ENSURE SILT FENCE IS PLACED AT LIMITS OF DISTURBANCE. ANY DISCREPANCIES SHOULD BE BROUGHT TO THE ENGINEER PRIOR TO PLACEMENT OF ANY EROSION CONTROL MEASURES.



FORTY-EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**  
750 W. STREETSBORO STREET  
HUDSON, OH 44236


Revisions / Submissions		
ID	Description	Date

© 2025 CESO, INC.  
Project Number: 765295  
Scale: AS SHOWN  
Drawn By: KAN  
Checked By: JMS  
Date: 5/22/2025  
Issue: PERMIT SET

Drawing Title:  
**SWPPP PHASE 3**

**C6.4**
















**UTILITY LEGEND**

**EXISTING**

REFER TO ALTA SURVEY BY DIEBEL FOR EXISTING FEATURES LEGEND

**PROPOSED**

	PAVEMENT/WALK
	STORM SEWER LINE
	SANITARY SEWER LINE
	DOMESTIC WATER SERVICE LINE
	FORCEMAIN
	CATCH BASIN
	STORM SEWER
	SANITARY SEWER
CO 	CLEANOUT
YO 	YARD DRAIN
	WATER VALVE



**SOL HARRIS/DAY ARCHITECTURE**

# CHRIST COMMUNITY CHAPEL

750 W. STREETSBO RO STREET  
HUDSON, OH 44236

Revisions / Submissions		
ID	Description	Date


© 2025 CESO, INC.	
Project Number:	76529
Scale:	1"=50'
Drawn By:	KAN
Checked By:	JMS
Date:	5/22/2025
Issue:	PERMIT SET

Drawing Title:  
**OVERALL UTILITY  
PLAN**

## C7.0

## CODED NOTES:


1. PROPOSED 2" DOMESTIC WATER SERVICE, DIRECTIONALLY BORED.
2. PROPOSED 1.25" SANITARY FORCEMAIN, DIRECTIONALLY BORED, 5' MIN. COVER, 18" CLEARANCE @0 BELOW ALL STORM AND WATER LINES.
3. PROPOSED E-ONE LIFT STATION. REFER TO SHEET C8.10 FOR DETAILS.
4. PROPOSED 6" SANITARY SEWER.
5. PROPOSED 6" CLEANOUT.
6. CONNECT TO EXISTING WATER MAIN. CONTRACTOR TO FIELD VERIFY SIZE OF MAIN AND COORDINATE CONNECTION WITH WATER COMPANY.
7. CONNECT PROPOSED 1.25" SANITARY FORCEMAIN.
8. POT HOLE TO VERIFY STORM INVERT.
9. CONTRACTOR TO FIELD VERIFY LOCATION AND DEPTH OF EXISTING STORM SEWER IN THIS LOCATION PRIOR TO ORDERING STORM STRUCTURES OR PIPE. CONFIRM WITH ENGINEER IF REUSE OF EXISTING PIPE IS FEASIBLE.



FORTY- EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



C:\D:\ACD\Draws\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\03-CIVIL\PLAN\LOT Major Site Plans\765295\_UTILITY PLAN.dwg - 5/22/2025 - Jalee McDaniel



#### UTILITY LEGEND

##### EXISTING

REFER TO ALTA SURVEY BY DIEBEL FOR EXISTING FEATURES LEGEND

##### PROPOSED

—	PAVEMENT/WALK
— STM —	STORM SEWER LINE
— SAN —	SANITARY SEWER LINE
— W —	DOMESTIC WATER SERVICE LINE
— FM —	FORCEMAIN
■	CATCH BASIN
⊙	STORM SEWER MANHOLE
⊙	SANITARY SEWER MANHOLE
○	CLEANOUT
•	YARD DRAIN
+	WATER VALVE

#### STORM SEWER STRUCTURE SCHEDULE

NO.	STRUCTURE	GRATE	INVERT
S1	GRINDER PUMP	1018.56	1013.67 (6") N 1013.56 (4") S
1	6" CO	1017.09	1013.76 (6") N 1013.76 (1.25") S
18	YARD DRAIN	1014.50	1011.45 (6") W

#### CODED NOTES:

1. PROPOSED 2" DOMESTIC WATER SERVICE. DIRECTIONALLY BORED.
2. PROPOSED 1.25" SANITARY FORCEMAIN. DIRECTIONALLY BORED, 5' MIN. COVER, 18" CLEARANCE O/O BELOW ALL STORM AND WATER LINES.
3. PROPOSED E-ONE LIFT STATION. REFER TO SHEET C8.10 FOR DETAILS.
4. PROPOSED 6" SANITARY SEWER.
5. PROPOSED 6" CLEANOUT.
6. PROPOSED HEADWALL. REFER TO ODOT DETAIL HW-2.1.
7. PROPOSED CATCH BASIN. REFER TO DETAIL ON SHEET C8.6.
8. PROPOSED STORM MANHOLE. REFER TO ODOT DETAIL MH-1.
9. INSTALL KNOX BOX ON BUILDING. CONTRACTOR TO COORDINATE WITH FIRE DEPARTMENT TO DETERMINE FINAL LOCATION.
10. PROPOSED YARD DRAIN INLET. REFER TO DETAIL ON SHEET C8.6.



**CESO**  
WWW.CESONINC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY  
CHAPEL**

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: 1"=20'

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET

Drawing Title:

**FIELD UTILITY PLAN**




**C7.1**



FORTY-EIGHT (48) HOURS  
BEFORE DIGGING IS TO  
COMMENCE, THE CONTRACTORS  
SHALL NOTIFY THE FOLLOWING  
AGENCIES: OHIO UTILITIES  
PROTECTION SERVICE AT 811 OR  
800-362-2764 AND ALL OTHER  
AGENCIES WHICH MIGHT HAVE  
UNDERGROUND UTILITIES  
INVOLVING THIS PROJECT AND  
ARE NONMEMBERS OF STATE  
UTILITIES PROTECTION SERVICE



C:\D:\ACCD\Draws\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\03-CIVIL\PLAN\LOT Major Site Plans\765295\_UTILITY PLAN.dwg - 5/21/2025 - Jalee McDaniel



FORTY-EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**

750 W. STREETSBO RO STREET  
HUDSON, OH 44236





Revisions / Submissions		
ID	Description	Date

© 2025 CESO, INC.  
Project Number: 765295  
Scale: AS SHOWN  
Drawn By: KAN  
Checked By: JMS  
Date: 5/22/2025  
Issue: PERMIT SET

Drawing Title:  
**FORCEMAIN PROFILE**

**C7.2**

C:\D:\ACCD\Draws\CESO\CCCC - Hudson - Civil Master Plan Study\Project Files\CESO\CCCC-CIVIL\PLAN\PILOT\Major Site Plans\765295 CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel




NOTES:

1. ALL CONCRETE CURBS AND SIDEWALKS TO BE 4000 P.S.I. CONCRETE.
2. SIDEWALK TO BE SLOPED 2% MAX. AWAY FROM BUILDING.
3. ALL SIDEWALKS SHALL BE BROOM FINISHED.

CONCRETE SIDEWALK

NTS




CONCRETE PAVEMENT

PAVEMENT LAYER DEPTHS		
	CONCRETE	
	A	B
STANDARD DUTY	6"	6"


PAVEMENT SECTION

NTS




BOLLARD

NTS



"NO PARKING ANY TIME" (R7-1)  
SIGN DETAIL



CESO  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number:	765295
Scale:	AS SHOWN
Drawn By:	KAN
Checked By:	JMS
Date:	5/22/2025
Issue:	PERMIT SET

Drawing Title:

CONSTRUCTION  
DETAILS

C8.0





C:\DC\ACD\at\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\ CESO103-CVIL\PLAN\LOT\Major Site Plans\765295\_ CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel

CITY OF HUDSON SECTION 2. WATER DISTRIBUTION REQUIREMENTS -CONTINUED

2.16 - BACKFLOW PREVENTION DEVICES, ENCLOSURES AND THERMAL EXPANSION CONTROL

- A. GENERAL - BACKFLOW PREVENTION DEVICES SHALL BE PROVIDED FOR, BUT NOT LIMITED TO, THE FOLLOWING CIRCUMSTANCES: ALL COMMERCIAL AND INDUSTRIAL BUILDINGS, FIRE LINES, IN-GROUND IRRIGATION SYSTEMS, SWIMMING POOLS, PROPERTIES WITH AUXILIARY WATER SUPPLY (WELLS), AND OTHER CIRCUMSTANCES AS DETERMINED BY THE CITY AND/OR CITY ORDINANCE AND ASSOCIATED RULES AND REGULATIONS FOR BACKFLOW PREVENTION, LATEST EDITION. THE CITY SHALL REVIEW AND APPROVE ALL DRAWINGS FOR BACKFLOW PREVENTION, BACKFLOW PREVENTION DEVICES, EXCEPT FOR FIRE SUPPRESSION SYSTEMS AND IN-GROUND IRRIGATION SYSTEMS, SHALL BE A MINIMUM OF A TESTABLE, REDUCED PRESSURE PRINCIPLE ASSEMBLY (ASSE 1013 OR ASSE 1047), FIRE SUPPRESSION SYSTEMS SHALL BE PROVIDED WITH A MINIMUM OF A TESTABLE, DOUBLE CHECK BACKFLOW ASSEMBLY (ASSE 1015 OR ASSE 1048) PROVIDED NO OTHER HAZARD OR CONDITION EXISTS REQUIRING THE USE OF A DIFFERENT BACKFLOW DEVICE. IN-GROUND IRRIGATION SYSTEMS SHALL BE PROVIDED WITH EITHER A TESTABLE REDUCED PRESSURE PRINCIPLE ASSEMBLY (ASSE 1013) OR A TESTABLE, PRESSURE VACUUM BREAKER (ASSE 1020). ALL BACKFLOW PREVENTION DEVICES MUST BE PROTECTED FROM FREEZING IF APPLICABLE IN THE FOLLOWING WAYS: INSTALLED IN A HEATED BUILDING OR APPROVED HEATED ENCLOSURE. ANY BACKFLOW DEVICE THAT IS NOT IN SERVICE DURING FREEZING WEATHER MAY BE PROTECTED BY COMPLETELY REMOVING ANY MOISTURE FROM THE DEVICE OR BY REMOVING THE DEVICE COMPLETELY FROM THE SYSTEM AND STORED IN A HEATED LOCATION. BACKFLOW PREVENTION DEVICES AND ENCLOSURES SHALL BE INSTALLED DOWNSTREAM OF THE METER AND SHALL REMAIN THE PROPERTY OF THE PROPERTY OWNER FOR MAINTENANCE AND OPERATION REQUIREMENTS.
- B. APPROVED BACKFLOW PREVENTION ASSEMBLY - APPROVED BACKFLOW PREVENTION ASSEMBLIES SHALL BE INCLUDED ON THE OHIO EPA LIST OF APPROVED BACKFLOW PREVENTION DEVICES, LATEST EDITION, OR APPROVED BY THE CITY.
- C. BACKFLOW PREVENTION DEVICE INSTALLATION - ALL BACKFLOW ASSEMBLIES SHALL BE INSTALLED IN SUCH A MANNER SO TO BE READILY ACCESSIBLE FOR INSPECTION, TESTING, AND MAINTENANCE. TEST COCKS CANNOT FACE TOWARDS A WALL OR OTHERWISE BE OBSTRUCTED. ALL BACKFLOW ASSEMBLIES SHALL BE INSTALLED "IN LINE" AND MUST NOT BE SMALLER THAN THE WATER METER SUPPLY LINE. ALL BACKFLOW ASSEMBLIES SHALL BE INSPECTED AND TESTED AT THE TIME OF INSTALLATION BY A STATE OF OHIO CERTIFIED BACKFLOW TESTER, WITH THE RESULTS BEING RECORDED ON A CITY-PROVIDED TEST FORM AND FORWARDED TO THE ADDRESS ON THE FORM.
1. PRESSURE VACUUM BREAKER INSTALLED AS FOLLOWS:
    - A. SHALL BE INSTALLED AT LEAST 12 INCHES ABOVE ALL DOWNSTREAM PIPING AND THE HIGHEST OUTLET OR FLOOD LEVEL RIM, OF THE FIXTURE(S) BEING SUPPLIED.
    - B. SHALL BE INSTALLED IN A VERTICAL POSITION WITH ADEQUATE SPACE TO FACILITATE MAINTENANCE AND TESTING.
    - C. SHALL BE INSTALLED IN AN AREA WHERE WATER SPILLAGE FROM THE AIR INLET VALVE IS NOT OBJECTIONABLE TO THE CONSUMER.
    - D. SHUT-OFF VALVES MAY BE INSTALLED ON THE DOWNSTREAM SIDE OF PRESSURE VACUUM BREAKERS.
    - E. DOUBLE CHECK VALVE ASSEMBLY INSTALLED AS FOLLOWS:
      - A. DOUBLE CHECK VALVE ASSEMBLIES SHALL BE INSTALLED IN A HORIZONTAL POSITION UNLESS SPECIFIED OTHERWISE BY THE MANUFACTURER AND APPROVED BY THE CITY.
      - B. INSTALLATION ABOVE GROUND LEVEL IS PREFERRED. WHERE ABOVE GROUND INSTALLATIONS ARE NOT REASONABLY PRACTICAL, A PIT OR VAULT MAY BE USED.
      - C. REDUCED PRESSURE PRINCIPLE ASSEMBLY INSTALLED AS FOLLOWS:
        - A. REDUCED PRESSURE PRINCIPLE BACKFLOW PREVENTION DEVICES SHALL BE INSTALLED ABOVE GROUND LEVEL OR FLOOR LEVEL, WHICHEVER IS HIGHER, IF INSTALLED IN AN AREA PRONE TO FLOODING.
        - B. REDUCED PRESSURE PRINCIPLE BACKFLOW PREVENTION DEVICES SHALL BE INSTALLED IN A HORIZONTAL POSITION UNLESS SPECIFIED OTHERWISE BY THE MANUFACTURER AND APPROVED BY THE CITY.
        - C. INSTALLED SO THAT THERE IS NO VISIBLE DISCHARGE FROM THE RELIEF VALVE PORT.
        - D. INSTALLED WITH A DRAIN TO RECEIVE SPILLAGE FROM THE RELIEF VALVE PORT IF THE DEVICE IS LOCATED WITHIN A BUILDING. THE RELIEF VALVE PORT, IF PIPED TO A DRAIN, MUST INCLUDE AN APPROVED AIR GAP SEPARATION AT THE DISCHARGE OPENING OF THE RELIEF VALVE PORT.
        - E. THE INSTALLATION OF THIS DEVICE IN A VAULT OR PIT IS PROHIBITED.
      - D. THERMAL EXPANSION CONTROL - PER THE OHIO BASIC BUILDING CODE, WHERE A BACKFLOW PREVENTION DEVICE IS INSTALLED ON A WATER SUPPLY SYSTEM UTILIZING STORAGE WATER HEATING EQUIPMENT SUCH THAT THERMAL EXPANSION CAUSES AN INCREASE IN PRESSURE, A THERMAL EXPANSION TANK FOR CONTROLLING PRESSURE SHALL BE INSTALLED. THE EXPANSION TANK SHALL BE INSTALLED IN THE COLD WATER SERVICE PIPING ON THE SUPPLY SIDE OF THE HOT WATER HEATER PRIOR TO ANY CONTROL VALVES. THE SIZE OF THE EXPANSION TANK IS BASED UPON THE SIZE OF THE HOT WATER HEATER AND MAY BE DETERMINED BY REFERRING TO THE MANUFACTURER RECOMMENDATIONS.
      - E. BACKFLOW PREVENTION DEVICE ENCLOSURE - THE ENCLOSURE, DEPENDING ON LOCATION, MAY BE AN EXISTING OR NEW BUILDING WHICH IS HEATED; AND WHICH MEETS THE REQUIREMENTS OF THE ARCHITECTURAL REVIEW BOARD (IF NEW) AND OTHER BUILDING ORDINANCES. IF AN EXISTING BUILDING IS NOT APPROPRIATE, A HEATED ENCLOSURE SHALL BE PROVIDED INCLUDING ELECTRICAL POWER FOR HEAT, PER THE MANUFACTURER'S RECOMMENDATIONS, BASED ON SIZE OF BACKFLOW PREVENTION DEVICE. THE HEATED ENCLOSURE SHALL COMPLY WITH ASSE-1060 PERFORMANCE REQUIREMENTS FOR OUTDOOR ENCLOSURES FOR BACKFLOW PREVENTION ASSEMBLIES.
    - NEW HEATED ENCLOSURES SHALL BE EITHER A BOX STYLE, AS MANUFACTURED BY HYDROCOWL, INC. OR HOT-BOX OR A HOT-ROK STYLE AS MANUFACTURED BY HOT-BOX. BOTH STYLES SHALL FULLY ENCLOSE THE BACKFLOW PREVENTER ASSEMBLY, VALVES, HANDWHEELS AND STEMS, AND BE CONSTRUCTED ON AN ODOT CLASS QC CONCRETE PAD, AS RECOMMENDED BY THE MANUFACTURER. THE HEATING AND ELECTRICAL REQUIREMENTS SHALL COMPLY WITH MANUFACTURER'S RECOMMENDATIONS. SEE FIGURE 2.16.1.

2.17 - BACTERIA SAMPLING AND FLUSHING ASSEMBLIES

SAMPLING AND FLUSHING ASSEMBLIES WILL BE INSTALLED AS A MINIMUM EVERY 1,200 L.F. OF WATER MAIN OR AS DIRECTED BY THE CITY. A CORPORATION COCK WILL BE INSTALLED IN THE MAIN WITH A BACTERIA SAMPLING AND FLUSHING ASSEMBLY AT EACH SAMPLING LOCATION. A CURB STOP OR BALL VALVE CAN BE USED IN THE PORTION OF THE ASSEMBLY THAT IS ABOVE GROUND TO FACILITATE THE SAMPLING PROCEDURE. AT LEAST 18 INCHES OF SMOOTH COPPER TUBE MUST EXTEND BEYOND THE VALVE (LOCATED ABOVE GROUND) AND BE BENT IN A DOWNWARD ARC. ADDITIONAL LENGTH SHALL BE PROVIDED TO PREVENT FLOODING, TO GO INTO STORM CONVEYANCE SYSTEM, ETC. CONTRACTOR SHALL BE RESPONSIBLE FOR CONTROLLING DIRECTION OF FLOW TO PROPER DRAINAGE LOCATION TO PREVENT FLOODING. ONCE INSTALLED, CONTRACTOR SHALL NOT BE PERMITTED TO OPERATE OR OTHERWISE TAMPER WITH BACTERIA SAMPLING AND FLUSHING ASSEMBLIES WITHOUT APPROVAL FROM THE CITY. THE BACTERIA SAMPLING AND FLUSHING ASSEMBLY SHALL NOT BE REMOVED UNTIL THE CONTRACTOR HAS RECEIVED WRITTEN NOTICE THAT THE MAIN HAS PASSED ALL BACTERIOLOGICAL TESTS PER AWWA C651-92, SECTION 7.3 AND OHIO EPA REQUIREMENTS. SEE FIGURE 2.17.1.

MATERIALS FOR BACTERIA SAMPLING AND FLUSHING ASSEMBLIES SHALL BE AS SPECIFIED IN ITEM 2.18, WITH THE EXCEPTION THAT A BALL VALVE MAY BE SUBSTITUTED FOR THE CURB STOP. THE BALL VALVE SHALL BE BRONZE, TWO PIECE BODY, CHROME PLATED, BRASS BALL, TEFLON SEATS AND STUFFING BOX RING, WITH LEVER HANDLE AND BALANCING STOPS, SOLDER OR THREADED ENDS WITH UNION, AND SHALL BE MODEL MODEL #S-587-70 OR T-587-70 AS MANUFACTURED BY NIBCO.

SEE SECTION III - TESTING FOR ADDITIONAL TESTING REQUIREMENTS.

2.18 - SERVICE CONNECTIONS AND METERS

A. SERVICE CONNECTIONS - SERVICE CONNECTIONS SHALL BE 1 INCH FOR RESIDENTIAL SERVICES UP TO THE ROAD RIGHT-OF-WAY (SEE FIGURE 2.18.1) AND FROM THE RIGHT-OF-WAY TO THE METER SETTING. LOCATIONS OF SERVICE CONNECTIONS, WHEN SHOWN ON THE DRAWINGS, ARE APPROXIMATE ONLY. FINAL LOCATIONS WILL BE ESTABLISHED AT THE TIME OF CONSTRUCTION BY THE CITY OR A REPRESENTATIVE OF THE OWNER OF THE PROPERTY BEING SERVED. SERVICE CONNECTIONS SHALL BE INSTALLED PRIOR TO THE NEW MAINS BEING TESTED AND DISINFECTED AND PLACED IN SERVICE. FOR SERVICE CONNECTIONS GREATER THAN 2-INCH DIAMETER, SEE FIGURE 2.18.2.

SEE FIGURE 2.18.1 & FIGURE 2.18.2.

SERVICE CONNECTIONS SHALL INCLUDE THE FURNISHING AND INSTALLATION OF TAPPING SADDLE, CORPORATION STOP, CURB STOP AND BOX, AND SERVICE PIPE AND FITTINGS AS REQUIRED. MATERIALS SHALL MEET ALL APPLICABLE REQUIREMENTS OF AWWA C800. WORK SHALL BE IN ACCORDANCE WITH ALL APPLICABLE REQUIREMENTS PREVIOUSLY SPECIFIED IN THIS ITEM. TAPPING SADDLES SHALL BE USED ON SERVICES GREATER THAN 1-INCH AND SHALL BE OF BRONZE OR BRASS, WITH SILICON BRONZE SCREWS, SHALL BE DESIGNED FOR USE WITH THE TYPE OF PIPE ON WHICH THEY ARE INSTALLED, AND SHALL ACCEPT THE SUBSEQUENTLY SPECIFIED CORPORATION STOPS. MINIMUM QUALITY SHALL BE EPOXY COATED SADDLE WITH DOUBLE STAINLESS STEEL STRAPS AND BOLTS. TAPPING SADDLES SHALL INCORPORATE AN "O" RING SEAL OR GASKET WHICH SHALL EFFECT A POSITIVE HYDRAULIC SEAL. INSTALLATION SHALL BE IN STRICT ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.

CORPORATION STOPS SHALL BE OF THE BEST QUALITY BRONZE OR BRASS, BALL VALVE, AND SHALL BE A TEFLON COATED BALL VALVE AND SHALL BE COMPLETE WITH REQUIRED COUPLING AND ACCESSORIES FOR CONNECTION TO TYPE OF SERVICE PIPE PROVIDED. CORPORATION STOPS SHALL BE SUBJECTED TO AN AIR TEST AT THE FACTORY, AND SHALL BE AS MANUFACTURED BY AY MCDONALD, MODEL NO. 4701-B; MUELLER, MODEL NO. B2500; FORD METER BOX CO., MODEL FB800-X-NL, OR AS APPROVED.

CURB STOPS SHALL BE OF THE BEST QUALITY BRASS OR BRONZE, AND SHALL BE A TEFLON COATED BALL VALVE COMPLETE WITH CONNECTIONS FOR THE TYPE OF SERVICE PIPE PROVIDED FROM THE MAIN AND FOR THE TYPE OF SERVICE PIPE REQUIRED TO THE BUILDING BEING SERVED. CURB BOXES SHALL BE OF STEEL AND CAST IRON AND SHALL BE BIBBY ST. CROIX MODEL #4E ARCH BASE, OR AS APPROVED. CONCRETE BLOCKING SHALL BE PROVIDED UNDER EACH CURB BOX.

SERVICE PIPE SHALL BE OF TYPE K COPPER TUBE MEETING THE REQUIREMENTS OF ASTM B88, AND SHALL BE SOFT TEMPERED WHEN INSTALLED IN OPEN TRENCHES AND HARD TEMPERED WHEN INSTALLED BY PUSHING. FLARE TYPE UNIONS SHALL BE USED WITH THE COPPER TUBE. EACH SERVICE CONNECTION TWO INCH DIAMETER AND SMALLER SHALL BE PROVIDED WITH A TAIL PIECE OF COPPER AS SHOWN IN FIGURE 2.18.1.

PIPE SHALL BE INSTALLED UNDER STREET AND HIGHWAY PAVEMENTS BY PUSHING OR BORING, WITH NO EXCAVATION CLOSER THAN 5 FEET TO THE EDGE OF THE PAVEMENT. IN ADDITION, NO JOINTS SHALL BE PERMITTED WITHIN THESE LIMITS. WHEN BORING UNDER PAVEMENT, IF THE OPENING EXCEEDS BY 2 INCHES THE OUTSIDE DIAMETER OF THE PIPE INSTALLED, THE OPENING AROUND THE PIPE SHALL BE FILLED WITH GROUT.

B. WATER METERS - WATER METERS SHALL BE MAGNETIC DRIVE, WITH A SCANCODE REMOTE READ, I.E. RESIDENTIAL, COMMERCIAL AND INDUSTRIAL. THEY SHALL READ IN CUBIC FEET, SET WITH VALVES BEFORE AND AFTER THE METER. WATER METER SETTING SHALL BE APPROVED BY THE CITY. ALL ¾" AND 1" DIAMETER WATER METER INSTALLATIONS REQUIRE COPPER HORNS OBTAINED FROM THE CITY. INSTALLATION OF WATER METERS, SETTINGS AND REMOTE METER WIRE IS THE RESPONSIBILITY OF THE CONTRACTOR.

WATER METERS GREATER THAN 1" DIAMETER SHALL BE RIGID PLUMBED. THESE METERS SHALL HAVE BY-PASS PIPING WITH A LOCKABLE VALVE INSTALLED ON THE BY-PASS. ONLY TEFLON TAPE SHALL BE USED ON FITTINGS AND THREADS LOCATED ON THE SUPPLY SIDE OF WATER METERS.

WATER METERS 2" DIAMETER AND SMALLER SHALL BE OBTAINED FROM THE CITY. WATER METERS GREATER THAN 2" DIAMETER SHALL BE COMPOUND METERS WITH STRAINER, UNLESS OTHERWISE APPROVED BY THE CITY. WATER METERS SHALL BE HORIZONTALLY MOUNTED APPROXIMATELY 30-42" ABOVE THE FLOOR AND MUST BE ACCESSIBLE AND PROTECTED FROM DAMAGE, ESPECIALLY FREEZING.

THE OWNER/CONTRACTOR SHALL INSTALL A REMOTE WATER METER WIRE FROM THE PROPOSED WATER METER LOCATION TO THE VICINITY OF THE PROPOSED ELECTRIC METER BASE LOCATION. THE REMOTE METER WIRE SHALL TERMINATE OUTSIDE THE STRUCTURE IN THE VICINITY OF THE PROPOSED ELECTRIC METER LOCATION AND ALLOW AT LEAST A TWO FEET PITGAL AT EACH END. THE REMOTE SHALL BE SET IN THE IMMEDIATE VICINITY OF WHERE THE REMOTE WIRE EXITS THE STRUCTURE. THE REMOTE METER WIRE SHALL BE SINGLE STRANDED, THERMO-COATED, 18 GAUGE WIRE WITH THREE CONDUCTORS. THE OWNER/CONTRACTOR SHALL CONTACT THE HUDSON PUBLIC POWER OR THE ELECTRIC UTILITY IN THAT AREA TO DETERMINE THE EXACT LOCATION OF THE ELECTRIC METER BASE LOCATION. THIS REQUIREMENT SHALL APPLY TO ALL RESIDENTIAL, COMMERCIAL AND INDUSTRIAL CONNECTIONS.

PER THE OHIO BASIC BUILDING CODE, WHERE THE WATER PRESSURE WITHIN ANY BUILDING EXCEEDS 80 PSI, A WATER PRESSURE REDUCING VALVE OR REGULATOR SHALL BE INSTALLED IMMEDIATELY AFTER THE WATER METER TO REDUCE THE PRESSURE TO A MAXIMUM OF 80 PSI WITHIN THE BUILDING.

2.19 - BEDDING AND BACKFILL

A. BEDDING - PIPE EMBEDMENT SHALL BE SAND MEETING THE REQUIREMENTS OF ODOT ITEM 703.06, FROM 4-INCHES BELOW THE PIPE BARREL TO 12-INCHES ABOVE THE PIPE BARREL.

CONCRETE ENCASEMENT SHALL BE ODOT CLASS QC CONCRETE.

B. GRANULAR BACKFILL - THE GRANULAR BACKFILL SHALL MEET THE REQUIREMENTS OF ODOT ITEM 304 CRUSHED LIMESTONE OR CONTROLLED DENSITY BACKFILL IN ACCORDANCE WITH FIG. 2.25.1.

TRENCHES WITHIN RAILROAD RIGHT-OF-WAY, EXCEPT FOR LONGITUDINAL OCCUPANCY, SHALL BE BACKFILLED WITH CRUSHED STONE WITH A TOP SIZE OF THE AGGREGATE TO BE A MAXIMUM OF TWO INCHES AND TO HAVE NO MORE THAN 5% PASSING THE NUMBER OF 200 SIEVE. THE GRADATION OF THE MATERIAL IS TO BE SUCH THAT A DENSE STABLE MASS IS PRODUCED.

C. CONTROL DENSITY FILL (CDF) - CONTROL DENSITY FILL (CDF) SHALL BE ODOT ITEM 613, TYPE 1 LOW STRENGTH MORTAR, EXCEPT NO FLY ASH PERMITTED. THE DESIGN MIX USED SHALL BE APPROVED BY THE CITY, AND SHALL HAVE A MAXIMUM DESIGN STRENGTH OF 50 PSI.

II. - INSTALLATION

2.20 - PIPE LAYING AND HYDRANT INSTALLATION

PIPE SECTIONS SHALL BE STRUNG ALONG THE ROUTE OF THE MAINS WITHIN THE RIGHT-OF-WAY OR EASEMENT SO AS TO INTERFERE LEAST WITH PEDESTRIAN AND VEHICULAR TRAFFIC AND TO PROTECT THE PIPE AS FULLY AS POSSIBLE. CARE SHALL BE TAKEN AT ALL TIMES IN HANDLING THE PIPE SO AS NOT TO DAMAGE IT IN ANY WAY AND AT NO TIME SHALL OTHER PIPES OR MATERIAL BE PLACED IN THE PIPES.

THE USE OF EQUIPMENT WITH METAL TRACKS OR TREADS WILL NOT BE PERMITTED ON PAVED SURFACES WHICH WILL NOT BE REMOVED DURING TRENCHING OPERATIONS WITHOUT SOME TYPE OF PAVEMENT PROTECTION SUCH AS MATTING OR RUBBER TRACKS. HEAVY EQUIPMENT SHALL NOT BE DRIVEN OVER STREETS, BUT SHALL BE MOVED BY TRAILER.

THE MAINS SHALL BE LAID IN THE LOCATIONS AND AT THE GRADES SHOWN ON THE DRAWINGS, EXCEPT AS SPECIFICALLY PERMITTED BY THE CITY IN ORDER TO AVOID EXISTING OR PROPOSED UTILITY LINES OR ANY OTHER OBSTRUCTIONS ENCOUNTERED IN THE PROGRESS OF THE WORK; TO SECURE A MORE READILY ACCESSIBLE POSITION FOR TRENCHING; OR TO FACILITATE THE LOCATION OF VARIOUS APPURTENANCES OF THE MAIN. DEFLECTION OF PIPE JOINTS SHALL BE IN STRICT ACCORDANCE WITH THE PIPE MANUFACTURER'S INSTRUCTIONS.

WHEN ABRUPT CHANGES IN THE GRADE OF THE MAIN ARE NECESSARY TO AVOID EXISTING UTILITIES OR OTHER OBSTRUCTIONS, SUITABLE FITTINGS, USUALLY 1/8 BENDS, SHALL BE USED SO AS TO SECURE AN EASY FLOW OF LIQUID AND TO PROVIDE SUFFICIENT COVER BELOW SAME UNLESS OTHERWISE SPECIFIED OR NOTED ON THE DRAWINGS. PIPE SHALL BE SO LOCATED TO MAINTAIN A MINIMUM CLEARANCE OF 18 INCHES IN ALL DIRECTIONS WITH RESPECT TO OTHER UTILITIES TO ALLOW FOR TAPS TO BE INSERTED. CARE SHALL BE TAKEN TO AVOID HIGH AND LOW POINTS IN THE MAINS. DEAD-END STUB MAY BE TERMINATED WITH A RESTRAINED VALVE (FOR FURTHER USE) AS DETERMINED BY THE CITY.

PIPE SHALL BE LAID AT A MINIMUM 10-FOOT HORIZONTAL DISTANCE FROM SEWERS AND MANHOLES AND AT A MINIMUM 18 INCHES VERTICAL DISTANCE FROM SEWERS AT THEIR CROSSING, BOTH AS MEASURED BETWEEN THE OUTSIDE OF THE PIPE WALLS. AT CROSSINGS, ONE FULL LENGTH OF WATER MAIN PIPE SHALL BE INSTALLED CENTERED ON THE PIPE BEING CROSSED SO BOTH JOINTS WILL BE AS FAR FROM THE SEWER AS POSSIBLE.

WITH PUSH-ON JOINTS, THE SURFACES TO BE IN CONTACT WITH THE RUBBER GASKET SHALL BE WIPED CLEAN AND DRY JUST PRIOR TO MAKING THE JOINT AND, WHEN MAKING THE JOINT, A LUBRICANT SHALL BE USED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS. WITH MECHANICAL JOINTS, THE SURFACES TO BE IN CONTACT WITH THE RUBBER GASKET SHALL BE BRUSHED WITH SOAPY WATER TO REMOVE ALL SAND AND GRIT JUST PRIOR TO MAKING THE JOINT.

THE CONTRACTOR IS RESPONSIBLE FOR DISINFECTION OF THE WATER MAIN IN ACCORDANCE WITH AWWA C651-92, AS SUBSEQUENTLY SPECIFIED IN ITEM 2.28. THE CONTRACTOR SHALL FOLLOW AWWA C651-14 - PREVENTIVE AND CORRECTIVE MEASURES DURING CONSTRUCTION. ALL PIPES SHALL BE THOROUGHLY CLEANED INSIDE AND OUTSIDE BEFORE BEING LOWERED INTO THE TRENCH; SHALL BE KEPT CLEAN DURING AND AFTER LAYING; AND THE END OF THE PIPE SHALL BE SEALED WITH A WATERTIGHT PLUG WHEN PIPE LAYING IS STOPPED FOR ANY REASON. IF, IN THE OPINION OF THE ENGINEER, THE PIPE CONTAINS DIRT THAT WILL NOT BE REMOVED DURING SUBSEQUENT FLUSHING OPERATIONS, THE INTERIOR OF THE PIPE SHALL BE CLEANED AND SWABBED, AS NECESSARY, WITH A 1% CHLORINE SOLUTION (10,000 MG/L) PREPARED BY MIXING ONE POUND OF HIGH-TEST CALCIUM HYPOCHLORITE (65-70% CL) AND 8 GALLONS OF WATER.

HYDRANTS SHALL BE SET PLUMB AND TO THE GRADE OF THE CURB, STREET, ALLEY, HIGHWAY OR RIGHT-OF-WAY AS APPROVED BY THE CITY. THE BREAKAWAY FLANGE SHALL BE WITHIN THREE INCHES OF FINISHED GRADE, EITHER EXISTING FOR DEVELOPED STREETS OR PROPOSED GRADE FOR PROPOSED STREETS. ANY READJUSTMENT OF THE GRADE WILL REQUIRE READJUSTMENT OF THE FIRE HYDRANT AS NOTED ABOVE. PUMPER NOZZLE SHALL ALWAYS BE SET TOWARD THE MIDDLE LINE OF THE STREET, HIGHWAY OR RIGHT-OF-WAY PRIOR TO FINAL ACCEPTANCE OF THE PROJECT. PRIOR TO THE WATER MAIN BEING PLACED INTO SERVICE, THE CONTRACTOR SHALL EITHER TURN PUMPER NOZZLE AWAY FROM THE MIDDLE LINE OF THE STREET OR PROVIDE PLASTIC BAGS, AS APPROVED BY THE CITY, TO COVER EACH HYDRANT.

THE HYDRANT BASE AND WATCH VALVE SHALL EACH REST ON APPROVED CONCRETE BLOCKING. EXCAVATION FOR HYDRANTS SHALL FIRST BE BACKFILLED WITH ODOT #57 WASHED GRAVEL (NO LIMESTONE) FOR A MINIMUM DEPTH OF TWO FEET. REMAINDER OF EXCAVATION SHALL BE BACKFILLED AS SPECIFIED FOR TRENCHES.

SHOULD IT BE NECESSARY, AS DETERMINED BY THE CITY TO SET A FIRE HYDRANT AT A GREATER DEPTH OF BURY AS A RESULT OF CHANGING HYDRANT LOCATION FROM THAT SHOWN, ELEVATION ADJUSTMENT SHALL BE ACCOMPLISHED BY FURNISHING AND INSTALLING THE FIRE HYDRANT MANUFACTURER'S STANDARD BARREL AND STEM EXTENSIONS OR GRADE ADJUSTMENT OFFSET.




FIG 2.16.1




FIG 2.18.1




FIG 2.18.2



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: AS SHOWN

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET

Drawing Title:

WATER DETAILS

C8.2



C:\DCC\ACDboat\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\ CESO\CC-CIVIL\PLAN\LOT\Major Site Plans\765295\_ CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel

CITY OF HUDSON SECTION 2. WATER DISTRIBUTION REQUIREMENTS -CONTINUED

**2.21 - TRENCHES** EXCEPT WHERE OTHERWISE SPECIFICALLY REQUIRED OR PERMITTED BY THE CITY, THE MAINS SHALL BE LAID IN OPEN TRENCH EXCAVATED TO A DEPTH SUFFICIENT TO PROVIDE NOT LESS THAN 4 FEET OF VERTICAL COVER OVER THE TOP OF THE PIPE BARREL AND TO PROVIDE NOT LESS THAN 4 INCHES OF BEDDING BELOW THE OUTSIDE BOTTOM OF THE PIPE BARREL TO 12 INCHES ABOVE THE PIPE BARREL. NO BLOCKING SHALL BE PERMITTED UNDER THE WATER MAIN. HOWEVER, PIPES SHALL BE INSTALLED AT A GREATER DEPTH WHEN SHOWN ON THE DRAWINGS; WHEN NECESSARY TO PASS UNDER OTHER UTILITIES OR OBSTRUCTIONS; OR WHERE NECESSARY TO PREVENT HIGH POINTS IN THE MAIN. IN ADDITION TO THE MINIMUM VERTICAL COVER, WHERE ANY PIPES PARALLEL, ROADSIDE DITCHES OR STREAMS, A LATERAL COVER SHALL BE PROVIDED AT LEAST EQUAL TO THE SPECIFIED VERTICAL COVER.

PRIOR TO TRENCHING, IN LAWN AREAS AND IN FIELDS USED FOR FARMING, BOTH AS DETERMINED BY THE CITY, ALL TOPSOIL SHALL BE REMOVED AND STOCKPILED FOR REPLACEMENT DURING BACKFILLING.

THE WIDTH OF THE TRENCH SHALL NOT BE MORE THAN 24 INCHES GREATER THAN THE OUTSIDE DIAMETER OF THE PIPE, EXCEPT AT JOINTS, WHERE SUFFICIENT SPACE SHALL BE PROVIDED FOR PROPERLY MAKING THE JOINTS WITHOUT RAISING THE LENGTH OF PIPE ABOVE THE SOLID BOTTOM OF THE TRENCH. CARE SHALL BE TAKEN TO DETECT AND REMOVE STONES AND DEBRIS IN THE BOTTOM OF THE TRENCH WHICH WOULD DAMAGE THE PIPE OR BE DETRIMENTAL TO THE PROPER BEDDING OF THE PIPE, WITH REMOVAL TO BE FOR A DEPTH OF AT LEAST 6 INCHES BELOW THE BOTTOM OF THE PIPE AND REPLACED WITH BEDDING MATERIAL.

TRENCHES IN ROCK SHALL BE EXCAVATED TO A DEPTH OF 6 INCHES BELOW THE OUTSIDE BOTTOM OF THE PIPE BARREL AND BELL WHEN THE PIPE IS LAID ON ITS FINAL GRADE AND THE PIPE SHALL THEN BE LAID ON A CUSHIONING LAYER OF BEDDING MATERIAL AS SPECIFIED AND PROVIDED BY THE CONTRACTOR. ROCK EXCAVATION SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS SUBSEQUENTLY SPECIFIED IN ITEM 2.27.

PRIOR TO OPEN TRENCHES ENTERING THE PAVED LIMITS OF A STREET, ALLEY, DRIVEWAY, SIDEWALKS, OR PARKING AREA, THE PAVEMENT SHALL BE NEATLY CUT FOR ITS FULL DEPTH, REMOVED, AND DISPOSED OF OFF THE PROJECT SITE. STREET AND ROAD CROSSINGS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE REQUIREMENTS SPECIFIED IN SECTION 7 - ROADWAY.

TRENCH EXCAVATION SHALL INCLUDE THE REMOVAL OF SUCH OTHER EXISTING FACILITIES NOTED TO BE REMOVED.

TRENCHES SHALL BE KEPT FREE OF WATER DURING PIPE LAYING AND JOINTING. WHEN WATER EXISTS IN THE TRENCHES AT THE TIME OF PIPE LAYING, THE CONTRACTOR SHALL DEWATER THE TRENCH AT HIS EXPENSE.

**2.22 - PROTECTION OF EXISTING UTILITIES**

EXISTING UNDERGROUND UTILITIES ALONG THE ROUTE OF CONSTRUCTION, AS SHOWN ON THE DRAWINGS OR MARKED AT THE TIME OF CONSTRUCTION BY THE UTILITY OWNER, SHALL BE UNCOVERED BY THE CONTRACTOR AND THEIR ELEVATIONS DETERMINED AT LEAST 200 FEET IN ADVANCE OF PIPE INSTALLATION. CONTRACTORS SHALL CONTACT OUPS 48 HOURS PRIOR TO ANY EXCAVATION WORK.

ALL UNDERGROUND UTILITIES, WHEN ENCOUNTERED, SHALL BE ADEQUATELY SUPPORTED, SHORED UP OR OTHERWISE PROTECTED WHENEVER EXPOSED IN THE EXCAVATION. TIMBER SUPPORTS SHALL BE A MINIMUM OF 6 INCHES SQUARE. SUPPORTS SHALL EXTEND INTO UNDISTURBED EARTH A MINIMUM OF 12 INCHES EACH SIDE OF THE TRENCH AND THE PIPE, CONDUIT, ETC., Banded OR TIED TO THE BRIDGING FOR ITS FULL LENGTH. WHERE BRIDGING CANNOT BE SUPPORTED BY A FIRM FOUNDATION, THE CONTRACTOR SHALL PROVIDE VERTICAL SUPPORT FOR THE BRIDGING, INCLUDING ANY LATERAL BRACING NECESSARY TO PROVIDE A FIRM AND SUBSTANTIAL SUPPORT. SUPPORTS AND BRACING SHALL BE OF NATIVE HARDWOOD AND SHALL BE FURNISHED AND INSTALLED BY THE CONTRACTOR. (SEE FIGURE 2.22.1)

ABOVE GROUND (AERIAL) UTILITIES, INCLUDING POWER, TELEPHONE AND CABLE TELEVISION, SHALL REMAIN IN SERVICE AT ALL TIMES. ANY ANTICIPATED DISRUPTION OF SERVICE SHALL BE WITH THE FULL KNOWLEDGE OF THE UTILITY COMPANY AND REQUIRED ADVANCE NOTICE TO THE AFFECTED USERS BY THE CONTRACTOR. REMOVAL OF GUY WIRES AND HOLDING OF POLES SHALL BE DONE AS REQUIRED TO COMPLETE THE WORK, SHALL BE AS AGREED UPON BY THE UTILITY COMPANY AND THE CONTRACTOR WITH NO ADDITIONAL COST TO THE CITY.

ARBITRARY DISRUPTION OF UNDERGROUND AND AERIAL UTILITY SERVICES WILL NOT BE PERMITTED.

**2.23 - TRENCH PROTECTION**

WHERE NECESSARY TO PREVENT CAVING OF THE TRENCH AND OTHER EXCAVATION, AND FOR PROTECTION OF WORKMEN AND NEARBY STRUCTURES, TRENCH PROTECTION SHALL BE PROVIDED PER OSHA STANDARDS BY AND AT THE EXPENSE OF THE CONTRACTOR.

**2.24 - PIPE EMBEDMENT**

AFTER THE PIPE HAS BEEN LAID AND THE JOINTS MADE, THE FULL LENGTH OF EACH PIPE SHALL BE THOROUGHLY BEDDED. THE MATERIAL SHALL BE PLACED IN LAYERS NOT EXCEEDING 6 INCHES IN THICKNESS, LOOSE MEASUREMENT, AND SECURELY COMPACTED BY HAND OR MECHANICAL TAMPING TO NOT LESS THAN 98% OF MAXIMUM DENSITY AS DETERMINED IN ACCORDANCE WITH ASTM D1557 (MODIFIED PROCTOR) WHILE TAKING CARE NOT TO DISPLACE OR DAMAGE THE PIPE OR JOINTS.

AN EXCEPTION SHALL BE MADE WHERE CONCRETE ENCASEMENT IS NOTED ON THE DRAWINGS. CONCRETE ENCASEMENT SHALL BE SQUARE IN CROSS SECTION, SHALL HAVE A MINIMUM THICKNESS OF 6 INCHES AT PIPE BELLS, AND SHALL BE OF THE LENGTH NOTED. (SEE FIGURE 2.24.1)

**2.25 - BACKFILLING**

BACKFILL SHALL INCLUDE THE MATERIAL PLACED ABOVE THE PIPE EMBEDMENT MATERIAL PREVIOUSLY SPECIFIED. NO HEAVY OR LARGE QUANTITIES OF BACKFILL MATERIAL SHALL BE PLACED OVER THE PIPE UNTIL BACKFILLING HAS PROGRESSED TO A DEPTH OF AT LEAST 3 FEET OVER THE TOP OF THE PIPE BARREL. ALL BACKFILL MATERIAL SHALL BE CAREFULLY PLACED SO AS NOT TO DAMAGE THE JOINTS OR DISPLACE THE PIPE. BACKFILLING SHALL IMMEDIATELY FOLLOW TRENCHING AND PIPE LAYING OPERATIONS TO REDUCE THE POSSIBILITY OF DAMAGE TO PAVEMENTS AND UTILITIES.

TRENCHES WITHIN EXISTING AND PROPOSED STONED STREETS, ALLEYS, DRIVEWAYS, STONED PARKING AREAS AND CONCRETE OR BRICK SIDEWALKS SHALL BE BACKFILLED WITH GRANULAR MATERIAL. THE MATERIAL SHALL BE PLACED AND COMPACTED TO NOT LESS THAN 100% OF MAXIMUM DENSITY AS DETERMINED IN ACCORDANCE WITH ASTM D1557 (MODIFIED PROCTOR).

CONTRACTOR SHALL PROVIDE CERTIFIED PROCTOR TEST FROM LIMESTONE SUPPLIER WITH THE SHOP DRAWINGS, PRIOR TO STONE BEING DELIVERED TO THE PROJECT SITE.

WHERE MAINS ARE INSTALLED ALONG EXISTING AND PROPOSED PAVED OR STONED STREETS, ALLEYS, DRIVEWAYS AND PARKING AREAS, THE SPECIFIED COMPACTED GRANULAR MATERIAL SHALL ALSO BE PROVIDED FOR BACKFILLING ANY PORTION OF THE TRENCHES FALLING WITHIN THAT AREA BELOW A LINE DRAWN AT 45 DEGREES TO THE HORIZONTAL FROM THE SURFACE AT THE EDGE OF THE PAVEMENT OR BACK OF CURB AND ABOVE THE HORIZONTAL PLANE OF THE PIPE EMBEDMENT MATERIAL. (SEE FIGURE 2.25.1)

FOR TRENCHES WITHIN EXISTING OR PROPOSED PAVED STREETS, ALLEYS, DRIVEWAYS AND PAVED PARKING AREAS A CONTROLLED DENSITY FILL (CDF) SHALL BE PROVIDED OR BACKFILL AS APPROVED BY THE CITY. THE MIX SHALL BE PLACED IN A USABLE FLUID FORM AND IN UNIFORM VERTICAL LIFTS. DESIGN, FINISHING AND PROTECTION OF THE MATERIAL SHALL BE RECOMMENDED BY THE MANUFACTURER FOR THE APPLICATION. QUALITY CONTROL TEST PROCEDURES OF THE MANUFACTURER SHALL INCLUDE ASTM C138 - TEST FOR UNIT WEIGHT, AND ASTM C39 - TEST FOR COMPRESSIVE STRENGTH. NO COMPACTION IS REQUIRED FOR C.D.F.

TRENCHES WHERE WATER MAINS ARE INSTALLED LONGITUDINAL TO THE RAILROAD TRACKS SHALL BE BACKFILLED PER RAILROAD REQUIREMENTS, LATEST REVISIONS. THE BACKFILL MATERIAL SHALL BE PLACED IN LOOSE SIX INCH LIFTS AND COMPACTED TO AT LEAST 95% OF ITS MAXIMUM DENSITY WITH A MOISTURE CONTENT THAT IS NOT MORE THAN 1% GREATER THAN OR 2% LESS THAN THE OPTIMUM MOISTURE AS DETERMINED IN ACCORDANCE WITH CURRENT ASTM DESIGNATION D - 1557 (MODIFIED PROCTOR). WHEN THE BACKFILL MATERIAL IS WITHIN THREE FEET OF THE SUBGRADE ELEVATION (THE INTERFACE OF THE BALLAST AND THE SUBSOIL), A COMPACTION OF AT LEAST 98% WILL BE REQUIRED. COMPACTION TEST RESULTS CONFIRMING COMPLIANCE MUST BE PROVIDED TO RAILROAD COMPANY'S ENGINEER BY THE CONTRACTOR.

THE CITY MAY REQUIRE CONTRACTOR TO CHECK COMPACTION OF THE BACKFILL AT NO COST TO CITY AT ANY TIME.

WHERE TRENCHES ARE BACKFILLED WITH GRANULAR MATERIAL, THE CONTRACTOR SHALL REMOVE EXCESS EXCAVATED MATERIAL. ANY EXCESS EXCAVATED SPOIL SHALL BE REMOVED TO AN APPROVED DUMP SITE.

IN ALL PAVED STREETS AND HIGHWAYS, IMMEDIATELY UPON COMPLETION OF OTHER BACKFILLING OPERATIONS AND PRIOR TO THE END OF WORK FOR THAT DAY, A TEMPORARY PAVEMENT AS SPECIFIED IN SECTION 7 - ROADWAY SHALL BE PROVIDED AND SHALL REMAIN IN PLACE AND BE PROPERLY MAINTAINED UNTIL SUCH TIME AS THE PERMANENT PAVEMENTS ARE PLACED. PERMANENT PAVEMENTS SHALL BE PLACED WITHIN TWO WEEKS AFTER COMPLETION OF TESTS AND ACCEPTANCE OF EACH SECTION OF THE WATER MAIN.

FOR BACKFILLING THE REMAINDER OF THE TRENCHES, AS MUCH OF THE EXCAVATED MATERIAL AS POSSIBLE SHALL BE REPLACED UNTIL BACKFILLING HAS PROGRESSED TO A DEPTH OF AT LEAST 3 FEET OVER THE TOP OF THE PIPE BARREL. THE MATERIAL SHALL BE FINELY DIVIDED FREE OF STONES 3 INCHES OR GREATER IN ANY DIMENSION, BOULDERS, ORGANIC MATERIAL OR OTHER HARMFUL DEBRIS, AND SHALL BE PLACED IN 6 INCH LAYERS, LOOSE MEASUREMENT, AND COMPACTED BY MECHANICAL TAMPING.

ALSO, IMMEDIATELY UPON COMPLETION OF OTHER BACKFILLING OPERATIONS AND PRIOR TO THE END OF WORK FOR THAT DAY, A TEMPORARY SIDEWALK SHALL BE PROVIDED, AND SHALL REMAIN IN PLACE AND BE PROPERLY MAINTAINED UNTIL SUCH TIME AS THE PERMANENT SIDEWALK IS PLACED. THE TEMPORARY SIDEWALK SHALL CONSIST OF A MINIMUM OF 1-1/2 INCHES OF THE SPECIFIED COMPACTED GRANULAR BACKFILL MATERIAL PLACED TO THE SAME WIDTH AS THE ORIGINAL SIDEWALK, AND SHALL BE FURNISHED, PLACED AND MAINTAINED BY AND AT THE EXPENSE OF THE CONTRACTOR. THE TEMPORARY SIDEWALK SHALL BE RESHAPED AND REGRADED PRIOR TO THE INSTALLATION OF PERMANENT SIDEWALK.

AFTER BACKFILLING, ALONG WEED OR UNSODDED AREAS THE MATERIAL SHALL BE GRADED TO CONFORM TO THE ORIGINAL GROUND PROFILE. IN LAWN AREAS AND IN FIELDS USED FOR FARMING, ALL TOPSOIL REMOVED AND STOCKPILED PRIOR TO TRENCHING SHALL BE REPLACED AND GRADED TO CONFORM TO THE ORIGINAL GROUND PROFILE. IN LAWNS AND OTHER AREAS WHERE GRASS EXISTS, AS DETERMINED BY THE OWNER OR THE CITY, THE AREA SHALL BE GRADED AND MADE READY FOR SEEDING AS SPECIFIED IN SECTION 1. IN LAWN AREAS, IF THE EXISTING REPLACED TOPSOIL DOES NOT PROVIDE THE REQUIRED 4-INCH MINIMUM DEPTH AS SPECIFIED IN SECTION 1, THE CONTRACTOR SHALL PROVIDE ADDITIONAL TOPSOIL AT HIS EXPENSE.

THE CONTRACTOR SHALL BE REQUIRED TO REGRADE AND RESHAPE ALL ROAD SHOULDERS AND ALL DITCHES OR SWALES FROM EXISTING HIGH POINTS TO EXISTING DRAINAGE STRUCTURES OR OTHER OUTLETS ALONG THE PROPOSED IMPROVEMENT. THE CONTRACTOR AND THE CITY SHALL MUTUALLY AGREE AND ESTABLISH ALL DITCH GRADES TO BE RESTORED PRIOR TO CONSTRUCTION. DITCHES, WHICH ARE RESHAPED, SHALL HAVE REASONABLE SIDE SLOPES. VERTICAL OR STEEP SLOPES WILL NOT BE PERMITTED.

**2.26 - CONNECTIONS TO MAINS**

NEW MAINS SHALL BE CONNECTED TO EXISTING MAINS USING PROPER FITTINGS. CONNECTIONS SHALL BE MADE IN A MANNER ACCEPTABLE TO THE CITY. ALL CONNECTIONS TO AC PIPE SHALL BE VIA PAD ADAPTORS. AC PIPE SHALL NOT BE CUT WITH A SAW. ALL CUTS SHALL BE ACCOMPLISHED BY SNAP CUT. NO CUT-INS OR CONNECTIONS TO EXISTING MAINS SHALL BE MADE UNLESS AT LEAST 48 HOURS NOTICE OF SUCH CUT-INS OR CONNECTIONS IS GIVEN TO THE CITY. ALL SUCH WORK SHALL BE PLANNED SO AS TO REDUCE THE NUMBER OF SHUT-OFFS.

TWO DAYS PRIOR TO SHUTTING VALVES ON EXISTING LINES, THE CONTRACTOR SHALL NOTIFY IN WRITING ALL AFFECTED PROPERTY OWNERS AND THE CITY OF SUCH SHUT OFF. THE SHUT OFF TIME SHALL BE KEPT TO A MINIMUM AND SHALL BE MADE AT OFF-PEAK HOURS OR ON WEEKENDS.

THE OPERATION OF ALL EXISTING VALVES SHALL BE ACCOMPLISHED BY A REPRESENTATIVE OF THE WATER RESOURCES DEPARTMENT. THE CONTRACTOR SHALL NOT OPERATE EXISTING VALVES.

THE CITY ASSUMES NO RESPONSIBILITY FOR ANY DELAY OCCASIONED BY SPECIAL REQUIREMENTS OR CONDITIONS WHICH MUST BE MET IN MAKING CONNECTIONS.

EXTREME CARE SHALL BE TAKEN IN MAKING SUCH CONNECTIONS TO PREVENT CONTAMINATION OF THE EXISTING MAINS. BEFORE MAKING CUT-INS OR CONNECTIONS TO EXISTING MAINS, ALL FITTINGS, VALVES AND PIPE SHALL BE WASHED WITH CLEAN WATER AND THEN DISINFECTED BY WASHING WITH A CHLORINE SOLUTION HAVING A RESIDUAL CHLORINE STRENGTH OF NOT LESS THAN 50 PPM.

PLUGS REMOVED FROM EXISTING MAINS THAT ARE NOT DAMAGED MAY BE REUSED WITHIN THE PROJECT, AND THOSE REMAINING AFTER COMPLETION OF CONSTRUCTION SHALL REMAIN THE PROPERTY OF THE CITY.

**2.27 - ROCK EXCAVATION**

A. GENERAL - THE TERM "ROCK EXCAVATION" SHALL INCLUDE THE REMOVAL OF SUCH MATERIAL AS CANNOT BE BROKEN AND REMOVED BY ORDINARY EXCAVATING EQUIPMENT. THE DEFINITION OF ORDINARY EXCAVATING EQUIPMENT DOES NOT INCLUDE RIPPERS OR POWER OPERATED JACK HAMMERS. DISINTEGRATED, WEATHERED, ROTTEN AND LOOSE ROCK PARTICLES CAPABLE OF REMOVAL BY ORDINARY METHODS ARE NOT INCLUDED WITHIN THE SCOPE OF ROCK EXCAVATION.

B. EXCAVATION - EXCAVATION SHALL BE CARRIED TO A SUFFICIENT DEPTH TO PROVIDE FOR A CUSHIONING LAYER OF BEDDING MATERIAL AS PREVIOUSLY SPECIFIED IN ITEM 2.21. WIDTH OF TRENCH SHALL BE NOT MORE THAN PREVIOUSLY SPECIFIED FOR THE RESPECTIVE TYPE OF PIPE.

EXCAVATION FOR STRUCTURES SHALL EXTEND TO A PLANE 4 INCHES BELOW THE UNDERSIDE OF THE CONCRETE FOUNDATIONS AND BE CONFINED TO LIMITS TWO FEET BEYOND THE OUTSIDE OF SUCH FOUNDATIONS.

C. DISPOSAL OF ROCK - EXCEPT UNDER SPECIAL PERMISSION FROM THE ENGINEER, ROCK REMOVED BY EXCAVATION SHALL NOT BE USED FOR BACKFILL, BUT SHALL BE DISPOSED OF BY THE CONTRACTOR OFF THE PROJECT SITE. NECESSARY BEDDING AND BACKFILL FOR TRENCHES AND OTHER EXCAVATIONS IN ROCK EXCAVATION SHALL BE APPROVED BY THE CITY.

D. METHOD - WHERE ROCK IS ENCOUNTERED WHICH CANNOT BE REMOVED BY ORDINARY EXCAVATING METHODS, ROCK EXCAVATION, UNLESS OTHERWISE SPECIFIED, MAY BE ACCOMPLISHED BY THE USE OF EXPLOSIVES, SUBJECT TO COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL LAWS AND THE FOLLOWING REQUIREMENTS:

- 1) ALL REQUIRED PERMITS SHALL BE SECURED BY THE CONTRACTOR WELL IN ADVANCE OF SUCH OPERATIONS.
- 2) THE TRANSPORTING, HANDLING AND FIRING OF EXPLOSIVES SHALL BE PERFORMED BY SOMEONE THOROUGHLY FAMILIAR, EXPERIENCED AND, IF APPLICABLE, LICENSED IN THIS TYPE OF WORK, PREFERABLY A REPRESENTATIVE OF THE MANUFACTURER OF THE EXPLOSIVES TO BE USED.
- 3) PRIOR TO REMOVING ROCK IN ANY AREA, THE TYPE OF EXPLOSIVES TO BE USED, THE NUMBER, DEPTH AND LOADING OF HOLES TO BE DETONATED AT ANY ONE TIME, AND ANY SPECIAL PRECAUTIONS TO BE OBSERVED SHALL BE DETERMINED AT A CONFERENCE BETWEEN REPRESENTATIVES OF THE OWNER, THE CITY, THE CONTRACTOR, THE CONTRACTORS INSURANCE COMPANY AND THE PERSON DIRECTLY RESPONSIBLE FOR DETONATION. THE PROCEDURE THEREAFTER FOLLOWED IN THAT AREA SHALL CONFORM TO THE DECISIONS REACHED, SUBJECT TO ANY MODIFICATIONS WHICH MAY BE REQUIRED BECAUSE OF UNSATISFACTORY OR UNSAFE RESULTS OR THE PROCEDURE AGREED UPON.
- 4) SUITABLE TIMBER MATS OR OTHER COVERINGS SHALL BE PROVIDED TO CONFINE ALL MATERIALS LIFTED BY BLASTING WITHIN THE LIMITS OF THE EXCAVATION.
- 5) ALL PUBLIC AND PRIVATE UTILITY COMPANIES HAVING FACILITIES IN THE VICINITY SHALL BE NOTIFIED BY THE CONTRACTOR OF THE LOCATION AND TIME OF CONTEMPLATED DETONATION IN SUFFICIENT TIME TO ALLOW THEM TO PROTECT THEIR FACILITIES. LIKEWISE, WHERE OPERATIONS ARE TO BE CARRIED ON IN ANY LOCATION WHERE TRAFFIC ON STREETS OR HIGHWAYS MAY BE AFFECTED, PROPER NOTICE SHALL BE GIVEN THE LOCAL POLICE DEPARTMENT.
- 6) FOR PURPOSE OF PROTECTING THE GENERAL PUBLIC, THE CONTRACTOR AND THE OWNER, THE UTMOST COOPERATION WILL BE REQUIRED BETWEEN THE CONTRACTOR AND ALL OTHER INTERESTED PARTIES. ALL SAFETY PRECAUTIONS SHALL BE STRICTLY ENFORCED.
- 7) SHOULD PERMIT LIMITATIONS OR THE NEARNESS OF EXISTING STRUCTURES AND UTILITIES PROHIBIT THE USE OF EXPLOSIVES, ROCK EXCAVATION SHALL BE PERFORMED BY AN APPROVED ALTERNATE METHOD.
- 8) SEISMOGRAPHIC MONITORING, PRE-BLASTING AND POST-BLASTING INSPECTIONS SHALL BE PERFORMED ON THOSE STRUCTURES NEARBY TO AVOID FRAUDULENT DAMAGE CLAIMS.
- E. DAMAGE TO EXISTING FACILITIES - THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DAMAGE TO EXISTING STRUCTURES, PIPING, SEWERS, DRAINS, CABLES, CONDUITS, EQUIPMENT AND APPURTENANCES RESULTING FROM HIS ROCK EXCAVATION OPERATIONS, AND SHALL REPAIR SAME TO THE SATISFACTION OF THE OWNER AND THE CITY.

**III. - TESTING**

**\*2.28 - DISINFECTION**

**\*2.29 - PRESSURE AND LEAKAGE TEST**

**\*2.30 - BACTERIOLOGICAL TESTS**

**\*2.31 - COMPLETION OF TESTS**

\*VERIFY APPLICABILITY WITH CITY PRIOR TO OBTAINING PERMITS AND STARTING CONSTRUCTION FOR SERVICE AND FIRE LINES ONSITE.






FIG. 2.25.1

GRANULAR OR CONTROLLED DENSITY FILL BACKFILL  
NOT TO SCALE



SECTION  
CONCRETE PIPE ENCASEMENT



GRANULAR EMBEDMENT

BEDDING DETAILS  
NO SCALE

CONCNCNS.DWG 09-15-99

FIG 2.24.1



www.cesoinc.com

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: AS SHOWN

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025

Issue: PERMIT SET

Drawing Title:  
WATER DETAILS

C8.3

C:\DC\ACD\atv\CESO\03-CIVIL\PLAN\LOT\Major Site Plans\765295\_CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel

CITY OF HUDSON SECTION 4. STORM COLLECTION

I. MATERIALS

A. PIPE AND FITTINGS

1. REQUIREMENTS - PIPE, FITTINGS, AND APPURTENANCES SHALL CONFORM TO THE LATEST EDITION OF THE REFERENCED STANDARDS.

2. MAIN LINE SEWERS, PIPES, CULVERTS, ETC. SHALL BE A MINIMUM SIZE OF 12-INCH DIAMETER. ALL SEWERS AND PIPES 15-INCH AND SMALLER SHALL BE PVC SDR35, PER ASTM D3034 OR POLYPROPYLENE MEETING ASTM F2764 UNLESS OTHERWISE DIRECTED BY THE CITY ENGINEER. ALL SEWERS AND PIPES GREATER THAN 15-INCH SHALL BE CONCRETE MEETING ASTM C76 CLASS IV UNLESS OTHERWISE DIRECTED BY THE CITY ENGINEER. POLYPROPYLENE PIPE MAY ONLY BE USED OUTSIDE THE PUBLIC ROADWAY'S PAVEMENT, AND ABOVE THE ROADWAY'S ANGLE OF REPOSE (ABOVE A 45-DEGREE LINE EXTENDING FROM THE EDGE OF PAVEMENT OR CURB DOWNWARDS).

3. ALL DRIVE CULVERTS WITH TWO (2) FOOT OR LESS COVER ABOVE THE TOP OF THE CULVERT SHALL BE EITHER CONCRETE PIPE, MEETING ASTM C76 CLASS IV, OR CONCRETE ENCASED PVC SDR 35 OR POLYPROPYLENE PIPE. THE CONCRETE ENCASEMENT SHALL BE CLASS M5, POURED THE ENTIRE LENGTH OF THE CULVERT, FROM THE SPRING LINE OF THE PIPE TO THE BOTTOM OF THE PROPOSED DRIVEWAY APPROACH. A VISQUEEN BARRIER SHALL BE PROVIDED BETWEEN THE CONCRETE ENCASEMENT AND BOTTOM OF THE APPROACH. ALL DRIVE CULVERTS WITH GREATER THAN TWO (2) FEET OF COVER SHALL BE OF PIPE MATERIAL AS SPECIFIED FOR SEWERS AND PIPES.

4. ALL DRIVE CULVERTS GREATER THAN 15-INCH SHALL HAVE INSTALLED, AS A MINIMUM, HALF-HEIGHT HEAD WALLS. FULL HEADWALLS MAY BE REQUIRED UPON REVIEW BY THE CITY. ALL DRIVE CULVERTS 15-INCH OR SMALLER ARE NOT REQUIRED TO HAVE HEADWALLS.

5. THE MANUFACTURER SHALL FURNISH AN AFFIDAVIT INDICATING THAT THE PIPE, FITTINGS AND APPURTENANCES HAVE BEEN MANUFACTURED AND TESTED IN ACCORDANCE WITH THE REQUIREMENTS OF THE APPLICABLE REFERENCED STANDARDS. A COPY OF THE AFFIDAVIT, INDICATING THE PROJECT ON WHICH THE MATERIAL IS TO BE USED, SHALL BE SUBMITTED AS A SHOP DRAWING TO THE CITY PRIOR TO CONSTRUCTION.

6. ALL PIPES, FITTINGS AND APPURTENANCES SHALL BE APPROPRIATELY MARKED FOR PURPOSES OF IDENTIFICATION. THE MATERIALS AND METHODS OF MANUFACTURE, AND THE COMPLETED PIPES, FITTINGS AND APPURTENANCES SHALL BE SUBJECT TO INSPECTION AND REJECTION AT ALL TIMES. THE CITY HAS THE RIGHT TO MAKE INSPECTIONS.

7. FOR NEW PUBLIC STORM SEWERS THAT TRANSITION FROM THE RIGHT-OF-WAY TO AN EASEMENT ON PRIVATE PROPERTY, THE STORM SEWER MATERIAL USED WITHIN THE RIGHT-OF-WAY WILL BE USED WITHIN THE DOWNSTREAM SECTION ON PRIVATE PROPERTY.

8. B. PVC PLASTIC PIPE AND FITTINGS - PVC PLASTIC PIPE AND FITTINGS SHALL HAVE A MINIMUM PIPE STIFFNESS OF 46 PSI AT 5% DEFLECTION WHEN TESTED IN ACCORDANCE WITH ASTM D2412, AND, AS APPLICABLE FOR THE SIZES INVOLVED, SHALL MEET THE REQUIREMENTS OF ASTM D3034, ASTM F679 OR ASTM D2729. THE PIPE SHALL BE OF THE ELASTOMERIC GASKET JOINT (INTEGRAL BELL) TYPE. JOINTS SHALL PROVIDE A WATERTIGHT SEAL AND SHALL BE MADE IN ACCORDANCE WITH THE PIPE MANUFACTURER'S INSTRUCTIONS. JOINTS SHALL BE OF THE PUSH-ON TYPE MEETING THE REQUIREMENTS OF ASTM D3212, AND, IN ADDITION, THE BELL SHALL BE DESIGNED TO RETAIN THE GASKET TO PREVENT PULL-OUT DURING THE MAKING OF THE JOINT.

9. PVC PLASTIC FITTINGS FOR USE WITH ASTM D3034 PIPE EIGHT (8) INCH IN SIZE AND SMALLER SHALL MEET THE REQUIREMENTS OF ASTM D3034 WITH A MINIMUM WALL THICKNESS OF SDR 35 AS DEFINED IN SECTION 7.4.1, AND SHALL BE MOLDED IN ONE PIECE WITH ELASTOMERIC JOINTS AND MINIMUM SOCKET DEPTHS AS SPECIFIED IN SECTIONS 6.2 AND 7.3.2. PVC MATERIAL SHALL HAVE A CELL CLASSIFICATION OF 1245-B OR C AS DEFINED IN ASTM D1784. GASKETS SHALL HAVE MINIMUM CROSS SECTIONAL AREA OF 0.20 SQ. IN. AND SHALL MEET THE REQUIREMENTS OF ASTM F447.

10. PVC PLASTIC FITTINGS FOR USE WITH ASTM D3034 PIPE TEN (10) INCH IN SIZE AND LARGER, AND FOR USE WITH ALL SIZES OF PVC PLASTIC PIPES OTHER THAN ASTM D3034 SHALL BE MOLDED OR FABRICATED IN ACCORDANCE WITH, AND HAVE JOINTS MEETING THE REQUIREMENTS OF THE ASTM STANDARD AS SPECIFIED FOR THE PIPE.

11. AT THE END OF ALL FITTINGS, PREMANUFACTURED TEES, ETC., OF ALL PIPE INSTALLATIONS, THE FINAL FITTING AT THE "PLUG" SHALL BE SDR 35 COMPATIBLE. NON-COMPATIBLE JOINTS TO EXISTING SEWERS SHALL BE MADE USING BANDED NEOPRENE COUPLINGS AS MANUFACTURED BY FERROCO, INC., OR CITY-APPROVED EQUAL.

12. THE PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321, AND WITH THE REQUIREMENTS OF THESE SPECIFICATIONS. ANY REQUIREMENTS IN THESE SPECIFICATIONS WHICH MAY BE IN CONFLICT OR INCONSISTENT WITH THE REQUIREMENTS OF ASTM D2321 SHALL BE VOID TO THE EXTENT OF SUCH CONFLICT OR INCONSISTENCY, EXCEPT IN ALL CASES MATERIAL FOR PIPE EMBEDMENT SHALL BE AS SUBSEQUENTLY SPECIFIED IN ITEM 4.12. PVC PLASTIC PIPE SHALL BE TESTED FOR DEFLECTION AS SUBSEQUENTLY SPECIFIED IN DIVISION III.

13. C. CONCRETE PIPE AND FITTINGS - CONCRETE PIPE AND FITTINGS SHALL BE OF THE SPIGOT AND SOCKET OR TONGUE AND GROOVE PATTERN MEETING THE REQUIREMENTS OF ASTM C76 AND SHALL BE CLASS IV OR V. PIPES SHALL BE OF THE GREATEST LENGTHS COMMERCIALY AVAILABLE. CIRCULAR PIPES HAVING ELLIPTICAL REINFORCING SHALL HAVE THE WORD "TOP" OR "BOTTOM" CLEARLY STENCILED ON THE INSIDE OF THE PIPE AT THE CORRECT PLACE TO INDICATE THE PROPER POSITION WHEN LAID. JOINTS SHALL BE OF THE RUBBER GASKET TYPE MEETING THE REQUIREMENTS OF ASTM C443. THE GASKET SHALL BE CONFINED IN A GROOVE AND SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.

14. FOR CONCRETE PIPES INSTALLED IN OPEN TRENCH, THE MAXIMUM ALLOWABLE TRENCH WIDTH AT THE TOP OF THE PIPE FOR THE VARIOUS SIZES AND CLASSES OF PIPE SHALL BE AS FOLLOWS:

CONCRETE PIPE TRENCH WIDTH

(AS MEASURED AT TOP OF PIPE)PIPE DIAMETERASTM C76-CLASSCONCRETE PIPE TRENCH WIDTH

(AS MEASURED AT TOP OF PIPE)PIPE DIAMETERASTM C76-CLASS(INCHES)INVT12'-0"3'-0"15'-0"3'-3"18'-3"3'-6"21'-3"6'-3"24'-0"4'-3"27'-4"6'-4"30'-4"9'-5"33'-5"35'-4"36'-5"6'-6"42'-3"6'-14"6'-9"47'-0"5'-7"54'-7"8'-0"60'-8"6'-16"6'-9"6'-22"6'-10"0"10'-0"

15. D. POLYPROPYLENE PIPE AND FITTINGS - PIPE SHALL BE JOINED USING A BELL & SPIGOT JOINT MEETING THE REQUIREMENTS OF ASTM F2764. THE JOINT SHALL BE WATERTIGHT ACCORDING TO THE REQUIREMENTS OF ASTM D3212. GASKETS SHALL MEET THE REQUIREMENTS OF ASTM F447. GASKET SHALL BE INSTALLED BY THE PIPE MANUFACTURER AND COVERED WITH A REMOVABLE, PROTECTIVE WRAP TO ENSURE THE GASKET IS FREE FROM DEBRIS AND PROTECTED FROM THE ELEMENTS. A JOINT LUBRICANT AVAILABLE FROM THE MANUFACTURER, OR AS APPROVED BY THE CITY, SHALL BE USED ON THE GASKET AND BELL DURING ASSEMBLY. 12-INCH THROUGH 60-INCH (300 TO 1500 MM) DIAMETERS SHALL HAVE AN EXTERIOR BELL WRAP INSTALLED BY THE MANUFACTURER.

16. FITTINGS SHALL CONFORM TO ASTM F2764. BELL AND SPIGOT CONNECTIONS SHALL UTILIZE A WELDED OR INTEGRAL BELL AND VALLEY OR INLINE GASKETS MEETING THE WATERTIGHT JOINT PERFORMANCE REQUIREMENTS OF ASTM D3212.

17. THE PIPE SHALL BE INSTALLED IN ACCORDANCE WITH ASTM D2321, AND WITH THE REQUIREMENTS OF THESE SPECIFICATIONS. ANY REQUIREMENTS IN THESE SPECIFICATIONS WHICH MAY BE IN CONFLICT OR INCONSISTENT WITH THE REQUIREMENTS OF ASTM D2321 SHALL BE VOID TO THE EXTENT OF SUCH CONFLICT OR INCONSISTENCY, EXCEPT IN ALL CASES MATERIAL FOR PIPE EMBEDMENT SHALL BE AS SUBSEQUENTLY SPECIFIED IN SECTION 4.15.

18. E. REPLACEMENT OF EXISTING SEWERS AND DRAINS - THE CONTRACTOR SHALL REPORT TO THE CITY ALL EXISTING SEWERS AND DRAINS EXPOSED DURING TRENCHING OR OTHER OPERATIONS. REPLACEMENTS SHALL BE MADE IN ACCORDANCE WITH ALL APPLICABLE REQUIREMENTS OF THESE SPECIFICATIONS FOR NEW CONSTRUCTION AND IN ACCORDANCE WITH ALL APPLICABLE REQUIREMENTS ODOT ITEM 611 USING PIPE WITH PREMIUM JOINTS UNLESS OTHERWISE SPECIFIED, AS APPROVED BY THE CITY. IN THE EVENT OF CONFLICT, THE REQUIREMENTS OF THESE SPECIFICATIONS SHALL TAKE PRECEDENCE.

19. PIPE FOR STORM SEWERS SHALL BE APPROVED FOR SUCH USE. REPLACEMENTS 12 FEET OR LESS IN LENGTH OF PERFORATED PIPE OR OPEN JOINT TILE (SUCH AS UNDERDRAINS) SHALL BE MADE BY USING PVC PLASTIC PIPE MEETING THE REQUIREMENTS OF ASTM D3034, SDR35, OR F679 BASED ON DIAMETER, AS SPECIFIED IN PARAGRAPH 4.1.A. IN ANY EVENT, ALL SUCH REPLACEMENTS IN CULTIVATED FIELDS SHALL BE WITH THE SPECIFIED PERFORATED PIPE. DRAIN DISCHARGES REMOVED AT DITCHES OR OTHER WATERCOURSES SHALL BE REPLACED WITH ONE STANDARD LENGTH OF REINFORCED CONCRETE PIPE, OR AS OTHERWISE APPROVED BY THE CITY. JOINTS BETWEEN EXISTING AND REPLACEMENT PIPES, WHEN OF DIFFERING MATERIALS OR WITH OTHERWISE NON-COMPATIBLE JOINTS, SHALL BE MADE USING BANDED NEOPRENE COUPLINGS AS MANUFACTURED BY FERROCO, INC.

20. EXISTING SEWERS AND DRAINS SHALL BE REPLACED SO AS TO WITHSTAND FUTURE SETTLEMENT BY BRIDGING WITH TIMBER SUPPORTS A MINIMUM OF SIX (6) INCHES SQUARE. BRIDGING SHALL EXTEND INTO UNDISTURBED EARTH A MINIMUM OF 12 INCHES EACH SIDE OF THE TRENCH, AND THE PIPE, TILE, ETC., BANDED OR TIED USING STAINLESS STEEL BANDING TO THE BRIDGING FOR ITS FULL LENGTH. WHERE TIMBER BRIDGING CANNOT BE SUPPORTED BY A FIRM FOUNDATION, THE CONTRACTOR SHALL PROVIDE VERTICAL SUPPORT FOR THE TIMBER BRIDGING, INCLUDING ANY LATERAL BRACING NECESSARY TO PROVIDE A FIRM AND SUBSTANTIAL SUPPORT. SUPPORTS AND BRACING SHALL BE OF NATIVE HARDWOOD.

21. F. STORM SEWER LATERALS - ALL STRUCTURES, YARD DRAINS, AND DOWNSPOUT DRAINS THAT CONNECT TO THE PUBLIC STORM SEWER SYSTEM WITHIN THE PUBLIC RIGHT-OF-WAY OR IN A STORMDRAINAGE EASEMENT SHALL BE A MINIMUM OF SIX (6) INCH DIAMETER, PVC SDR 35 OR AS SPECIFIED IN PARAGRAPH 4.1.A.

(ORD. 18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.2 PIPELINE MARKERS - N/A

4.3 STEEL ENCASEMENT PIPE -N/A

4.4 BRIDGES/BOX CULVERTS

A BRIDGE IS ANY STRUCTURE GREATER THAN OR EQUAL TO TEN (10) FEET IN LENGTH, INCLUDING SUPPORTS, ERRECTED OVER A DEPRESSION OR AN OBSTRUCTION, AS WATER, HIGHWAY OR RAILWAY, AND HAVING A PASSAGEWAY FOR MOVING TRAFFIC. PEDESTRIANS OR OTHER MOVING LOADS. BRIDGE AND BOX CULVERTS SHALL BE SIZED ACCORDING TO THE ODOT LOCATION AND DESIGN MANUAL AND BRIDGE DESIGN MANUAL, LATEST EDITION. BOX CULVERT MATERIAL AND CONSTRUCTION SHALL BE IN COMPLIANCE WITH THE ODOT ITEM 706.05, LATEST EDITION. BRIDGES SHALL MEET AASHTO STANDARD SPECIFICATIONS FOR HIGHWAY BRIDGES, LATEST EDITION.

(ORD. 18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.5 CATCH BASINS

A. BASES AND WALLS - BASES AND WALLS FOR CATCH BASINS SHALL BE PRECAST AND SHALL EITHER BE 2'-0" X 2'-0" (ODOT 2-2-4 OR B) OR 3'-0" X 3'-0" (ODOT 2-3) IN SIZE. AS DESIGNATED ON THE DRAWINGS OR AS REQUIRED TO PROPERLY ACCOMMODATE THE PIPE SIZES REQUIRED FOR THE INSTALLATION. THE STRUCTURES SHALL MEET H-20 LOADINGS IF LOCATED WITHIN ANY PAVEMENT. SPACING SHALL BE NO GREATER THAN 300 FEET APART. INVERTS SHALL BE POURED TO THE SPRING LINE OF PIPE. CATCH BASINS GREATER THAN FOUR (4) FEET DEEP SHALL HAVE A MINIMUM OF 3' X 3' WITH POLYPROPYLENE STEPS.

B. FRAMES AND GRATES - FRAMES AND GRATES FOR CATCH BASINS SHALL BE EJ (FORMERLY EAST JORDAN IRON WORKS) 5250 FRAME WITH 5110, TYPE M3 SINUSOIDAL GRATE OR CITY-APPROVED EQUAL. FRAMES AND GRATES WITH A CURB SHALL BE EJ 7035 (SINGLE), 7036 (DOUBLE) WITH A TYPE M6 VANE GRATE AND TYPE T6 BACKS, OR EQUAL. GRATE OPENINGS SHALL ALLOW PASSAGE OF 25-YEAR STORM EVENT VOLUMES.

(ORD. 18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.6 MANHOLES

A. DESCRIPTION - MANHOLES SHALL BE CONSTRUCTED OF PRECAST REINFORCED CONCRETE SECTIONS AND APPURTENANCES MEETING THE REQUIREMENTS OF ASTM C478, EXCEPT AS MODIFIED BY THESE SPECIFICATIONS AND THE DETAILS ON THE DRAWINGS, AND SHALL BE COMPLETE WITH REQUIRED PIPE SEWER STUBS. MANHOLES SHALL HAVE A MINIMUM 48-INCH I.D. OR LARGER AS RECOMMENDED BY THE MANUFACTURER. AN AFFIDAVIT FROM THE MANUFACTURER SHALL BE PROVIDED STATING THAT THE MANHOLE IS APPROPRIATELY SIZED FOR THE SIZES AND ANGLES OF INCOMING PIPES.

THE CITY MAY REQUIRE ANTI-FLOATATION PADS FOR MANHOLES, UPON REVIEW OF THE REQUIRED SOIL BORINGS.

B. BASES - BASES SHALL BE CONSTRUCTED IN TWO POURS OR MONOLITHICALLY WITH BOTTOM REINFORCEMENT TIED TO SIDE REINFORCEMENT TO FORM AN INTEGRAL STRUCTURE. WALLS SHALL HAVE A MINIMUM THICKNESS OF 1/12 THE BASE I.D. PLUS ONE (1) INCH. SEE FIGURE 4.6.1.

BASES SHALL INCORPORATE PROVISIONS FOR MAKING A FLEXIBLE JOINT BETWEEN THE PIPE AND THE MANHOLE FOR ALL PIPE CONNECTIONS. FLEXIBLE JOINTS SHALL BE KOR-N-SEAL AS MANUFACTURED BY NATIONAL POLLUTION CONTROL SYSTEMS, INC.; A-LOK AS MANUFACTURED BY A-LOK PRODUCTS CORPORATION, OR CITY-APPROVED EQUAL. FLEXIBLE JOINTS SHALL BE SHOCK ABSORBENT AND SHEAR RESISTANT; SHALL BE DESIGNED TO PREVENT ANY DIRECT CONTACT BETWEEN THE PIPE AND MANHOLE, AND SHALL PROVIDE A TIGHT, INFILTRATION PROOF SEWER CONNECTION WITH THE PIPE DEFLECTED UP TO 10 DEGREES IN ANY DIRECTION. SHOULD INCORPORATION OF THE FLEXIBLE JOINTS REQUIRE A BASE I.D. GREATER THAN REQUIRED FOR THE WALL SECTIONS, THE CONTRACTOR SHALL FURNISH AND INSTALL THE LARGER BASE AND AN APPROVED PRECAST REINFORCED CONCRETE TRANSITION SECTION TO GO FROM THE LARGER BASE TO THE WALL SECTIONS.

JOINTS BETWEEN BASES AND WALL SECTIONS SHALL BE AS SUBSEQUENTLY SPECIFIED FOR THE WALLS.

IF NOT INTEGRALLY CAST WITH THE BASE, AFTER INSTALLATION OF THE PIPES PROVIDE AN ODOT CLASS F CONCRETE INVERT THROUGH THE MANHOLE. THE INVERT SHALL HAVE A DEPTH THROUGH THE MANHOLE EQUAL TO ONE HALF OF THE DIAMETER OF THE SEWER PIPE AND SHALL SLOPE UPWARD TOWARD THE MANHOLE WALLS APPROXIMATELY THREE (3) INCHES. CONCRETE SHALL BE TROWELLED SMOOTH, AND SHALL BE PLACED SO AS NOT TO INTERFERE WITH THE FLEXIBILITY OF THE JOINT.

BASES SHALL BE SET PLUMB AND AT THE PROPER ELEVATION ON A CUSHION OF COMPACTED ODOT #57 CRUSHED LESTMONE AS APPROVED BY THE CITY.

C. WALLS AND TOPS - WALLS SHALL BE VERTICAL RISER SECTIONS HAVING A MINIMUM WALL THICKNESS OF 1/12 THE BASE I.D. PLUS ONE (1) INCH. THE TOP SECTION SHALL BE AN ECCENTRIC CONE NARROWING DOWN TO AN I.D. OF NOT LESS THAN 24 INCHES AND AN O.D. OF NOT LESS THAN THAT OF THE SUBSEQUENTLY SPECIFIED GRADE RINGS. NO PIPES SHALL ENTER THE CONE SECTION. SEE FIGURE 4.6.2 FOR STANDARD AND SHALLOW MANHOLE DETAILS AND FIGURE 4.6.3 FOR TRANSITION MANHOLE DETAILS. MANHOLES TOO SHALLOW TO ACCOMMODATE A CONE SECTION SHALL HAVE A REINFORCED FLAT SLAB TOP. FLAT SLAB TOPS SHALL BE DESIGNED TO WITHSTAND H-20 TRAFFIC LOADING AND DESIGN CALCULATIONS SHALL BE SUBMITTED TO THE CITY. SEE FIGURE 4.6.4.

FIGURE 4.6.2

FIGURE 4.6.4

ADJOINING RISER SECTIONS SHALL BE FIRMLY KEYED TOGETHER BY MEANS OF TONGUE AND GROOVE JOINTS WITH RUBBER GASKETS MEETING THE REQUIREMENTS OF ASTM C443. IN ADDITION, PREFORMED PLASTIC GASKET MATERIAL SHALL BE PROVIDED ON THE OUTSIDE SHOULDER OF ALL JOINTS. INSTALLATION OF THE GASKET MATERIAL SHALL NOT INTERFERE WITH THE PROPER SEALING OF THE RUBBER GASKET. THE PREFORMED GASKET MATERIAL SHALL MEET THE REQUIREMENTS OF FEDERAL SPECIFICATION SS-S-210A AND SHALL BE AS MANUFACTURED BY HAMILTON-KENT MANUFACTURING COMPANY, K.T. SNYDER COMPANY, INC., OR EQUAL.

EACH MANHOLE FRAME SHALL BE SET AT THE PROPER ELEVATION BY USE OF PRECAST CONCRETE GRADE RINGS. THE RINGS SHALL BE PROVIDED FOR A MINIMUM HEIGHT OF FOUR (4) INCHES AND SHALL NOT EXCEED 12 INCHES IN HEIGHT. RINGS, UNLESS OTHERWISE SUBSEQUENTLY SPECIFIED, SHALL HAVE AN I.D. EQUAL TO THE ACCESS OPENING IN THE MANHOLE TOP SECTION, AND AN O.D. NOT LESS THAN THE O.D. OF THE MANHOLE FRAME. THE RINGS SHALL EACH BE SET IN A FULL BED OF MORTAR COMPOSED OF 1 PART, BY VOLUME, PORTLAND CEMENT AND 2 PARTS CLEAN, HARD SAND. THE INTERIOR OF THE GRADE RINGS SHALL BE MORTARED TO PROVIDE A SMOOTH COMMON SURFACE FROM FRAME TO TOP. SEE FIGURES 4.6.5.

WHEN THE MANHOLE FRAME IS TO BE ANCHORED TO THE MANHOLE TOP, AS SUBSEQUENTLY SPECIFIED IN ITEM 4.7, THE TOP SECTION AND GRADE RINGS SHALL HAVE FOUR 1-INCH DIAMETER HOLES LOCATED TO MATCH THE HOLES IN THE CASTING AND SHALL BE OF SUCH DIMENSIONS AS TO PROVIDE A MINIMUM TWO (2) INCH CONCRETE COVER FOR THE ONE (1) INCH DIAMETER HOLES. HOLES IN THE TOP SECTION SHALL EXTEND AT LEAST SIX (6) INCHES INTO THE CONCRETE. HOLES SHALL NOT BE MADE IN THE FIELD.

D. STEPS - STEPS SHALL BE PROVIDED IN ALL MANHOLES. STEPS SHALL MEET THE REQUIREMENTS OF ASTM C478 AND SHALL BE OF REINFORCED POLYPROPYLENE. INSTALLATION OF MANHOLES, WHEN IN PAVEMENT, SHALL BE SUCH THAT STEPS ARE IN THE CENTER OF A TRAFFIC LANE OR BETWEEN LANES WHERE POSSIBLE, AND, WHEN OUTSIDE PAVEMENT, SHALL BE SUCH THAT STEPS ARE LOCATED AWAY FROM THE PAVEMENT EDGE UNLESS THE MANHOLE IS WITHIN A DITCH LINE, IN WHICH CASE THEY SHALL BE LOCATED AT THE HIGH SIDE OF THE DITCH SLOPE.

REINFORCED POLYPROPYLENE STEPS SHALL CONSIST OF A 1/2 INCH STEEL REINFORCING ROD ENCAPSULATED IN A COPOLYMER POLYPROPYLENE PLASTIC AND SHALL INCORPORATE A NOTCHED TREAD RIDGE AND RETAINER LUGS ON EACH SIDE OF THE TREAD RIDGE. THE STEEL ROD SHALL BE CONTINUOUS THROUGH THE ENTIRE LENGTH OF LEGS AND TREAD. STEPS OF THE PRESS FIT TYPE DRIVEN INTO THE CONCRETE WALL SHALL HAVE A PULLOUT RESISTANCE OF NOT LESS THAN 1,500 POUNDS PER LEG, AS EVIDENCED BY TEST DATA. STEPS MUST BE PROVIDED FOR ANY STRUCTURE GREATER THAN FOUR (4) FEET DEEP.

E. PIPE SEWER STUBS - WHERE NOTED, PIPE SEWER STUBS SHALL BE PROVIDED AT MANHOLES FOR FUTURE SEWER CONNECTIONS. THE STUBS SHALL BE OF THE SAME TYPE OF PIPE AS BEING PROVIDED ON THE PROJECT FOR THE RESPECTIVE SIZES OF PIPE, SHALL BE A MINIMUM OF TWO (2) FEET IN LENGTH OUTSIDE THE MANHOLE WALL, AND SHALL TERMINATE WITH A FULL PIPE BELL. INSTALLATION SHALL BE AS SPECIFIED IN DIVISION II. THE END OF EACH STUB SHALL BE PROVIDED WITH A PIPE STOPPER (PLUG) SPECIFICALLY DESIGNED FOR USE WITH THE PIPE. PLUGS SHALL BE FOR PERMANENT OR TEMPORARY USE, SHALL BE WATERTIGHT, AND SHALL BE REMOVABLE WITHOUT DAMAGING THE PIPE.

(ORD. 18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.7 FRAMES AND COVERS

ALL FRAMES AND COVERS SHALL BE HEAVY DUTY GRAY IRON CASTINGS CONFORMING TO ASTM A48. BOTH THE UNDERSIDE OF THE COVER AND THE UPPER SURFACE OF THE LEDGE UPON WHICH IT RESTS SHALL BE MACHINED SO AS TO PREVENT ROCKING ON ITS SUPPORTING SURFACE. ALL CASTINGS SHALL BE CLEANED AND COATED WITH ASPHALT PAINT PRIOR TO INSTALLATION AND, AFTER INSTALLATION, THE TOPS OF FRAMES AND COVERS SHALL BE GIVEN AN ADDITIONAL COAT OF ASPHALT PAINT.

THE FRAMES SHALL HAVE A CLEAR OPENING OF NOT LESS THAN 24 INCHES IN DIAMETER AND A HEIGHT OF NOT LESS THAN 7 INCHES. COVERS SHALL HAVE STRENGTHENING RIBS ON THE UNDERSIDE, AND SHALL HAVE THE WORDS "CITY OF HUDSON STORM SEWER" CAST INTO THE TOP. NO FRAME AND COVER UNIT SHALL WEIGH LESS THAN 375 POUNDS. STANDARD FRAMES AND COVERS SHALL BE EAST JORDAN IRON WORKS 1040 WITH TYPE A SOLID COVER, OR EQUAL.

FRAMES SHALL HAVE FOUR EQUALLY SPACED ANCHOR BOLT HOLES IN THE BASE FLANGE AND SHALL BE ANCHORED TO THE MANHOLE TOP. ANCHORS SHALL BE FOUR 3/4-INCH DIAMETER ALL-THREAD RODS, AND EACH SHALL BE COMPLETE WITH WASHER AND NUT FOR HOLDING THE FRAME DOWN. ANCHORS SHALL BE OF A LENGTH TO EXTEND THROUGH THE GRADE RINGS AND TO THE BOTTOM OF THE HOLE IN THE MANHOLE TOP, AND ALLOW FOR AT LEAST THE LENGTH OF ONE NUT TO PROTRUDE THROUGH THE NUT WHEN TIGHTENED. THE ANCHORS SHALL BE SET WITH THE ENTIRE ANNULAR SPACE AROUND THE RODS FILLED WITH EPOXY FROM THE TOP OF THE RINGS TO THE BOTTOM OF THE HOLE IN THE MANHOLE TOP. THE EPOXY SHALL BE 100%, 2-PART, WITH A MINIMUM COMPRESSIVE STRENGTH OF 5,000 PSI, AND SHALL BE RAWLUMSKA FOIL-FAST INJECTION GEL SYSTEM BY THE RAWLUMPLUG COMPANY, INC., OR EQUAL. AFTER THE EPOXY HAS CURED, THE FRAME SHALL BE BOLTED IN PLACE.

THE MANHOLE FRAMES SHALL BE FIRMLY SET ON TOP OF THE ADJUSTING RINGS WITH A FULL LEVELING BED OF 1:1 CEMENT MORTAR. WHERE MANHOLES ARE LOCATED IN PAVED AREAS, THE SURFACE OF THE COVER SHALL BE MADE FLUSH WITH THE PAVEMENT SURFACE. IN UNPAVED STREETS AND ALLEY AREAS, THE COVER SHALL BE SET NOT TO EXCEED ONE (1) INCH ABOVE THE GROUND SURFACE. ON RIGHT-OF-WAY AND IN DITCHES COVER ELEVATION SHALL BE AS APPROVED BY THE CITY.

AFTER A MANHOLE FRAME IS INSTALLED IN ITS FINAL POSITION, IT SHALL BE ENCASED IN CLASS C CONCRETE. THE CONCRETE ENCASEMENT SHALL EXTEND FROM A HORIZONTAL PLANE FOUR (4) INCHES BELOW THE LOWEST ADJUSTING RING UP TO A HORIZONTAL PLANE THROUGH THE MID-POINT OF THE FRAME. THE CONCRETE ENCASEMENT SHALL BE MADE CIRCULAR IN PLAN, USING A MINIMUM 48-INCH DIAMETER STEEL CASING RING AS A FORM, AND SHALL BE CENTERED ON THE FRAME. (ORD18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.8 STORMWATER CONNECTIONS

STORMWATER CONNECTIONS FOR STORM SEWERS SHALL BE SIX (6) INCHES IN DIAMETER, UNLESS OTHERWISE SHOWN, AND SHALL BE FURNISHED AND INSTALLED FOR EXISTING AND FUTURE HOUSES AND BUSINESSES. LOCATIONS AND DEPTHS OF STORMWATER CONNECTIONS, WHERE SHOWN ON THE DRAWINGS, ARE APPROXIMATE ONLY. FINAL LOCATIONS AND DEPTHS WILL BE ESTABLISHED BY THE CITY AT THE TIME OF CONSTRUCTION. ALL DOWNSPOUTS, FOUNDATION DRAINS, AND YARD DRAINS SHALL BE CONNECTED TO THE STORM SEWER, AS APPROVED BY THE CITY.

CONNECTIONS TO THE MAIN SEWER SHALL INCLUDE THE FURNISHING AND INSTALLATION OF AN APPROPRIATE WYE IN THE NEW SEWER.

NEW STORMWATER CONNECTIONS SHALL BE CONNECTED INTO EXISTING STORM SEWERS WHERE APPROVED BY MEANS OF POSITIVELY SEALING CONNECTIONS. CONNECTORS SHALL BE OF MATERIALS SUCH AS RUBBER GASKETS, SLEEVES, ETC. WITH OR WITHOUT STAINLESS STEEL CLAMPS, BOLTS, ETC. THAT WILL NOT ERODE OVER TIME. CONNECTORS SHALL BE DESIGNED SPECIFICALLY FOR THE APPLICATION INTENDED. SERVICE CONNECTIONS SHALL BE BY SEWER SADDLES, STYLE "CB" ALL STAINLESS STEEL, AS MANUFACTURED BY ROMAC INDUSTRIES, OR EQUAL; OR BY USE OF INSERTA TEES AS MANUFACTURED BY INSERTA FITTINGS COMPANY.

WHERE STORMWATER CONNECTIONS ARE TO BE INSTALLED TO THE PROPERTY LINE, THE PIPE SHALL BE INSTALLED TRUE TO LINE, AT A 90° ANGLE FROM THE MAINLINE, IF POSSIBLE, AND ON AT LEAST A 1% GRADE, BUT NO MORE THAN A 3% GRADE. EXCEPT WHERE OTHERWISE SPECIFICALLY REQUIRED OR PERMITTED BY THE CITY, STORMWATER CONNECTIONS SHALL BE INSTALLED BY OPEN CUT EXCAVATION, SHALL HAVE A MINIMUM DEPTH OF SIX (6) FEET AT THE PROPERTY LINE AND SHALL BE DEEP ENOUGH TO SERVE ALL BASEMENT FOUNDATION DRAINS, UNLESS OTHERWISE APPROVED BY THE CITY. THE REQUIREMENTS FOR CONSTRUCTION SHALL, IN ALL RESPECTS, COMPLY WITH THOSE SPECIFIED IN THIS SECTION FOR THE MAIN SEWERS.

IN GENERAL, RISER SECTIONS WILL BE REQUIRED BETWEEN THE MAIN LINE SEWER CONNECTION AND THAT PORTION OF THE SERVICE CONNECTION INSTALLED ON AT LEAST A 1% GRADE WHERE DEPTHS TO THE MAIN SEWER INVERT EXCEED 12 FEET. RISER PIPE SHALL BE DEFINED AS THE VERTICAL PIPE, PLUS ALL PIPE AND FITTINGS REQUIRED BETWEEN THE VERTICAL PIPE AND THE CONNECTION AT THE MAIN SEWER. THE RISER SHALL BE FIXED IN PLACE FOR ITS FULL HEIGHT BY PROVIDING THOROUGHLY TAMPED PIPE EMBEDMENT MATERIAL. CLEAN-OUTS SHALL BE ALLOWED AS REQUIRED AND/OR APPROVED BY CITY. SEE FIGURE 4.10.1.

WHERE REQUIRED, STORMWATER CONNECTIONS SHALL BE INSTALLED WITHIN STEEL ENCASEMENT PIPE. STEEL ENCASEMENT PIPE SHALL EXTEND FIVE (5) FEET EACH SIDE OF THE PAVEMENT. STEEL ENCASEMENT PIPE SHALL BE AS PREVIOUSLY SPECIFIED IN ITEM 4.3, WITH THE ENCASEMENT PIPE TO BE SIZED FOR AT LEAST 2 INCHES CLEARANCE AROUND THE PIPE BELL, BUT NOT TO EXCEED 14 INCHES IN SIZE, AND THE MINIMUM WALL THICKNESS SHALL BE 0.188 INCH.

STORMWATER CONNECTIONS NOT IMMEDIATELY CONNECTED TO AN EXISTING SEWER SHALL BE CLOSED WITH A STOPPER. STOPPERS SHALL BE SPECIFICALLY DESIGNED FOR USE WITH THE PIPE, SHALL BE FOR USE AS A PERMANENT OR TEMPORARY PLUG, SHALL BE WATERTIGHT, AND SHALL BE REMOVABLE WITHOUT DAMAGING THE PIPE. PIPE DAMAGED WHEN INSTALLING OR REMOVING STOPPERS SHALL BE REPLACED AT THE EXPENSE OF THE CONTRACTOR.

THE ENDS OF STORMWATER CONNECTIONS SHALL NOT BE BACKFILLED UNTIL THE LOCATION IS REFERENCED IN ACCORDANCE WITH FIGURE 4.10.2. A TWO (2) INCH SQUARE OAK POLE SHALL BE ACCURATELY PLACED OVER THE TERMINI OF ALL SUCH STORMWATER CONNECTIONS AND SHALL EXTEND VERTICALLY TO FLUSH WITH THE SURFACE OF THE GROUND SO THAT IT CAN BE LOCATED.

NO STORMWATER CONNECTIONS SHALL BE TIED INTO THE STORM SEWERS PRIOR TO THE CITY RECEIVING AND APPROVING RECORD DRAWINGS FOR THE STORM SEWER INSTALLATION.

(ORD. 18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.9 BEDDING AND BACKFILL

A. BEDDING - PIPE EMBEDMENT SHALL BE CRUSHED LESTMONE #57 FOR SEWERS, FROM FOUR (4) - INCHES BELOW THE PIPE BARREL TO 12-INCHES ABOVE THE PIPE BARREL FOR PVC PIPE AND TO THE SPRINGLINE FOR RCP PIPE. FOR POLYPROPYLENE PIPE, CRUSHED LESTMONE #57 SHALL EXTEND FOUR (4) INCHES BELOW THE PIPE BARREL TO SIX (6) INCHES ABOVE THE PIPE BARREL FOR 12-INCH THROUGH 24 DIAMETER SEWER, AND SIX (6) BELOW THE PIPE BARREL TO SIX (6) INCHES ABOVE THE PIPE BARREL FOR 30- INCH THROUGH 60-INCH DIAMETER SEWER. SEE FIGURE 4.17.1. CONCRETE ENCASEMENT AND CONCRETE PIPE CRODLES SHALL BE ODOT CLASS C CONCRETE.

B. GRANULAR BACKFILL - THE GRANULAR BACKFILL SHALL MEET THE REQUIREMENTS OF ODOT ITEM 304 CRUSHED LESTMONE. TRENCHES WITHIN RAILROAD RIGHT-OF-WAY, EXCEPT FOR LONGITUDINAL OCCUPANCY, SHALL BE BACKFILLED WITH CRUSHED STONE WITH A TOP SIZE OF THE AGGREGATE TO BE A MAXIMUM OF TWO INCHES AND TO HAVE NO MORE THAN 5% PASSING THE NUMBER 200 SIEVE. THE GRADATION OF THE MATERIAL IS TO BE SUCH THAT A DENSE STABLE MASS IS PRODUCED.

C. CONTROL DENSITY FILL (CDF) - CONTROL DENSITY FILL (CDF) SHALL BE ODOT ITEM 613, TYPE I LOW STRENGTH MORTAR, EXCEPT NO SLAG PERMITTED. THE DESIGN MIX USED SHALL BE APPROVED BY THE CITY, AND SHALL HAVE A DESIGN STRENGTH OF 50 PSF. (ORD. 18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

II. INSTALLATION

4.10 TRENCHES

EXCEPT WHERE OTHERWISE SPECIFICALLY REQUIRED OR PERMITTED BY THE CITY, SEWERS SHALL BE LAID IN OPEN TRENCH, SHALL BE STARTED AT THE LOWEST POINT, AND SHALL HAVE SPIGOT ENDS POINTING IN THE DIRECTION OF FLOW.

PRIOR TO TRENCHING, IN LAWN AREAS AND IN FIELDS USED FOR FARMING, BOTH AS DETERMINED BY THE CITY, ALL TOPSOIL SHALL BE REMOVED.

THE USE OF EQUIPMENT WITH METAL TRACKS OR TREADS WILL NOT BE PERMITTED ON PAVED SURFACES WHICH WILL NOT BE REMOVED DURING TRENCHING OPERATIONS WITHOUT SOME TYPE OF PAVEMENT PROTECTION, SUCH AS MATTING OR RUBBER TRACKS.

THE WIDTH OF TRENCHES BELOW THE LEVEL OF THE TOP OF THE PIPE SHALL NOT EXCEED THE DIMENSIONS PREVIOUSLY SPECIFIED FOR THE VARIOUS TYPES AND SIZES OF PIPE, AND SHALL NOT BE LESS THAN 12 INCHES GREATER IN WIDTH THAN THE OUTSIDE DIAMETER OF THE PIPE BARREL, UNLESS OTHERWISE DIRECTED BY THE CITY. WHENEVER THE MAXIMUM ALLOWABLE TRENCH WIDTH (BELOW THE LEVEL OF THE TOP OF THE PIPE) IS EXCEEDED FOR ANY REASON, THE CITY RESERVES THE RIGHT TO DIRECT THE CONTRACTOR TO UTILIZE PIPE OF GREATER STRENGTH, TO MODIFY THE TYPE OF BACKFILL, TO EMBED THE PIPE IN CONCRETE, OR TO UTILIZE A COMBINATION OF THESE PROCEDURES, ALL AT THE EXPENSE OF THE CONTRACTOR.

TRENCHES IN EARTH SHALL BE EXCAVATED TO A DEPTH OF NOT LESS THAN ONE-EIGHTH THE OUTSIDE DIAMETER OF THE PIPE BEING INSTALLED OR 4 INCHES, WHICHEVER IS GREATER, BELOW THE OUTSIDE BOTTOM OF THE PIPE BARREL AND BELL WHEN THE PIPE IS LAID ON ITS FINAL GRADE.

TRENCHES IN ROCK SHALL BE EXCAVATED TO A DEPTH OF ONE-THIRD THE INSIDE DIAMETER OF THE PIPE, BUT WITHIN THE LIMITS OF 4 INCHES TO 12 INCHES, BELOW THE OUTSIDE BOTTOM OF THE PIPE BARREL AND BELL WHEN THE PIPE IS LAID ON ITS FINAL GRADE AND THE PIPE SHALL THEN BE LAID ON A CUSHIONING LAYER OF BEDDING MATERIAL AS SPECIFIED OR AS APPROVED BY THE CITY AND PROVIDED BY AND AT THE EXPENSE OF THE CONTRACTOR. ROCK EXCAVATION SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS SUBSEQUENTLY SPECIFIED IN ITEM 4.17.

PRIOR TO OPEN TRENCHES ENTERING THE PAVED LIMITS OF A STREET, ALLEY, DRIVEWAY, SIDEWALKS OR PARKING AREA, THE PAVEMENT SHALL BE NEATLY CUT FOR ITS FULL DEPTH, REMOVED, AND DISPOSED OF OFF THE PROJECT SITE. STREET AND ROAD CROSSINGS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE REQUIREMENTS SPECIFIED IN SECTION 7 - ROADWAY.

TRENCHES SHALL BE KEPT SUFFICIENTLY FREE OF WATER DURING PIPE LAYING AND JOINTING. WHEN WATER EXISTS IN THE TRENCHES AT THE TIME OF PIPE LAYING, THE CONTRACTOR SHALL DEWATER THE TRENCH AT HIS EXPENSE.

(ORD. 18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.11 PROTECTION OF EXISTING UTILITIES

EXISTING UNDERGROUND UTILITIES ALONG THE ROUTE OF CONSTRUCTION, AS SHOWN ON THE DRAWINGS OR MARKED AT THE TIME OF CONSTRUCTION BY THE UTILITY OWNER, SHALL BE UNCOVERED BY THE CONTRACTOR AND THEIR ELEVATIONS DETERMINED AT LEAST 400 FEET IN ADVANCE OF PIPE INSTALLATION FOR SEWERS. CONTRACTOR SHALL CONTACT OUPS 48 HOURS PRIOR TO ANY EXCAVATION WORK.

ALL UNDERGROUND UTILITIES, WHEN ENCOUNTERED, SHALL BE ADEQUATELY SUPPORTED, SHORED UP OR OTHERWISE PROTECTED WHENEVER EXPOSED IN THE EXCAVATION. TIMBER SUPPORTS SHALL BE A MINIMUM OF 6 INCHES SQUARE. SUPPORTS SHALL EXTEND INTO UNDISTURBED EARTH A MINIMUM OF 12 INCHES EACH SIDE OF THE TRENCH AND THE PIPE, CONDUIT, ETC.. BANDED OR TIED TO THE BRIDGING FOR ITS FULL LENGTH USING STAINLESS STEEL BANDING. WHERE BRIDGING CANNOT BE SUPPORTED BY A FIRM FOUNDATION, THE CONTRACTOR SHALL PROVIDE VERTICAL SUPPORT FOR THE BRIDGING, INCLUDING ANY LATERAL BRACING NECESSARY TO PROVIDE A FIRM AND SUBSTANTIAL SUPPORT. SUPPORTS AND BRACING SHALL BE FURNISHED AND INSTALLED BY THE CONTRACTOR. SEE FIGURE 4.15.1.

THE DRAWINGS SHALL INDICATE THE LOCATION OF EXISTING UTILITIES, IN ACCORDANCE WITH THE BEST INFORMATION PRESENTLY AVAILABLE. THE CITY ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THEIR LOCATION OR THAT ALL UTILITIES ARE SHOWN. A LISTING OF UTILITY COMPANY CONTACTS SHALL BE INCLUDED ON THE DRAWINGS.

PRIOR TO PERFORMING ANY EXCAVATION, WRITTEN OR ORAL NOTIFICATION SHALL BE GIVEN TO ALL UTILITIES WITHIN THE AREA TO BE EXCAVATED NOT LESS THAN TWO WORKING DAYS NOR MORE THAN TEN WORKING DAYS IN ADVANCE OF THE WORK. FOR CITY UTILITIES, NOTIFICATION MUST BE IN WRITING. THE NOTICE SHALL INCLUDE:

- THE NAME OF THE PROJECT, IF APPLICABLE;
- THE NAME, ADDRESS, AND TELEPHONE NUMBER OF THE PERSON FILING THE NOTICE;
- THE NAME, ADDRESS, AND TELEPHONE NUMBER OF THE PERSON DOING THE EXCAVATION;
- THE ANTICIPATED STARTING DATE OF THE EXCAVATION;
- THE ANTICIPATED DURATION OF THE EXCAVATION;
- THE TYPES OF EXCAVATION TO BE CONDUCTED;
- THE LOCATION OF THE PROPOSED EXCAVATION;
- ANY ANTICIPATED INTERRUPTIONS TO SERVICE; AND
- WHETHER OR NOT EXPLOSIVES WILL BE USED.

THE EXCAVATION WORK SHALL BE SO PLANNED AS TO AVOID DAMAGE TO AND MINIMIZE THE INTERFERENCE WITH EXISTING UNDERGROUND UTILITIES IN THE AREA. ADEQUATE CLEARANCE BETWEEN THE CUTTING EDGE OF THE EXCAVATION EQUIPMENT AND THE UNDERGROUND UTILITY SHALL BE MAINTAINED TO AVOID DAMAGE TO THE UTILITY. ABOVE GROUND (AERIAL) UTILITIES, INCLUDING POWER, TELEPHONE AND CABLE



C:\DC\ACD\Draw\CES0\CCC - Hudson - Civil Master Plan Study\Project Files\CES0\03-CIVIL\PLAN\NOT\Major Site Plans\765295\_CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel

CITY OF HUDSON SECTION 4. STORM COLLECTION  
4.12 TRENCH PROTECTION

WHERE NECESSARY TO PREVENT CAVING OF THE TRENCH AND OTHER EXCAVATION, AND FOR PROTECTION OF WORKMEN AND NEARBY STRUCTURES, TRENCH PROTECTION SHALL BE PROVIDED PER OSHA STANDARDS BY AND AT THE EXPENSE OF THE CONTRACTOR. TRENCH PROTECTION SHALL BE BY TRENCH BOX, WOOD SHEETING AND BRACING OR SUCH OTHER METHODS AS DETERMINED BY THE CONTRACTOR. IF WOOD SHEETING OR BRACING IS USED, THE DESIGN OF THE SHEETING OR BRACING SHALL BE SEALED BY AN OHIO REGISTERED PROFESSIONAL ENGINEER AND SUBMITTED TO THE CITY PRIOR TO INSTALLATION. CONTRACTOR SHALL HAVE A COMPETENT PERSON ON-SITE TO DETERMINE THE APPROPRIATE METHOD FOR THE CONDITIONS.

WOOD SHEETING AND BRACING SHALL BE OF SOUND LUMBER SUITABLE FOR THE PURPOSE INTENDED AND SHALL BE SO ARRANGED AS TO SUPPORT THE TRENCH WALLS AND EXISTING STRUCTURES AND UTILITIES. SHEETING LEFT IN PLACE SHALL BE CUT OFF NOT LESS THAN 18 INCHES BELOW GROUND SURFACE.

SHEETING AND BRACING NOT NOTED TO BE LEFT IN PLACE MAY BE REMOVED AT THE DISCRETION AND RESPONSIBILITY OF THE CONTRACTOR AFTER BACKFILL HAS BEEN PLACED AND COMPACTED TO A LEVEL AT LEAST TWO (2) FEET ABOVE THE TOP OF THE PIPE. IN NO CASE SHALL SHEETING BE PULLED IN INCREMENTS EXCEEDING THREE (3) TO FOUR (4) FEET IN ORDER TO AVOID THE DANGER OF BREAKING THE PIPE DUE TO THE WEIGHT OF THE BACKFILL. UPON REMOVAL OF SHEETING AND BRACING, VOIDS LEFT DUE TO SUCH REMOVAL SHALL IMMEDIATELY BE FILLED AND THE BACKFILL RECOMPACTED.

WHERE IT IS NECESSARY TO DRIVE SHEETING BELOW THE CENTERLINE OF THE PIPE, IT SHALL BE DRIVEN BELOW THE BOTTOM OF THE PIPE AS DETERMINED BY THE CITY, AND THAT SHEETING BELOW A POINT TWO FEET ABOVE THE TOP OF THE PIPE SHALL BE LEFT IN PLACE.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.13 PIPE EMBEDMENT

THE BEDDING MATERIAL SHALL BE SHAPED TO CONFORM TO THE BOTTOM QUADRANT OF THE PIPE BARREL. THE CITY RESERVES THE PRIVILEGE OF ALTERING THE TYPE OF BEDDING MATERIAL AND REGULATING THE EXACT GRADING OF THE BEDDING MATERIAL DEPENDING UPON THE WATER CHARACTERISTICS OF THE TRENCH. AT LEAST THE MINIMUM OF BEDDING SHALL BE PROVIDED UNDER PIPE BELLS.

AFTER THE PIPE IS LAID, THE BEDDING MATERIAL SHALL BE SHOVEL PLACED AND TAMPED TO FILL ALL VOIDS. THE BEDDING MATERIAL SHALL BE PLACED IN SIX (6) INCH LAYERS. LOOSE MEASUREMENT, AND COMPACTED BY HAND OR MECHANICAL TAMPING TO SECURE A GOOD COMPACTION. ALL EMBEDMENT MATERIAL SHALL BE CAREFULLY PLACED AND TAMPED SO AS NOT TO DAMAGE OR DISPLACE THE JOINTS OR PIPE, AND NO MATERIAL SHALL BE DROPPED DIRECTLY ON THE PIPE. THE MATERIAL SHALL BE COMPACTED TO NOT LESS THAN 98% OF MAXIMUM DENSITY AS DETERMINED IN ACCORDANCE WITH ASTM D1557 (MODIFIED PROCTOR).

AN EXCEPTION SHALL BE MADE WHERE CONCRETE ENCASEMENT IS NOTED ON THE DRAWINGS. CONCRETE ENCASEMENT SHALL BE SQUARE IN CROSS SECTION, SHALL HAVE A MINIMUM THICKNESS OF SIX (6) INCHES AT PIPE BELLS, AND SHALL BE OF THE LENGTH AS SHOWN ON PLAN/PROFILE DRAWINGS OR AS REQUIRED. SEE FIGURE 4.17.1.

THIS SHALL INCLUDE THE MATERIALS AND CONSTRUCTION OF CONCRETE PIPE CRADLES TO SUPPORT THE NEW PIPES WHERE THEY CROSS OVER EXISTING PIPES IN THE LOCATIONS NOTED ON THE DRAWINGS. DAMAGE TO EXISTING PIPES RESULTING FROM THE CONTRACTOR'S OPERATIONS SHALL BE REPAIRED OR REPLACEMENTS MADE TO THE SATISFACTION OF THE CITY BY AND AT THE EXPENSE OF THE CONTRACTOR. SEE FIGURE 4.17.2.

IF THE MATERIAL FOUND AT THE SPECIFIED DEPTHS OF EXCAVATION BELOW THE ELEVATION OF THE OUTSIDE BOTTOM OF THE PIPE BARREL IS NOT SUITABLE TO PROVIDE ADEQUATE FOUNDATION FOR THE PIPE, A FURTHER DEPTH SHALL BE EXCAVATED AND FILLED WITH GRANULAR BEDDING MATERIAL APPROVED BY THE CITY.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.14 PIPE LAYING

PIPES SHALL BE LAID WITH THEIR FULL LENGTHS TRUE TO LINE AND GRADE WITH THE AID OF BATTERBOARDS, GRADE POLE AND GRADE STRING, OR OTHER METHOD APPROVED BY THE CITY, AND SHALL REST ON THE BEDDING MATERIAL PROVIDED. PIPE SLOPE SHALL BE AS DESIGNED AND APPROVED BY THE CITY OF HUDSON.

WHEN BATTERBOARDS ARE USED, NOT LESS THAN THREE, SET AT 25-FOOT INTERVALS, SHALL BE INSTALLED AND MAINTAINED IN PROPER POSITION AT ALL TIMES AS A CHECK ON THE ACCURACY OF THE GRADE LINE.

WHEN LASER BEAM EQUIPMENT IS USED, IT SHALL BE CHECKED A MINIMUM OF TWICE DAILY, ONCE IN THE A.M. AND ONCE IN THE P.M., IN THE PRESENCE OF THE CITY TO VERIFY THAT THE EQUIPMENT IS MAINTAINING THE ESTABLISHED LINE AND GRADE. IN ADDITION, WHEN TEMPERATURE AND OTHER ATMOSPHERIC CONDITIONS PREVENT THE LASER BEAM FROM MAINTAINING GRADE, THE CONTRACTOR SHALL PROVIDE ADDITIONAL VENTILATION THROUGH THE PIPELINE BY THE USE OF BLOWERS AS RECOMMENDED BY THE EQUIPMENT MANUFACTURER OR AS DIRECTED BY THE CITY.

REGARDLESS OF THE METHOD USED, THE CITY SHALL BE IMMEDIATELY NOTIFIED OF ANY MISALIGNMENT OF THE PIPE WHEN LAID IN ACCORDANCE WITH ESTABLISHED CUTS OR ELEVATIONS.

PIPES AND MANHOLES SHALL BE INSTALLED AT A MINIMUM TEN (10) FOOT HORIZONTAL DISTANCE FROM WATER MAINS, AND PIPES LAID AT A MINIMUM 18 INCHES VERTICAL DISTANCE FROM WATER MAINS AT THEIR CROSSING, BOTH AS MEASURED BETWEEN THE OUTSIDE OF THE PIPE WALLS. AT CROSSINGS, ONE FULL LENGTH OF PIPE SHALL BE INSTALLED SO BOTH JOINTS WILL BE AS FAR FROM THE MAIN AS POSSIBLE. IF NECESSARY, EXISTING WATER MAINS SHALL BE RELOCATED UNDER PROPOSED SEWERS. SEE FIGURE 4.18.1.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.15 BACKFILLING

BACKFILL SHALL INCLUDE THE MATERIAL PLACED ABOVE THE PIPE EMBEDMENT MATERIAL PREVIOUSLY SPECIFIED. NO HEAVY OR LARGE QUANTITIES OF BACKFILL MATERIAL SHALL BE PLACED OVER THE PIPE UNTIL BACKFILLING HAS PROGRESSED TO A DEPTH OF AT LEAST THREE (3) FEET OVER THE TOP OF THE PIPE BARREL. ALL BACKFILL MATERIAL SHALL BE CAREFULLY PLACED SO AS NOT TO DAMAGE THE JOINTS OR DISPLACE THE PIPE. BACKFILLING SHALL IMMEDIATELY FOLLOW TRENCHING AND PIPE LAYING OPERATIONS TO REDUCE THE POSSIBILITY OF DAMAGE TO PAVEMENTS AND UTILITIES.

TRENCHES WITHIN EXISTING AND PROPOSED STONED STREETS, ALLEYS, DRIVEWAYS, STONED PARKING AREAS AND CONCRETE OR BRICK SIDEWALKS SHALL BE BACKFILLED WITH GRANULAR MATERIAL. THE MATERIAL SHALL BE PLACED AND COMPACTED TO NOT LESS THAN 100% OF MAXIMUM DENSITY AS DETERMINED IN ACCORDANCE WITH ASTM D1557 (MODIFIED PROCTOR). CONTRACTOR SHALL PROVIDE A CERTIFIED PROCTOR TEST RESULT FROM LIMESTONE SUPPLIER WITH THE SHOP DRAWINGS, PRIOR TO STONE BEING DELIVERED TO THE PROJECT SITE.

WHERE SEWERS ARE INSTALLED ALONG AND ACROSS EXISTING AND PROPOSED PAVED OR STONED STREETS, ALLEYS, DRIVEWAYS AND PARKING AREAS, THE SPECIFIED COMPACTED GRANULAR MATERIAL SHALL ALSO BE PROVIDED FOR BACKFILLING ANY PORTION OF THE TRENCHES FALLING WITHIN THAT AREA BELOW A LINE DRAWN AT 45 DEGREES TO THE HORIZONTAL FROM THE SURFACE AT THE EDGE OF THE PAVEMENT OR BACK OF CURB AND ABOVE THE HORIZONTAL PLANE OF THE PIPE EMBEDMENT MATERIAL. SEE FIGURE 4.19.1.

FOR TRENCHES WITHIN EXISTING OR PROPOSED PAVED STREETS, ALLEYS, DRIVEWAYS AND PAVED PARKING AREAS A CONTROLLED DENSITY FILL (C.D.F.) SHALL BE PROVIDED OR BACKFILL AS APPROVED BY THE CITY. THE MIX SHALL BE PLACED IN A USABLE FLUID FORM AND IN UNIFORM VERTICAL LIFTS. DESIGN, FINISHING AND PROTECTION OF THE MATERIAL SHALL BE RECOMMENDED BY THE MANUFACTURER FOR THE APPLICATION. QUALITY CONTROL TEST PROCEDURES OF THE MANUFACTURER SHALL INCLUDE ASTM C138 - TEST FOR UNIT WEIGHT, AND ASTM C39 - TEST FOR COMPRESSIVE STRENGTH. NO COMPACTION IS REQUIRED FOR C.D.F.

TRENCHES WITHIN RAILROAD RIGHT-OF-WAY, EXCEPT FOR LONGITUDINAL OCCUPANCY, SHALL BE BACKFILLED WITH CRUSHED STONE. TRENCHES WHERE SEWERS ARE INSTALLED LONGITUDINAL TO THE RAILROAD TRACKS SHALL BE BACKFILLED PER RAILROAD REQUIREMENTS, LATEST REVISIONS. THE BACKFILL MATERIAL SHALL BE PLACED IN LOOSE SIX (6) INCH LIFTS AND COMPACTED TO AT LEAST 95% OF ITS MAXIMUM DENSITY WITH A MOISTURE CONTENT THAT IS NOT MORE THAN 1% GREATER THAN OR 2% LESS THAN THE OPTIMUM MOISTURE AS DETERMINED IN ACCORDANCE WITH CURRENT ASTM DESIGNATION D - 1557 (MODIFIED PROCTOR). WHEN THE BACKFILL MATERIAL IS WITHIN THREE FEET OF THE SUBGRADE ELEVATION (THE INTERFACE OF THE BALLAST AND THE SUBSOIL), A COMPACTION OF AT LEAST 98% WILL BE REQUIRED. COMPACTION TEST RESULTS CONFIRMING COMPLIANCE MUST BE PROVIDED TO RAILROAD COMPANY'S ENGINEER BY THE CONTRACTOR.

THE CITY MAY REQUIRE CONTRACTOR TO CHECK COMPACTION OF THE BACKFILL AT A LOCATION AND DEPTH DETERMINED BY THE CITY, AT ANY TIME AT NO COST TO CITY. WHERE TRENCHES ARE BACKFILLED WITH GRANULAR MATERIAL, THE CONTRACTOR SHALL REMOVE EXCESS EXCAVATED MATERIAL. ANY EXCESS EXCAVATED SPOIL SHALL BE REMOVED TO AN APPROVED DUMP SITE.

IN ALL PAVED STREETS AND HIGHWAYS, IMMEDIATELY UPON COMPLETION OF OTHER BACKFILLING OPERATIONS AND PRIOR TO THE END OF WORK FOR THAT DAY, A TEMPORARY PAVEMENT AS SPECIFIED IN SECTION 7 - ROADWAY SHALL BE PROVIDED AND SHALL REMAIN IN PLACE AND BE PROPERLY MAINTAINED UNTIL SUCH TIME AS THE PERMANENT PAVEMENTS ARE PLACED. FOR A PROJECT WITH MORE THAN ONE ROAD CROSSING PERMANENT PAVEMENTS SHALL BE PLACED WITHIN TWO WEEKS AFTER COMPLETION OF TESTS AND ACCEPTANCE OF EACH SECTION OF THE STORM SEWER. FOR A SINGLE ROAD CROSSING OR UTILITY REPAIR, PERMANENT PAVEMENTS SHALL BE PLACED WITHIN 48 HOURS AFTER ACCEPTANCE OF THE CROSSING OR REPAIR.

FOR BACKFILLING THE REMAINDER OF THE TRENCHES, AS MUCH OF THE EXCAVATED MATERIAL AS POSSIBLE SHALL BE REPLACED UNTIL BACKFILLING HAS PROGRESSED TO A DEPTH OF AT LEAST 3 FEET OVER THE TOP OF THE PIPE BARREL. THE MATERIAL SHALL BE FINELY DIVIDED FREE OF STONES THREE (3) INCHES OR GREATER IN ANY DIMENSION. NO BOULDERS, ORGANIC MATERIALS OR OTHER HARMFUL DEBRIS SHALL BE USED. THE MATERIAL SHALL BE PLACED IN SIX (6) INCH LAYERS, LOOSE MEASUREMENT, AND COMPACTED BY MECHANICAL TAMPING.

ALSO, IMMEDIATELY UPON COMPLETION OF OTHER BACKFILLING OPERATIONS AND PRIOR TO THE END OF WORK FOR THAT DAY, A TEMPORARY SIDEWALK SHALL BE PROVIDED, AND SHALL REMAIN IN PLACE AND BE PROPERLY MAINTAINED UNTIL SUCH TIME AS THE PERMANENT SIDEWALK IS PLACED. THE TEMPORARY SIDEWALK SHALL CONSIST OF A MINIMUM OF 1-1/2 INCHES OF THE SPECIFIED COMPACTED GRANULAR BACKFILL MATERIAL PLACED TO THE SAME WIDTH AS THE ORIGINAL SIDEWALK, AND SHALL BE FURNISHED, PLACED AND MAINTAINED BY AND AT THE EXPENSE OF THE CONTRACTOR. THE TEMPORARY SIDEWALK SHALL BE RESHAPED AND REGRADED PRIOR TO THE INSTALLATION OF PERMANENT SIDEWALK.

AFTER BACKFILLING, ALONG WEED OR UNSODDED AREAS THE MATERIAL SHALL BE GRADED TO CONFORM TO THE ORIGINAL GROUND PROFILE. IN LAWN AREAS AND IN FIELDS USED FOR FARMING, ALL TOPSOIL REMOVED AND STOCKPILED PRIOR TO TRENCHING SHALL BE REPLACED AND GRADED TO CONFORM TO THE ORIGINAL GROUND PROFILE. IN LAWNS AND OTHER AREAS WHERE GRASS EXISTS, AS DETERMINED BY THE OWNER OR THE CITY, THE AREA SHALL BE GRADED AND MADE READY FOR SEEDING AS SPECIFIED IN SECTION 1. IN LAWN AREAS, IF THE EXISTING REPLACED TOPSOIL DOES NOT PROVIDE THE REQUIRED FOUR (4) INCH MINIMUM DEPTH AS SPECIFIED IN SECTION 1, THE CONTRACTOR SHALL PROVIDE ADDITIONAL TOPSOIL AT HIS EXPENSE.

THE CONTRACTOR SHALL BE REQUIRED TO REGRADE AND RESHAPE ALL ROAD SHOULDERS AND ALL DITCHES OR SWALES FROM EXISTING HIGH POINTS TO EXISTING DRAINAGE STRUCTURES OR OTHER OUTLETS ALONG THE PROPOSED IMPROVEMENT. THE CONTRACTOR AND THE CITY SHALL MUTUALLY AGREE AND ESTABLISH ALL DITCH GRADES TO BE RESTORED PRIOR TO CONSTRUCTION. DITCHES, WHICH ARE RESHAPED, SHALL HAVE REASONABLE SIDE SLOPES. VERTICAL OR STEEP SLOPES WILL NOT BE PERMITTED.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.16 CONNECTIONS TO STRUCTURES AND PIPES

WHEN REQUIRED, NEW AND EXISTING SEWERS SHALL BE CONNECTED TO STRUCTURES THROUGH STUBS, WALL CASTINGS, WALL SLEEVES, ETC. PROVIDED FOR SAME OR A CORED OPENING SHALL BE MADE AT THE PROPER ELEVATION IN THE WALL OF THE STRUCTURE, THE PIPE INSERTED AND THE OPENING AROUND THE PIPE NEATLY AND PERMANENTLY CLOSED WITH A NON-SHRINKING AND NON-CORROSIVE GROUT. NO STRAIGHT-LINE SAW CUTTING AND/OR HAMMERING OF OPENINGS WILL BE ALLOWED. GROUT SHALL BE, FIVE STAR GROUT AS MANUFACTURED BY FIVE STAR PRODUCTS, INC.; SEALTIGHT 588-10K GROUT AS MANUFACTURED BY W.R. MEADOWS, INC.; SET GROUT AS MANUFACTURED BY MASTER BUILDERS; OR EQUAL. ALL CONNECTIONS SHALL BE WATERTIGHT. WHERE NECESSARY, THE BOTTOMS OF EXISTING STRUCTURES SHALL BE RESHAPED TO GIVE A SMOOTH FLOW IN ALL DIRECTIONS.

CONNECTIONS TO UNLIKE TYPES AND SIZES OF PIPE SHALL BE ACCOMPLISHED USING THE PROPER ADAPTER AND/OR CONNECTOR AS MANUFACTURED BY FERNCO, INC.

(ORD.18-104. PASSED 8-21-18.)

(ORE.

4.17 ROCK EXCAVATION

A. GENERAL - THE TERM "ROCK EXCAVATION" SHALL INCLUDE THE REMOVAL OF SUCH MATERIAL AS CANNOT BE BROKEN AND REMOVED BY ORDINARY EXCAVATING EQUIPMENT. THE DEFINITION OF ORDINARY EXCAVATING EQUIPMENT DOES NOT INCLUDE RIPPERS OR POWER OPERATED JACK HAMMERS. DISINTEGRATED, WEATHERED, ROTTEN AND LOOSE ROCK PARTICLES CAPABLE OF REMOVAL BY ORDINARY METHODS ARE NOT INCLUDED WITHIN THE SCOPE OF ROCK EXCAVATION.

B. EXCAVATION - EXCAVATION SHALL BE CARRIED TO A SUFFICIENT DEPTH TO PROVIDE FOR A CUSHIONING LAYER OF BEDDING MATERIAL AS PREVIOUSLY SPECIFIED IN ITEM 4.12. WIDTH OF TRENCH SHALL BE NOT MORE THAN PREVIOUSLY SPECIFIED FOR THE RESPECTIVE TYPE OF PIPE.

EXCAVATION FOR STRUCTURES SHALL EXTEND TO A PLANE FOUR (4) INCHES BELOW THE UNDERSIDE OF THE CONCRETE FOUNDATIONS AND BE CONFINED TO LIMITS TWO FEET BEYOND THE OUTSIDE OF SUCH FOUNDATIONS.

C. DISPOSAL OF ROCK - EXCEPT UNDER SPECIAL PERMISSION FROM THE ENGINEER, ROCK REMOVED BY EXCAVATION SHALL NOT BE USED FOR BACKFILL, BUT SHALL BE DISPOSED OF BY THE CONTRACTOR OFF THE PROJECT SITE. NECESSARY BEDDING AND BACKFILL FOR TRENCHES AND OTHER EXCAVATIONS IN ROCK EXCAVATION SHALL BE APPROVED BY THE CITY.

D. METHOD - WHERE ROCK IS ENCOUNTERED WHICH CANNOT BE REMOVED BY ORDINARY EXCAVATING METHODS, ROCK EXCAVATION, UNLESS OTHERWISE SPECIFIED, MAY BE ACCOMPLISHED BY THE USE OF EXPLOSIVES, WITH THE APPROVAL OF THE CITY MANAGER AND SUBJECT TO COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL LAWS AND THE FOLLOWING REQUIREMENTS:

1) ALL REQUIRED PERMITS SHALL BE SECURED BY THE CONTRACTOR WELL IN ADVANCE OF SUCH OPERATIONS.

2) THE TRANSPORTING, HANDLING AND FIRING OF EXPLOSIVES SHALL BE PERFORMED BY SOMEONE THOROUGHLY FAMILIAR, EXPERIENCED AND, IF APPLICABLE, LICENSED IN THIS TYPE OF WORK, PREFERABLY A REPRESENTATIVE OF THE MANUFACTURER OF THE EXPLOSIVES TO BE USED.

3) PRIOR TO REMOVING ROCK IN ANY AREA, THE TYPE OF EXPLOSIVES TO BE USED, THE NUMBER, DEPTH AND LOADING OF HOLES TO BE DETONATED AT ANY ONE TIME; AND ANY SPECIAL PRECAUTIONS TO BE OBSERVED SHALL BE DETERMINED AT A CONFERENCE BETWEEN REPRESENTATIVES OF THE OWNER, THE CITY, THE CONTRACTOR, THE CONTRACTORS INSURANCE COMPANY AND THE PERSON DIRECTLY RESPONSIBLE FOR DETONATION. THE PROCEDURE THEREAFTER FOLLOWED IN THAT AREA SHALL CONFORM TO THE DECISIONS REACHED; SUBJECT TO ANY MODIFICATIONS WHICH MAY BE REQUIRED BECAUSE OF UNSATISFACTORY OR UNSAFE RESULTS OR THE PROCEDURE AGREED UPON.

4) SUITABLE TIMBER MATS OR OTHER COVERINGS SHALL BE PROVIDED TO CONFINE ALL MATERIALS LIFTED BY BLASTING WITHIN THE LIMITS OF THE EXCAVATION.

5) ALL PUBLIC AND PRIVATE UTILITY COMPANIES HAVING FACILITIES IN THE VICINITY SHALL BE NOTIFIED BY THE CONTRACTOR OF THE LOCATION AND TIME OF CONTEMPLATED DETONATION IN SUFFICIENT TIME TO ALLOW THEM TO PROTECT THEIR FACILITIES. LIKEWISE, WHERE OPERATIONS ARE TO BE CARRIED ON IN ANY LOCATION WHERE TRAFFIC ON STREETS OR HIGHWAYS MAY BE AFFECTED, PROPER NOTICE SHALL BE GIVEN THE LOCAL POLICE DEPARTMENT.

6) FOR PURPOSE OF PROTECTING THE GENERAL PUBLIC, THE CONTRACTOR AND THE OWNER, THE UTMOST COOPERATION WILL BE REQUIRED BETWEEN THE CONTRACTOR AND ALL OTHER INTERESTED PARTIES. ALL SAFETY PRECAUTIONS SHALL BE STRICTLY ENFORCED.

7) SHOULD PERMIT LIMITATIONS OR THE NEARNESS OF EXISTING STRUCTURES AND UTILITIES PROHIBIT THE USE OF EXPLOSIVES, ROCK EXCAVATION SHALL BE PERFORMED BY AN APPROVED ALTERNATE METHOD.

8) SEISMOGRAPHIC MONITORING, PRE-BLASTING AND POST-BLASTING INSPECTIONS SHALL BE PERFORMED ON THOSE STRUCTURES NEARBY TO AVOID FRAUDULENT DAMAGE CLAIMS.

E. DAMAGE TO EXISTING FACILITIES - THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DAMAGE TO EXISTING STRUCTURES, PIPING, SEWERS, DRAINS, CABLES, CONDUITS, EQUIPMENT AND APPURTENANCES RESULTING FROM HIS ROCK EXCAVATION OPERATIONS, AND SHALL REPAIR SAME TO THE SATISFACTION OF THE OWNER AND THE CITY.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

III. TESTING

4.18 TESTING FOR DEFLECTION (STORM SEWERS)

ALL STORM SEWERS OF PVC PLASTIC PIPE OR POLYPROPYLENE PIPE SHALL BE TESTED FOR A MAXIMUM DEFLECTION OF 5% OF THE PIPE AVERAGE INSIDE DIAMETER NOT LESS THAN 30 DAYS AFTER FINAL FULL BACKFILL, HAS BEEN PLACED, AS DETERMINED BY THE CITY.

SUCH TESTS SHALL BE CONDUCTED WITH A REPRESENTATIVE OF THE ENGINEER PRESENT. ALL PIPES EXCEEDING A DEFLECTION OF 5% OF THE AVERAGE INSIDE DIAMETER SHALL BE REPAIRED OR REPLACED AND THEN RETESTED UNTIL SATISFACTORY TEST RESULTS ARE OBTAINED. THE CONTRACTOR SHALL PAY ALL COSTS FOR THE TESTS.

THE TESTS SHALL BE CONDUCTED USING ELECTRONIC EQUIPMENT SPECIFICALLY DESIGNED FOR MEASURING AND RECORDING DEFLECTION IN FLEXIBLE PIPE OR BY THE USE OF AN APPROVED DEFLECTION PROBE, HAVING A DIAMETER EQUAL TO 95% OF THE AVERAGE INSIDE DIAMETER OF THE PIPE BEING TESTED, PULLED THROUGH THE SEWER LINE. IF THE DEFLECTION PROBE IS USED, TEST SHALL BE PERFORMED WITHOUT MECHANICAL PULLING DEVICES, AND A PROVING RING, HAVING AN I.D. EQUAL TO THE O.D. OF THE PROBE, SHALL BE AVAILABLE AT THE TIME THE PROBE IS USED TO VERIFY THAT THE PROBE HAS THE PROPER DIAMETER BY INSERTING THE PROBE INTO THE RING.

THE DEFLECTION PROBE SHALL BE AS AVAILABLE FROM WORTCO, INC.; BURKE CONCRETE ACCESSORIES, INC.; OR EQUAL, AND SHALL BE DESIGNED SPECIFICALLY FOR TESTING THE DEFLECTION OF THE TYPE AND SIZE OF PIPE SUBJECT TO TEST. THE PROBE SHALL INCORPORATE AN ODD NUMBER (NO LESS THAN 9) OF 1/2" X 3/16" BAR STOCK RUNNERS EQUALLY SPACED ON EDGE AROUND AND WELDED TO THE CIRCUMFERENCE OF TWO MINIMUM 1/4 INCH THICK CIRCULAR STEEL PLATES. THE DIAMETER OF THE PROBE FOR THE TYPE AND NOMINAL SIZE OF THE PIPE TO BE TESTED SHALL BE EQUAL TO 95% OF THE AVERAGE INSIDE DIAMETER OF THE RESPECTIVE PIPE AS SPECIFICALLY GIVEN OR DETERMINED BY THE ENGINEER FROM INFORMATION GIVEN IN THE APPROPRIATE ASTM STANDARD FOR THE PIPE.

THE DISTANCE BETWEEN PLATES, OUT-TO-OUT, SHALL NOT BE LESS THAN TWO (2) INCHES SMALLER THAN THE NOMINAL DIAMETER OF THE PIPE TO BE TESTED. THE RUNNERS SHALL EXTEND APPROXIMATELY 1-1/2 INCHES BEYOND EACH PLATE, BEING BENT INWARD FOR THIS DISTANCE AT APPROXIMATELY 30°. A CONTINUOUS 3/4 INCH THREADED ROD SHALL BE PROVIDED THROUGH THE CENTER OF THE PLATES, HAVING A HEX NUT DRAWN TIGHT AGAINST THE INSIDE FACE OF EACH PLATE, AND EXTENDING EACH SIDE AS REQUIRED FOR PROVIDING A 3/4 INCH FERRULE LOOP INSERT OR SIMILAR PIECE FOR ATTACHING THE PULLING MEDIUM.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.19 TESTING FOR LEAKAGE (STORM SEWERS)

A. GENERAL - THE CONTRACTOR SHALL INCLUDE LABOR AND MATERIALS, INCLUDING ANY WATER AND ALL EQUIPMENT, NECESSARY TO COMPLETE THE LEAKAGE TESTS SPECIFIED HEREIN. SUCH TESTS SHALL BE CONDUCTED AFTER TESTING FOR DEFLECTION IS COMPLETE, WHERE APPLICABLE, AND WITH A REPRESENTATIVE OF THE CITY PRESENT, AND HIS JUDGMENT SHALL BE FINAL AS TO THE ACCEPTANCE OF ALL TESTS. LEAKAGE TESTS SHALL BE CONDUCTED ON EACH PIPE SECTION AND MANHOLE.

EACH SECTION OF PIPE SHALL BE TESTED FOR OBSTRUCTIONS PRIOR TO VISUAL TESTING FOR LEAKAGE. EITHER MANDRELS, SOLID CYLINDERS, OR BALLS WITH DIAMETERS OF 95% OF THE PIPE DIAMETER MAY BE USED TO TEST FOR OBSTRUCTIONS. ALL OBSTRUCTIONS SHALL BE REMOVED.

ALL VISIBLE LEAKAGE IN SEWERS AND MANHOLES SHALL BE REPAIRED.

ALL PLUGS USED DURING LEAKAGE TESTS SHALL BE OF A LENGTH AT LEAST EQUAL TO THE DIAMETER OF THE PIPE BEING TESTED TO ASSURE A WATERTIGHT SEAL. PNEUMATIC PLUGS FOR AIR TESTING SHALL BE ABLE TO RESIST INTERNAL TEST PRESSURES WITHOUT REQUIRING EXTERNAL BLOCKING.

B. MANHOLES - EACH MANHOLE SHALL BE TESTED AFTER ASSEMBLY AND AFTER ALL LIFT HOLES HAVE BEEN PLUGGED WITH AN APPROVED NON-SHRINK GROUT, AND, AT THE OPTION OF THE CONTRACTOR, BEFORE OR AFTER BACKFILLING IS COMPLETED.

TESTING SHALL BE BY DRAWING A VACUUM ON THE MANHOLE USING EQUIPMENT SPECIFICALLY DESIGNED FOR SUCH TESTING. ALL PIPES ENTERING THE MANHOLE SHALL BE PLUGGED AND BRACED TO PREVENT BEING DRAWN INTO THE MANHOLE. A TEST HEAD WITH NECESSARY GAUGES AND CONNECTIONS SHALL BE PLACED AT THE INSIDE OF THE TOP OF THE CONE SECTION AND SEALED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS. A VACUUM OF TEN (10) INCHES OF MERCURY SHALL THEN BE DRAWN AND THE VACUUM PUMP SHUT OFF. WITH VALVES CLOSED, THE TIME SHALL BE MEASURED FOR THE VACUUM TO DROP TO NINE (9) INCHES. THE TEST SHALL BE SUCCESSFUL IF THE TIME MEASURED MEETS OR EXCEEDS THE VALUES INDICATED IN THE FOLLOWING TABLE:

MINIMUM TEST TIMES IN SECONDSMANHOLE DEPTHMANHOLE DIAMETER48"60"72"MINIMUM TEST TIMES IN SECONDSMANHOLE DEPTHMANHOLE DIAMETER48"60"72"8"20283310"25334112"30394914"35465716"40526518"45597320"506598122"55728924"59789728"648510528"699111330"7498121

IF THE TEST IS UNSUCCESSFUL, NECESSARY REPAIRS SHALL BE MADE AND RETESTING SHALL PROCEED UNTIL A SATISFACTORY TEST IS OBTAINED.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.20 TELEVISION INSPECTION (STORM SEWERS)

UPON COMPLETION OF LEAKAGE TESTING, SEWERS SHALL BE TELEVISED IN THE PRESENCE OF THE CITY. CLOSED-CIRCUIT TELEVISION INSPECTION SHALL BE PERFORMED FOR ALL NEW MAIN LINE SEWERS. THE CITY SHALL HAVE ACCESS TO VIEW MONITOR AT ALL TIMES, AND SHALL APPROVE PICTURE QUALITY AND DEFINITION.

VIDEO EQUIPMENT FOR TESTING SHALL PRODUCE DVD FORMAT VIDEO DISCS COLOR VIDEO PICTURE AND INCLUDE TWO AUDIO TRACKS. A MOBILE STUDIO FOR ABOVE GROUND CONTROL AND ADJUSTMENT OF EQUIPMENT AND VIEWING THE MONITOR SHALL BE USED, AND SHALL ACCOMMODATE A MINIMUM OF FOUR PEOPLE. THE CAMERA SHALL BE DESIGNED SPECIFICALLY FOR SUCH INSPECTIONS; SHALL BE OPERATIVE IN 100% HUMIDITY CONDITIONS; SHALL HAVE LIGHTING SUITABLE TO ALLOW A CLEAR PICTURE FOR ENTIRE PIPE PERIPHERY AND, SHALL HAVE METERING DEVICE SO LOCATION OF CAMERA AT POINT OF OBSERVATION IS KNOWN AT ALL TIMES.

DURING CLOSED-CIRCUIT TELEVISION INSPECTION, LOCATION OF LEAKAGE, DAMAGE, OBSTRUCTIONS, OR OTHER FAULTS DISCOVERED AND SERVICE CONNECTIONS SHALL BE REFERENCED FROM A STRUCTURE OR TERMINUS AND APPEAR ON THE TAPE AND IN THE REPORT.

DURING VIDEO INSPECTION, ANY LEAKAGE, DAMAGES OR OTHER FAULTS DISCOVERED SHALL BE CORRECTED TO THE SATISFACTION OF THE CITY. AFTER COMPLETION OF REPAIR WORK OR SUBSEQUENT CLEANING OF THE SEWERS, THE SEWERS SHALL BE SUBJECT TO THE CLOSED-CIRCUIT TELEVISION INSPECTION AGAIN TO DOCUMENT THE REPAIRS AND/OR CORRECTIVE MEASURES TAKEN; AND THAT THESE CORRECTIVE MEASURES HAVE ACHIEVED THE RESULTS DESIRED. ALL SUBSEQUENT INSPECTIONS SHALL BE AT THE CONTRACTOR'S COST.

THE CONTRACTOR INSTALLING THE SEWERS SHALL PROVIDE ONE SET OF DVD FORMAT VIDEO FOR EACH INSPECTION ATTEMPT AND ONE COPY OF THE REPORT TO THE CITY. THE REPORT SHALL INCLUDE THE RESULTS OF THE VIDEO INSPECTION AND ACTIONS TAKEN TO CORRECT LEAKAGE, DAMAGE AND OTHER FAULTS DISCOVERED AND REMOVAL OF ANY OBSTRUCTIONS.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)

4.21 COMPLETION OF TESTS

A. WHEN THE TESTS ON THE SEWER HAVE BEEN SUCCESSFULLY COMPLETED, THE LINE SHALL BE FLUSHED AND CLEANED BEFORE IT IS ACCEPTED.

(ORD.18-104. PASSED 8-21-18; ORD. 24-151. PASSED 1-7-25.)



CESO  
WWW.CESONINC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY

CHAPEL

750 W. STREETSBOBO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID Description Date

© 2025 CESO, INC.

Project Number: 765295

Scale: AS SHOWN

Drawn By: KAN

Checked By: JMS

Date: 5/22/2025





Issue: PERMIT SET

Drawing Title:

STORM DETAILS

C8.5

C:\D:\ACCDetail\CESO\CCCC - Hudson - Civil Master Plan Study\Project Files\CESO\CCCC-CIVIL\PLAN\LOT\Major Site Plans\765295\_ CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**

750 W. STREETSBO RO STREET  
HUDSON, OH 44236

Revisions / Submissions		
ID	Description	Date

© 2025 CESO, INC.  
Project Number: 765295  
Scale: AS SHOWN  
Drawn By: KAN  
Checked By: JMS  
Date: 5/22/2025  
Issue: PERMIT SET

Drawing Title:  
**STORM DETAILS**

**C8.6**



C:\DC\ACD\at\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\03-CIVIL\PLAN\LOT\Major Site Plans\765295\_CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel

DEPARTMENT OF SANITARY SEWER SERVICES - SUMMIT COUNTY  
STANDARD CONSTRUCTION DRAWINGS AND PROCEDURES

GENERAL NOTES

PERMISSION TO CONSTRUCT SANITARY SEWERS IS GRANTED BY THE STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY ( O.E.P.A. ), THE COUNTY OF SUMMIT DEPARTMENT OF SANITARY SEWER SERVICES (D.S.S.S.) AND THE COUNCIL OF THE COUNTY OF SUMMIT WHEN APPROPRIATE. THE D.S.S.S. HAS AUTHORITY TO STOP ANY SANITARY SEWER CONSTRUCTION NOT IN COMPLIANCE WITH CURRENT REGULATIONS AND STANDARDS.

1. THE ATTACHED STANDARD CONSTRUCTION DRAWINGS ARE DERIVED FROM "RECOMMENDED STANDARDS FOR WASTEWATER FACILITIES", LATEST EDITION (KNOWN AS "THE TEN STATES STANDARDS") AS ESTABLISHED BY THE GREAT LAKES UPPER MISSISSIPPI RIVER BOARD OF STATE AND PROVINCIAL PUBLIC HEALTH AND ENVIRONMENTAL MANAGERS (GLUMRB) AND AS AMENDED BY THE SUMMIT COUNTY COMMISSIONERS RESOLUTION NO. 294-75. IF NO APPLICABLE STANDARD IS ATTACHED, THE TEN STATES STANDARDS WILL APPLY.

2. ALL WORK SHALL BE DIRECTED BY A COMPETENT ENGINEER, LICENSED BY THE STATE OF OHIO.  
3. ALL CONSTRUCTION SHALL BE INSPECTED BY THE D.S.S.S. AND THE COST OF THAT INSPECTION SHALL BE BORNE BY THE PROJECT.

4. NO SEWER CONSTRUCTION SHALL OCCUR PRIOR TO THE PROJECT PLAN AND SPECIFICATION APPROVAL BY THE D.S.S.S., THE O.E.P.A. AND LOCAL REGULATORY AGENCIES AS APPLICABLE.

5. ANY AND ALL PLAN REVISIONS SHALL BE APPROVED BY THE D.S.S.S. PRIOR TO IMPLEMENTATION.

6. ALL SEWERS 6 THROUGH 12 INCHES IN DIAMETER SHALL BE TESTED BY THE LOW PRESSURE AIR TEST METHOD AS OUTLINED IN THE APPLICABLE ASTM STANDARDS. ALL SEWERS 15 INCHES AND GREATER DIAMETER SHALL BE TESTED BY THE MOST PRACTICAL METHOD. ACCEPTABLE TEST METHODS ARE:

- LOW PRESSURE AIR TEST
- INFILTRATION TEST
- EXFILTRATION TEST

THE TEST METHOD SELECTION SHALL BE BASED ON THE EXISTING GROUND WATER CONDITIONS AND OTHER FACTS PERTINENT TO THE PARTICULAR PROJECT AND SHALL BE APPROVED BY THE ENGINEER.

7. SEWERS SHALL BE INSPECTED IN ACCORDANCE WITH THE STANDARD FOR "INTERNAL VIDEO INSPECTION OF SANITARY SEWERS" AND THE COST OF THAT INSPECTION SHALL BE BORNE BY THE PROJECT.

a. NO "PERMIT TO CONNECT" TO THE PROJECT SHALL BE ISSUED PRIOR TO THE APPROVAL BY D.S.S.S. OF ALL PROJECT WORK, DOCUMENTATION, TESTING, INSPECTION AND MEASUREMENT.

9. NO FOOTER DRAINS, DOWN SPOUTS, SUMP PUMPS OR OTHER CLEAN WATER SOURCES SHALL BE CONNECTED TO THE SANITARY SEWER AS PROHIBITED BY SUMMIT COUNTY ORDINANCE NO. 85-656, AS APPROVED OCTOBER 08, 1985.

10. DEFLECTION TEST:

DEFLECTION TESTS SHALL BE PERFORMED ON ALL FLEXIBLE PIPE, AND SHALL BE CONDUCTED AFTER THE FINAL BACKFILL HAS BEEN IN PLACE AT LEAST 30 DAYS TO PERMIT STABILIZATION OF THE SOIL-PIPE SYSTEM, AS DIRECTED BY THE SUMMIT COUNTY DEPARTMENT OF SANITARY SEWER SERVICES (DSSS). DEFLECTION TESTS SHALL BE PERFORMED IN THE PRESENCE OF AND APPROVED BY THE DSSS. DEFLECTION TESTS SHALL BE PERFORMED WITHOUT MECHANICAL PULLING DEVICES.

NO PIPE SHALL EXCEED A DEFLECTION OF 5 PERCENT OF THE INSIDE DIAMETER. IF THE DEFLECTION EXCEEDS 5 PERCENT THE PIPE SHALL BE EXCAVATED, CORRECTED, AND/OR REPLACED AS NECESSARY. REPLACEMENT AND CORRECTION OF THE PIPE SHALL BE ACCOMPLISHED IN ACCORDANCE WITH THE COUNTY'S STANDARD SPECIFICATIONS AND DETAILS AT THE CONTRACTOR'S EXPENSE.

THE RIGID BALL OR MANDREL USED FOR THE DEFLECTION TEST SHALL HAVE A DIAMETER NOT LESS THAN 95 PERCENT OF THE BASE INSIDE DIAMETER OR AVERAGE INSIDE DIAMETER OF THE PIPE, DEPENDING UPON WHICH IS SPECIFIED IN THE ASTM SPECIFICATION (INCLUDING APPENDICES) TO WHICH THE PIPE IS MANUFACTURED. THE DEVICE USED FOR THE DEFLECTION TEST SHALL BE OF MATERIAL AND CONSTRUCTION APPROPRIATE FOR USE WITH THE PIPE BEING TESTED.

ACCEPTABLE MATERIALS AND SUPPLIERS

ASTM AND AWWA SPECIFICATION NUMBERS REFER TO THE LATEST VERSION THEREOF. OTHER STANDARDS SHALL APPLY BY REFERENCE ALTHOUGH NOT SPECIFICALLY STATED HEREIN.

- CONCRETE PIPE - ASTM C-76, C-443, C-507, C-655
- HANSON PIPE AND PRECAST COMPANY
- INDEPENDENT CONCRETE PIPE COMPANY
- SUPERIOR CONCRETE PIPE COMPANY

- DUCTILE IRON PIPE AND FITTINGS - AWWA C-110, C-115, C-116, C-151; ASTM A-746
- AMERICAN CAST IRON PIPE COMPANY
- CLOW CORPORATION
- U.S. PIPE COMPANY

- PVC PIPE AND FITTINGS - ASTM D-3034, F-679, F-789, F-794, F-949
- CERTAIN-TEED PRODUCTS CORPORATION
- HARCO FITTINGS
- HERITAGE PLASTICS PIPE
- JM EAGLE
- PLASTIC TRENDS

- TRUSS PIPE - ASTM D-2680
- CONTECH

- VITRIFIED CLAY PIPE - ASTM C-301, C-425, C-700
- LOGAN CLAY PIPE
- UNITED PIPE SUPPLY
- SUPERIOR CLAY PRODUCTS

- PRECAST CONCRETE MANHOLES - ASTM C-478, C-497, C-923
- USA PRECAST CONCRETE
- MACK INDUSTRIES - VALLEY CITY, OHIO
- MICHELBRINK PRECAST CONCRETE

- MANHOLE FRAMES AND COVERS - ASTM A-48
- EJ COMPANY FKA
- NEENAH FOUNDRY

- FLEXIBLE PIPE ENTRIES - ASTM C-923
- KOR - N - SEAL
- A - LOK CORP

- INTERNAL VIDEO INSPECTION
- DYNAMERICAN
- GREAT LAKES
- LAKE COUNTY SEWER
- UNITED SURVEY, INCORPORATED

- PRESSURE PIPE & FITTINGS - ASTM D-1785, D-2241, AWWA C-900, C-905, C-909
- JM EAGLE
- NATIONAL PIPE & PLASTIC

- PE PIPE AND FITTINGS - ASTM D-1248, D-3350, F-714, F-2736, AWWA C-906
- ADVANCED DRAINAGE SYSTEMS
- ISCO INDUSTRIES
- NATIONAL PIPE & PLASTIC

- PUMPS
- FLYGT
- HYDRAMATIC
- MYERS
- ESSCO

INTERNAL VISUAL INSPECTION POLICY AND PROCEDURES

GENERAL

A. ALL GRAVITY SANITARY SEWER EXTENSIONS, REPAIRS AND REPLACEMENTS, 8 INCHES AND LARGER IN DIAMETER, SHALL BE SUBJECT TO AN INTERNAL VISUAL INSPECTION AFTER THE COMPLETION OF CONSTRUCTION. THE INTERNAL VISUAL INSPECTION SHALL DOCUMENT THE SEWER CONDITION AND CONSIST OF AN AUDIO-VISUAL RECORDING AND WRITTEN REPORT. THE RECORDING AND REPORT SHALL BE SUBMITTED BY THE INTERNAL INSPECTION CONTRACTOR DIRECTLY TO THE DEPARTMENT OF SANITARY SEWER SERVICES FOR REVIEW, APPROVAL AND PERMANENT RECORD. SUBMITTALS FROM DEVELOPERS, ENGINEERS OR ANY OTHER CONTRACTOR ASSOCIATED WITH THE SEWER INSTALLATION SHALL BE REJECTED.

B. THE CONDITION OF A SEWER SYSTEM SHALL BE PROVEN SATISFACTORY BY THE INTERNAL INSPECTION, AS WELL AS OTHER TESTS REQUIRED BY DSSS AS STATED IN THE GENERAL NOTES, PRIOR TO ITS PLACEMENT INTO SERVICE.  
C. IT IS SUGGESTED THAT THE ENTIRE NEW SEWER SYSTEM BE THOROUGHLY CLEANED BY JETTING OR OTHER APPROPRIATE METHOD IMMEDIATELY PRIOR TO THE INSPECTION. SHOULD ANY AMOUNT OF MUD, WATER, DEBRIS, FOREIGN MATERIAL, IDENTIFIABLE OR OTHERWISE, OR OTHER OBSTRUCTIONS TO OR THE VIEWING OF THE SEWER BE FOUND, THE SYSTEM MUST BE RE-CLEANED AND RE-INSPECTED. THE PROJECT INSPECTOR SUPERVISOR SHALL MAKE THE DETERMINATION OF THE SEWER CONDITION, THE NECESSITY OF REPAIR OR REPLACEMENT OF THE SEWER AND THE NECESSITY OF ADDITIONAL INTERNAL INSPECTIONS.

D. UNDER NORMAL CIRCUMSTANCES A DSSS PROJECT INSPECTOR NEED NOT BE PRESENT FOR SEWER CLEANING OR INTERNAL INSPECTION. HOWEVER, THE DSSS PROJECT INSPECTOR SUPERVISOR MUST BE NOTIFIED OF THE INTENT TO PERFORM THE INSPECTION PRIOR TO 9:00 A.M. ON THE DAY PRECEDING THE ANTICIPATED INSPECTION.  
E. ALL LINES, STRINGS, ROPES, PLUGS AND PARAPHERNALIA NECESSARY FOR THE PERFORMANCE OF THE INTERNAL VISUAL INSPECTION SHALL BE REMOVED FROM THE SEWER SYSTEM. ANY DAMAGE TO THE NEW OR EXISTING SEWERS, ANY LOSS SUFFERED BY A COUNTY SEWER CUSTOMER AND ANY OTHER INCIDENTAL DAMAGES RESULTING FROM THE INTERNAL INSPECTION OR ITS PARAPHERNALIA SHALL BE REMEDIED BY THE INTERNAL INSPECTION CONTRACTOR.

F. ALL COSTS OF THE INTERNAL INSPECTION, RE-INSPECTION, REPAIRING, CLEANING, ETC. SHALL BE PAID BY THE SEWER INSTALLATION CONTRACTOR PRIOR TO THE SEWER SYSTEM ACCEPTANCE FOR OWNERSHIP.

G. ALL INTERNAL INSPECTION SHALL BE DONE BY PERSONS OR FIRMS QUALIFIED AND APPROVED BY DSSS. INTERIOR WORK WILL BE REJECTED. MULTIPLE REJECTIONS WILL BE CAUSE FOR THE SUSPENSION OF ACCEPTANCE BY DSSS OF THE FIRMS WORK UNTIL THE CORRECTION OF THE DEFICIENCIES HAS BEEN PROVEN.

H. THE USE OF AIR, WHETHER PRESSURIZED OR VACUUM, TO REMOVE RESIDUAL WATER OR DEBRIS FROM THE SEWER CLEANING OPERATION IS NOT ACCEPTABLE.  
I. VIDEO RECORDING  
A. THE VISUAL RECORDING SHALL BE IN COLOR SHOWING CONTINUOUS COVERAGE OF THE SANITARY SEWER FROM ONE MANHOLE TO THE NEXT MANHOLE. THE COLOR SHALL BE A GOOD RENDITION OF THE SEWER INSTALLED IN THE OPINION OF DSSS.

B. THE RECORDING SHALL BE IN GOOD FOCUS AND HAVE ADEQUATE BUT NOT EXCESSIVE LIGHTING. THE LIGHT INTENSITY SHALL BE ADJUSTED TO ASSURE A QUALITY VIEWING OF THE PIPE SURFACE AND OBSERVATION OF CHANGES IN COLOR AND MATERIAL OF THE SURFACE. THIS SECTION DOES NOT REPRESENT APPROVAL OF THE USE OF DIFFERENT COLOR PIPE.

C. THE RECORDING SHALL BE FREE OF VIDEO "NOISE" IN THE FORM OF SNOW, STREAKS, MIGRATING COLOR OR FOCUS PATTERNS OR OTHER ELECTRONIC INTERFERENCE WHICH MAY HINDER OBSERVATION OF THE SANITARY SEWER.  
D. THE RECORDING OF ANY SEWER INSPECTION SHALL BE CONTINUOUS WITH NO BREAKS IN THE RECORDING OPERATION.

E. THE RECORDING SHALL SHOW THE ACTUAL LENGTH OF THE SEWER AT THE TOP CENTER OF THE IMAGE. OBSTRUCTION OF THE VIEW OF THE PIPE INVERT SHALL RESULT IN THE REJECTION OF THE RECORDINGS.

F. THE CAMERA DRAG LINE SHALL NOT OBSTRUCT THE VIEW OF THE FLOW LINE OF THE PIPE.  
G. THE VIEW SHALL BE CLEAR AND UNOBSTRUCTED BY DIRT, WATER, CONDENSATION OR VAPOR ON THE CAMERA LENS OR IN THE SEWER. SEE SECTION I-C FOR CLEANING AND RE-INSPECTION REQUIREMENTS.

H. THE VISUAL RECORDING SHALL BE AUGMENTED WITH AN AUDIO RECORDING OF THE INSPECTOR'S NARRATION CALLING OUT THE NOMENCLATURE OF THE SEWER SYSTEM, THE PIPE, MANHOLES, WYES, DEBRIS, MUD, WATER, BAD JOINTS, CRACK DAMAGE OR DEFORMED PIPE, JOINTS OR FITTINGS OR ANY OTHER OBSERVATION THAT MAY BE OF USE TO THE ASSESSMENT OF THE SEWER CONDITION. THE NARRATION SHALL BE CLEAR, CONCISE, AND LOUD ENOUGH TO OVERCOME ANY BACKGROUND NOISE FROM MACHINERY OR EQUIPMENT. THE NARRATION SHALL BEGIN WITH THE IDENTIFICATION OF THE PIPE. THE DISTANCE FROM THE DOWNSTREAM MANHOLE OF THE SEWER THEN THE IDENTIFICATION OF EACH AND EVERY OBSERVATION. THE CAMERA SHALL STOP AT EACH OBSERVATION AT THE DISCRETION OF THE RECORDING FIRM AS TO THE SIGNIFICANCE OF THE OBSERVATION AND ITS SEVERITY (OR THE INABILITY TO IDENTIFY) TO WARRANT REVERSING THE CAMERA ONE OR MORE TIMES TO PROVIDE A BETTER VIEW.

I. THE CAMERA VIEW SHALL BE LOOKING UPSTREAM SO THAT THE BUTT-ENDS OF THE PIPE SPIGOT WILL SHOW CLEARLY.  
J. THE CAMERA DIRECTION OF TRAVEL SHALL BE UPSTREAM.

K. THE VIDEO INSPECTION SEQUENCE SHALL BE FROM THE LOWEST MANHOLE TO THE FARTHEST UPSTREAM "TERMINAL" MANHOLE. EACH SUBSEQUENT BRANCH SHALL BE RECORDED FROM A MANHOLE ALREADY RECORDED TO THE TERMINAL MANHOLE OF THE BRANCH.  
L. AT EACH MANHOLE VIDEO ANNOTATION AND AUDIO NARRATION SHALL BE PRESENTED IDENTIFYING IN A UNIFORM MANNER THE FOLLOWING:

- BEGINNING MANHOLE NUMBER FROM THE APPROVED CONSTRUCTION DRAWING SET
- MANHOLE NUMBER TO WHICH THE CAMERA IS ABOUT TO APPROACH
- PROJECT NAME AND NUMBER
- STREET NAME
- DATE OF RECORDING
- SIZE AND MATERIAL OF PIPE

M. EACH PROJECT OR PHASE SHALL BE RECORDED SEPARATELY AND SUPPLIED TO DSSS ON SEPARATE MEDIA. RECORDINGS OF THE SAME PHASE SUBMITTED ON MULTIPLE PIECES OF MEDIA SHALL BE REJECTED UNLESS THE SIZE OF THE PROJECT PREVENTS ITS SUBMITTAL ON ONE SINGLE PIECE OF MEDIA.

N. EACH RECORDING SHALL BE MARKED WITH THE FOLLOWING:

- PROJECT NAME, PHASE AND NUMBER
- TOWNSHIP OR CITY IN WHICH THE IMPROVEMENT IS LOCATED
- DEVELOPER'S NAME
- INSTALLATION CONTRACTOR'S NAME
- INTERNAL INSPECTION COMPANY NAME, ADDRESS AND TELEPHONE NUMBER
- DATE OF SUBMITTAL AND DATE OF INSPECTION
- NUMBER OF PIECES OF MEDIA BEING SUBMITTED.

O. EACH RECORDING SUBMITTAL SHALL BE ACCOMPANIED WITH A REPORT DESCRIBING THE MEDIA AND ITS CONTENTS. SEE SECTION III REPORT FOR REQUIREMENTS.

6327)

III. REPORT

A. EACH RECORDING OF AN INTERNAL VISUAL INSPECTION SHALL BE SUBMITTED TO DSSS WITH AN ACCOMPANYING REPORT ON 8-1/2 BY 11 INCH PAPER WITH A COVER SHEET.

B. THE REPORT COVER SHEET FOR A RECORDING SUBMITTAL SHALL INCLUDE THE FOLLOWING:

- PROJECT NAME, PHASE AND NUMBER
- TOWNSHIP OR CITY IN WHICH THE IMPROVEMENT IS LOCATED
- DEVELOPER'S NAME
- INSTALLATION CONTRACTOR'S NAME
- INTERNAL INSPECTION COMPANY NAME, ADDRESS AND TELEPHONE NUMBER
- DATE OF SUBMITTAL AND DATE OF INSPECTION
- NUMBER OF PIECES OF MEDIA SUBMITTED.
- THE REPORT SHALL CONTAIN A MAP OF THE SUBDIVISION, STREETS OR EASEMENTS SHOWING THE GENERAL LAYOUT OF THE IMPROVEMENT. THE MAP SHALL INCLUDE NO LESS THAN:

- PROJECT NAME, PHASE AND NUMBER
- TOWNSHIP OR CITY IN WHICH THE IMPROVEMENT IS LOCATED
- DEVELOPER'S NAME
- STREET NAMES AND RIGHTS-OF-WAY IDENTIFICATIONS MATCHING THE NAMES ON THE APPROVED CONSTRUCTION DRAWING SET.
- NORTH ARROW
- SCALE
- MANHOLE NUMBERS OR NAMES FROM THE APPROVED CONSTRUCTION DRAWING SET
- INTENDED FLOW DIRECTIONAL ARROWS.

D. THE REPORT SHALL INCLUDE A SEPARATE SHEET FOR EACH SEWER (MANHOLE TO MANHOLE) CONTAINING DETAILED INFORMATION OF THAT SPECIFIC SEWER. EACH SHEET SHALL INCLUDE NO LESS THAN:

- INSPECTION COMPANY NAME
- PROJECT NAME, PHASE AND NUMBER
- TOWNSHIP OR CITY IN WHICH THE IMPROVEMENT IS LOCATED
- INTERNAL INSPECTION MEDIA
- DATE OF THE INTERNAL INSPECTION
- SIZE AND MATERIAL OF SEWER PIPE
- INSPECTION BEGINNING AND ENDING CONSTRUCTION STATION NUMBERS
- INSPECTION BEGINNING AND ENDING MANHOLE NAMES OR NUMBERS, FROM THE MAP AND THE APPROVED CONSTRUCTION DRAWING SET
- TOTAL LENGTH OF THE SEWER PIPE, IN FEET.

E. THE SPECIFIC INFORMATION TO BE INCLUDED FOR EACH SEWER SHALL BE IN A COLUMNAR TABULAR FORM INDICATING THE DISTANCE FROM THE PREVIOUS MANHOLE AND A DESCRIPTION OF EACH AND EVERY OBSERVATION. THESE COLUMNS SHALL BE MARKED TO INDICATE EACH AND EVERY OBSERVATION OF THE FOLLOWING CONDITIONS AT A MINIMUM:

- BEGINNING MANHOLE IDENTIFICATION NAME OR NUMBER
- SERVICE CONNECTION CALLED AS EITHER LEFT OR RIGHT OR BY "O'CLOCK" ONLY
- ABNORMAL PIPE JOINTS SUCH AS OPEN OR PARTIALLY OPEN, CRACKED, EXCESSIVE GLUE, GASKET EXPOSURE, LEAKING, DEFECTS
- ABNORMAL PIPE SUCH AS CRACKED, LEAKING, DAMAGED, DEFLECTED
- OBSTRUCTIONS SUCH AS MUD, STONES, LEAVES, PAPER, TOOLS
- STANDING WATER STARTING POINT
- STANDING WATER ENDING POINT
- SUBMERGENCE OF CAMERA
- BLOCKED PIPE PREVENTING CAMERA TRAVEL
- CHANGE OF PIPE MATERIAL OR COLOR
- WATER VAPOR (SEE SECTION II-G)
- OTHER EVENTS EITHER ORDINARY OR EXTRA-ORDINARY
- ENDING MANHOLE IDENTIFICATION NAME OR NUMBER.

INFILTRATION/EXFILTRATION TEST PROCEDURE

The Contractor shall conduct tests to determine the water tightness of the gravity sewer when completed. The tests shall be observed by the Engineer, but the Contractor shall furnish all labor, equipment and materials required in connection herewith.

It is agreed that the sewer shall be tested in sections, each section extending between two adjacent manholes or from the end of the sewer to nearest manhole. The Contractor may elect to use either an infiltration test, an exfiltration test, or the low pressure air test (see Sheet 6), with the approval of the Summit County Department of Sanitary Sewer Services.

A. Infiltration Test

Each section under test shall be covered with not less than two (2) feet of water above the top of the pipe at the highest point. The infiltration will be measured by means of weir located in the downstream manhole. The above head of two (2) feet shall be maintained for a period of not less than twenty-four (24) hours before the weir measurements are made.

B. Exfiltration Test

The sewer at the upstream side of the lower manhole and the upstream side of the upper manhole in each section shall be closed with a watertight bulkhead and the sewer filled with water until the water elevation in the upstream manhole is not less than two (2) feet above the top of the sewer pipe or two (2) feet above ground water elevation in the trench, whichever is higher. The exfiltration will be determined by measuring the amount of water required to maintain the above stated water elevation for a period of one (1) hour from the start of the test. The entire length of section to be tested shall be filled and maintained full of water for a period of approximately twenty-four (24) hours prior to the start of the test.

STANDARD DETAIL DWG. NO. 5A DEPARTMENT OF SANITARY SEWER SERVICES INFILTRATION EXFILTRATION TEST PROCEDURE APPROVED BY: DEPUTY DIRECTOR DATE 04/18/23
--

C. Allowable Infiltration or Exfiltration

The amount of infiltration or exfiltration shall not exceed 100 gallons per inch of pipe diameter per twenty-four (24) hours per mile of sewer in each and every section tested in accordance with the above.

D. Testing Requirements

In the event the allowable leakage rates are not met, the Contractor shall determine the location(s) where excess water is entering the sewer or leaving the sewer. The sewer and/or the manholes shall be repaired in manner satisfactory to the Summit County Department of Sanitary Sewer Services and retested until the leakage in the sewer is within the allowable limits.

The Contractor shall include in the price bid per lineal foot of sewer, the cost of all bulkheads, plugs, pipe stoppers, pumps, water, wyes, accessories, labor, delay and any other items of cost necessary for the performance and the completion of the required leakage tests and for the cost of the any repairs or adjustments which may be necessary to make the sewer conform to the required allowable leakage rates (for public projects only).

All leakage test shall be conducted under the supervision of the Summit County Department of Sanitary Sewer Services.

It is understood that each section, as above described, must be tested under the supervision of the Summit County Department of Sanitary Sewer Services for conformity to these requirements before such section or sections are included in any current or final estimate for payment to the Contractor, (for public projects only). It is further understood that, if the leakage does not come within the limits specified, the Contractor will be required to do such work as may be necessary in order to insure conformity with the extent of reconstructing the defective section or sections.

STANDARD DETAIL DWG. NO. 5B DEPARTMENT OF SANITARY SEWER SERVICES INFILTRATION EXFILTRATION TEST PROCEDURE APPROVED BY: DEPUTY DIRECTOR DATE 04/18/23
--

LOW PRESSURE AIR TEST PROCEDURE

In lieu of performing an infiltration or exfiltration test to determine the water tightness of the sewer, the Contractor may elect to perform a low pressure air test by the Ramseler procedure, as recommended by the National Clay Pipe Institute (NCPI).

Ramseler's method of conducting acceptance tests may be separated into two parts, one having to do with field procedure and the other having to do with the determination of pressure holding time.

Field Procedures

- Clean pipe to be tested by propelling snug fitting inflated rubber ball through the pipe with water, by jetting, or by other method approved by the Summit County Department of Sanitary Sewer Services.
- Plug all pipe outlets with suitable test plugs. Brace each plug securely.
- If the pipe to be tested is submerged in ground water, insert a pipe probe, by boring or jetting, into the backfill material adjacent to the center of the pipe, and determine the pressure in the probe when air passes slowly through it. This is the back pressure due to ground water submergence over the end of the probe. All gauge pressures in the test should be increased by this amount.

In ground water conditions, the standard air test is not reliable if adjustments are not made. The following standard should be followed where applicable. For every foot of water over the top of the sanitary sewer 0.4333 PSI should be added to our standard 4.0 PSI.

Where heavy ground water conditions prevail, contractor should be notified that he may air test at 4.0 PSI immediately after a run is completed (M.H. to M.H.), while his pumps are still operating, holding ground water below sanitary sewer), otherwise, 0.4333 PSI per foot of water above sanitary sewer will be added when air test is performed at a later date.

testing requirements before it is accepted by DSSS and/or, on public projects, is included in any current or final estimate for payment to the Contractor.

SANITARY FORCE MAIN TESTING AND PUMP STATIONS

Sanitary force mains shall be subject to post-construction leakage and pressure tests prior to acceptance by the DSSS. Tests shall conform to appropriate ASTM testing standards based upon system design pressures and operating conditions, and specific force main material type. Necessary repairs and replacements shall be the responsibility of the Contractor.

Site tests for emergency generators, where required, shall include a full rated load test of two (2) hours duration utilizing a resistive load bank furnished by the generator set manufacturer, and conducted by the generator set manufacturer's representative in accordance with the manufacturer's standard procedures and requirements.

STANDARD DETAIL DWG. NO. 6B DEPARTMENT OF SANITARY SEWER SERVICES LOW PRESSURE AIR TEST PROCEDURES AND FORCE MAIN TESTING APPROVED BY: DEPUTY DIRECTOR DATE 04/18/23
---



SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.







Project Number:	765295
Scale:	AS SHOWN
Drawn By:	KAN
Checked By:	JMS
Date:	5/22/2025
Issue:	PERMIT SET

Drawing Title:

SANITARY -  
DSSS-STANDARDS

C8.7





CESO  
WWW.CESOINC.COM

175 Monroeville West Ave., Suite 400  
Altoona, OH 44201  
Phone: 330.665.0660 Fax: 888.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBORO STREET  
HUDSON, OH 44236







Revisions / Submissions  
ID Description Date

© 2025 CESO, INC.  
Project Number: 765295  
Scale: AS SHOWN  
Drawn By: KAN  
Checked By: JMS  
Date: 5/22/2025  
Issue: PERMIT SET

Drawing Title:  
SANITARY DETAILS

C8.8





CESO  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBOBO STREET  
HUDSON, OH 44236

Revisions / Submissions  
ID Description Date

Project Number: 765295  
Scale: AS SHOWN  
Drawn By: KAN  
Checked By: JMS  
Date: 5/22/2025  
Issue: PERMIT SET

Drawing Title:  
SANITARY DETAILS



C8.9







C:\D:\ACD\Draws\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\CC-CIVIL\PLAN\LOT\Major Site Plans\765295\_CONSTRUCTION DETAILS.dwg - 5/21/2025 - Jake McDaniel



WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



5/22/2025

SOL HARRIS/DAY ARCHITECTURE

CHRIST COMMUNITY  
CHAPEL

750 W. STREETSBOBO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.


Project Number:	765295
Scale:	AS SHOWN
Drawn By:	KAN
Checked By:	JMS
Date:	5/22/2025
Issue:	PERMIT SET

Drawing Title:

FIELD DETAILS

C8.11

C:\D:\ACD\ora\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\CESO\06-LA\_PLANT\_CD\765295-PLANTING PLAN.dwg - 5/21/2025 - Jeff Lape



#### PLANT SCHEDULE

**SYMBOL**   **QTY**   **BOTANICAL / COMMON NAME**   **SIZE**   **MIN HT / SPR**   **SPACING**

#### TREES

	15	BETULA NIGRA RIVER BIRCH	2" CAL	12' HT	AS SHOWN
	21	CHIONANTHUS VIRGINICUS WHITE FRINGETREE	1.5" CAL	8-10' HT	AS SHOWN
	23	MAGNOLIA LILIFLORA 'JANE' JANE MAGNOLIA, MULTI-TRUNK	---	8-10' HT	AS SHOWN
	5	QUERCUS MACROCARPA BURR OAK	2" CAL	10'-12' HT	AS SHOWN

#### SHRUBS

	4	PRUNUS LAUROCERASUS 'OTTO LUYKEN' OTTO LUYKEN ENGLISH LAUREL	---	24" HT	4'-0" OC
	6	THUJA OCCIDENTALIS 'HETZ MIDGET' HETZ MIDGET ARBORVITAE	---	18" HT	3'-0" OC

#### GROUND COVERS

	36,666 SF	POA PRATENSIS KENTUCKY BLUEGRASS	SEED
	11,110 SF	POA PRATENSIS KENTUCKY BLUEGRASS	SOD

**MULCH**  
ALL SEED/ SOIL SHALL BE PLACED ON 4" OF TOP SOIL.  
CONTRACTOR TO PLACE A 4" DIAMETER MULCH RING AROUND ALL TREES IN LAWN.

#### LANDSCAPE REQUIREMENTS

**FRONT YARD & SETBACK LANDSCAPING REQUIREMENTS:**  
50' WIDE BUFFER YARD: (4) SMALL TREES & (2) LARGE OR MEDIUM TREES PER 100 LF

STREETSBORO RD (NORTH)- 483 LF


TREES REQUIRED: 30 TREES ( 10 LARGE OR MEDIUM TREES & 20 SMALL TREES)  
TREES PROPOSED: 30 ( 10 LARGE/ MEDIUM TREES & 20 SMALL TREES)

TEREX RD (WEST)- 283 LF

TREES REQUIRED: 18 TREES ( 6 LARGE OR MEDIUM TREES & 12 SMALL TREES)  
TREES PROPOSED: 32 TREES (10 LARGE/ MEDIUM TREES & 22 SMALL TREES)

#### LEGEND

	RIGHT-OF-WAY
	PROPERTY LINE
	SETBACK
	EASEMENT
	BUILDING
	CONCRETE CURB
	PAVEMENT/WALK
	SURVEYED TREE LINE TO REMAIN
	TREE LINE FROM AERIAL IMAGERY
	SIGN
	CATCH BASIN
	STORM MANHOLE
	SANITARY MANHOLE
	FIRE HYDRANT
	LIGHT POLE
	EXISTING TREE TO REMAIN
	EXISTING TREE TO BE REMOVED



FORTY- EIGHT (48) HOURS BEFORE DIGGING IS TO COMMENCE, THE CONTRACTORS SHALL NOTIFY THE FOLLOWING AGENCIES: OHIO UTILITIES PROTECTION SERVICE AT 811 OR 800-362-2764 AND ALL OTHER AGENCIES WHICH MIGHT HAVE UNDERGROUND UTILITIES INVOLVING THIS PROJECT AND ARE NONMEMBERS OF STATE UTILITIES PROTECTION SERVICE



**CESO**  
WWW.CESONC.COM

175 Montrose West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 330.208.4826



2025-05-22

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295

Scale: AS SHOWN

Drawn By: JC

Checked By: JL

Date: 5/16/2025

Issue: PERMIT SET


Drawing Title:

**LANDSCAPE PLAN-NORTH**

**L1.0**



C:\D:\ACD\ora\CESO\CCC - Hudson - Civil Master Plan Study\Project Files\ CESO\06-LA\_PLAN\_CD\76295-PLANTING PLAN.dwg - 5/21/2025 - Jeff Lape



**CESO**  
WWW.CESONC.COM

175 Monrovia West Ave., Suite 400  
Akron, OH 44321  
Phone: 330.665.0660 Fax: 888.208.4826



2025-05-22

SOL HARRIS/DAY ARCHITECTURE

**CHRIST COMMUNITY CHAPEL**

750 W. STREETSBORO STREET  
HUDSON, OH 44236

Revisions / Submissions

ID	Description	Date
----	-------------	------

© 2025 CESO, INC.

Project Number: 765295  
Scale: AS SHOWN  
Drawn By: JC  
Checked By: JL  
Date: 5/16/2025  
Issue: PERMIT SET


Drawing Title:  
**LANDSCAPE PLAN-SOUTH**

**L1.1**





BEING PART OF ORIGINAL LOTS 31 AND 41  
LOCATED IN HUDSON TOWNSHIP, SUMMIT COUNTY, OHIO

[illegible]









PROJECT No.	24.00
-------------	-------


**Planning Commission  
Submission  
05/09/25**

### DRAWING UPDATES

PANEL NOTES:

- ① FURNISH AND INSTALL ASTRONOMIC TIME CLOCK WITH 2 CHANNELS. 1 CHANNEL SHALL BE SPARE. TIME CLOCK SHALL CONTROL LIGHTING CONTACTOR "C-1" TORK #DWZ200B
- ② LIGHTING CONTACTOR "C-1". MULTI CONTACTOR IN NEMA 1 ENCLOSURE. 8 POLE (2 ARE SPARE) SQUARE D #LG80-120V  
ROUTE LIGHTING THROUGH CONTACTORS AS NOTED FOR CONTROL VIA CHANNEL 1 IN TIME CLOCK T/C-1
- ③ ROUTE CIRCUIT THROUGH LIGHTING CONTACTOR "C-1".

### KEY PLAY



## ELECTRICAL SITE LIGHTING PLAN

# 26-300





SCALE: 1" = 20'-0"



GRAPHIC SCALE: 1" = 20' - 0"

LIGHTING FIXTURE SCHEDULE							
TYPE AND SYMBOL	NO. OF LAMPS AND TYPE	FIXTURE WATTS	VOLTS	MANUFACTURER CATALOG NO.	MOUNTING	DESCRIPTION	ALTERNATE MANUFACTURERS
B1	LED 3500K 2075 LUMENS	31W	208	LUMINIS LUMIQUAD BOLLARD LQ427-L1L20-LD2-4000K- MVOLT-BLS1-BKT	CONCRETE BASE	4" X 4" BOLLARD, 42" HIGH. BLACK FINISH, TYPE 2 DISTRIBUTION, BLOCKOUT SHIELD ON BACK SIDE.	AS APPROVED BY ENGINEER



**FIXTURE BASE DETAIL  
TYPICAL FOR FIXTURE TYPE B1**

SCALE: NONE


\\Fs01\Shared\Active\24ch006-Christ Community Church in Hudson, OH - Reno & Addition\24ch006 26-300 Soccer field electrical plan - PH2.dwg [24x36] May 09, 2025 - 1:42pm

PROJECT NAME:

QUANTITY:

TYPE:

ORDERING CODE:

- 
- ① Heavy cast aluminum top cover.
  - ② Optical system assembly.
  - ③ 4x extruded aluminum struts.
  - ④ Cast aluminum driver housing.
  - ⑤ 4" (102mm) x 4" (102mm) extruded aluminum square body.
  - ⑥ Cast aluminum mounting base.



LQ427

## MATERIALS

Lumiquad bollard is made of corrosion resistant 356 aluminum alloy with a copper (CU) content of less than 0.1%.

## ELECTRICAL DRIVER

Driver is 0-10V dimming-ready (dims to 10%) with: 120-277 multi-volt compatibility (50-60Hz), operating temperatures of -40°C/-40°F to 55°C/131°F, output over voltage protection, output over current protection, output short circuit protection with auto-recovery.

## LED LIGHT ENGINE

Offered in 2700K/3000K/3500K/4000K CCT with 80 CRI. 70% LED lumen maintenance at 60,000 hours (L70/B50) based on IESNA LM-80-08 LED extrapolated life, calculated per IESNA TM-21-21. Optional true amber LED for turtle sensitive areas. Wavelengths: 585nm to 597nm.

## FINISH

Five-stage preparation process includes preheating of cast aluminum parts for air extraction. Polyester powder coating is applied through an electrostatic process, and oven cured for long term finish.

## CERTIFICATION

UL Certified to Canadian and U.S. safety standards. Certified for use in wet locations. Rated IP65. Photometric testing performed by an independent laboratory in accordance with IES LM-79-08 standards at 25°C. Actual performance may differ as a result of end-user environment and application.


## WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: <https://www.acuitybrands.com/support/warranty/terms-and-conditions>

## MOUNTING


Mounts with a set of 4 x 3/8"-16 x 3 3/4" lg. galvanized anchor bolts.

## MEASUREMENTS





## ORDERING CODE

*SERIES	*LIGHT OUTPUT	DISTRIBUTION	*CCT²	*VOLTAGE	FUSE
<div>LQ427</div> <div></div>	<u>Static White</u>	LD2    Type II	27K    2700K	120    120V	FS    Fuse
	L1L10    1039 lm/14w	LD5    Type V	30K    3000K	277    277V	
	L1L20    2078 lm/31w		35K    3500K	347    347V	
	<u>True Amber</u>		40K    4000K	480    480V	
	L1LK2A    301 lm/12w¹		AMB    Wavelengths: 585nm to 597nm	MVOLT    120V-277V	
	Delivered lumens calculated at 4000K/80CRI except for amber. Type V distribution. Refer to reference table for outputs at other distribution types. Typical power consumption. Refer to LCF table for outputs at other CCTs.		Required field for except with LVR option.		

PHOTOCELL	SURGE PROTECTOR	EMERGENCY	SHIELDING ACCESSORIES	LOUVERS
<b>PH</b> Photocell	<b>SP</b> Surge protector	<b>REM7</b> Remote emergency battery, 90 min, 7W <sup>3</sup>	<b>BLS1</b> Blockout shield - one side <sup>7</sup> <b>BLS2</b> Blockout shield - two sides at 90° <sup>4</sup> <b>BLS3</b> Blockout shield - three sides <sup>5</sup>	<b>LVR</b> Glare control louvers with 90° optic lens <sup>6</sup>

*FINISH	WOOD FINISHES <sup>9</sup>	ENVIRONMENT	LESS ANCHOR BOLTS
<b>BKT</b> Jet black <b>BZT</b> Bronze <b>CHT</b> Champagne <b>DGT</b> Gun metal <b>GRT</b> Titanium gray <b>MST</b> Matte silver <b>SGT</b> Steel gray <b>WHT</b> Snow white  <b>CMC</b> Custom matched color <sup>7</sup> <b>RAL</b> RAL color <sup>8</sup>	<b>ADG</b> American douglas <b>BRC</b> Birch <b>CHN</b> Chestnut <b>CRY</b> Cherry <b>KNP</b> Knotty pine <b>MPL</b> Maple <b>OFL</b> Oak <b>RSW</b> Rosewood <b>TEK</b> Teak <b>WLN</b> Walnut	<b>MG</b> Marine grade paint <sup>10</sup>	<b>L/AB</b> Less anchor bolts

### NOTES

\*- Denotes a required field

1- Available only with AMB.

2- For IDA certification compliance, luminaire must be ordered with 3000K or warmer.

3- Remote mount 50ft - 12" square enclosure with access cover. Not available with 347V, 480V, HVOLT or PH. Cable between fixture and remote box is provided by other.

4- Installed on back side when distribution LD2 is selected.

5- Not available with distribution LD2.

6- Not available with any BLS option. Not available with LD2 or LD5.

7- Contact factory to coordinate custom matching color.

8- Specify RAL number.

9- Faux wood finish not applied to the fixture head or accessories. Additional delay required. Not compatible with marine grade paint.

10- Marine grade paint for harsh, coastal environment and exposure to salt water. Additional delay required.

## LUMINIS.COM

Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: info@luminis.com  
260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5


© 2024 Acuity Brands Lighting Canada, Inc. All rights reserved. Specifications subject to change without notice.

## REFERENCE TABLE - LIGHT OUTPUT

SERIES	LIGHT OUTPUT - STATIC WHITE	LIGHT OUTPUT - AMBER
LQ427	<u>Type II</u> <b>L1L10</b> 1186 lm / 14w <b>L1L20</b> 2211 lm / 31w	<u>Type II</u> <b>L1LK2A</b> 320 lm / 12w


## TYPICAL PHOTOMETRY SUMMARY

### LQ427-L1L20-LD2



**Total Lms:** 2211 Lumens  
**Total Input Watts:** 24,7 W  
**Efficacy:** 89,3 Lumens/Watt  
**BUG:** B1-U0-G1  
**CCT/CRI:** 4000K/80  
**Maximum Candela:** 1753 @ 55°H/29°V

### LQ427-L1L20-LD5



**Total Lms:** 2078 Lumens  
**Total Input Watts:** 31,3 W  
**Efficacy:** 66,3 Lumens/Watt  
**BUG:** B1-U0-G1  
**CCT/CRI:** 4000K/80  
**Maximum Candela:** 777 @ 19.5°H/55°V

### LUMEN CONVERSION FACTOR (LCF)

CCT	CRI	LCF
2700K	80	0.91
3000K	80	0.94
3500K	80	0.98
4000K	80	1.00

All Photometry shown use the 80CRI 4000K LEDs.  
 Please visit our web site [www.luminis.com](http://www.luminis.com) for complete I.E.S. file.

## LUMINIS.COM

Toll free: (866) 586-4647 | Fax: (514) 683-8872 | Email: [info@luminis.com](mailto:info@luminis.com)  
 260 Labrosse, Pointe-Claire (QC) Canada H9R 5L5

© 2024 Acuity Brands Lighting Canada, Inc. All rights reserved. Specifications subject to change without notice.



## OPTION DETAILS



### BLS1-BLS2-BLS3

Blockout shield available on one side, two sides (at 90°) or three sides.



### LVR

Glare control louvers with 90° optic lens.